

Hypress ONE 1SN (TFD0012 - TFD2012); HyFreeze (TFDL012N); HyCelsius ONE (TFDH012B) ;HyCompressor ONE (TFDC012B)

**ONE**

Hypress One 1SN - EN 853 - SAE100R1AT - ISO 1436

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 15,7                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 5/16"           | 05           | 8        | 0022G05           | 18,0                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 19,7                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 23,4                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 5/8"            | 10           | 16       | 0022G10           | 26,6                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 3/4"            | 12           | 19       | 0022G12           | 30,8                      | One-Piece         | NO SKIVE          |              |              | 32                         |
| 1"              | 16           | 25       | 0022G16           | 38,6                      | One-Piece         | NO SKIVE          |              |              | 40                         |
| 1.1/4"          | 20           | 31       | 0022G20           | 46,0                      | One-Piece         | NO SKIVE          |              |              | 47                         |
| 1.1/2"          | 24           | 38       | 0022G24           | 54,2                      | One-Piece         | NO SKIVE          |              |              | 57                         |
| 2"              | 32           | 51       | 0022G32           | 67,6                      | One-Piece         | NO SKIVE          |              |              | 64                         |

Hypress TWO 2SN (TFD0022 - TFD2022; HyFreeze (TFDL022N); HyCelsius TWO (TFDH022B)

**TWO**

Hypress Two 2SN - EN 853 - SAE100R2AT - ISO 1436

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 16,9                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 5/16"           | 05           | 8        | 0022G05           | 18,8                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 20,5                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 24,4                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 5/8"            | 10           | 16       | 0022G10           | 27,7                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 3/4"            | 12           | 19       | 0022G12           | 32,1                      | One-Piece         | NO SKIVE          |              |              | 32                         |
| 1"              | 16           | 25       | 0022G16           | 39,6                      | One-Piece         | NO SKIVE          |              |              | 40                         |
| 1.1/4"          | 20           | 31       | 0022G20           | 48,6                      | One-Piece         | NO SKIVE          |              |              | 47                         |
| 1.1/2"          | 24           | 38       | 0022G24           | 56,4                      | One-Piece         | NO SKIVE          |              |              | 57                         |
| 2"              | 32           | 51       | 0022G32           | 69,5                      | One-Piece         | NO SKIVE          |              |              | 64                         |

Hypress 1SC (TFE001K - TFE201K); Longlife 1SC (THE201K - THEY01K);  
LongLift 1SC (THL201K); LongLife Dual 1SC (T2E101K); HyGEAR (THE0G1K)

**1SC**

EN 857 1SC ISO 11237 1SC

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 15,7                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 5/16"           | 05           | 8        | 0022G05           | 17,4                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 19,0                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 23,0                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 5/8"            | 10           | 16       | 0022G10           | 26,6                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 3/4"            | 12           | 19       | 0022G12           | 31,0                      | One-Piece         | NO SKIVE          |              |              | 32                         |
| 1"              | 16           | 25       | 0022G16           | 37,8                      | One-Piece         | NO SKIVE          |              |              | 40                         |
| 1.1/4"          | 20           | 31       | 0022G20           | 45,8                      | One-Piece         | NO SKIVE          |              |              | 47                         |
| 1.1/2"          | 24           | 38       | 0022G24           | 53,2                      | One-Piece         | NO SKIVE          |              |              | 57                         |
| 2"              | 32           | 51       | 0022G32           | 66,4                      | One-Piece         | NO SKIVE          |              |              | 64                         |

Hypress 2SC (TFE202K-TFEY02K-TFEV02K); Longlife 2SC (THE202K-THEY02K-  
THEV02K); LongLift 2SC (THL202K); LongLife Dual 2SC (T2E102K)

**2SC**

EN 857 2SC - ISO 11237 2SC - SAE 100R16

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 16,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 5/16"           | 05           | 8        | 0022G05           | 18,4                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 20,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 23,7                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 5/8"            | 10           | 16       | 0022G10           | 26,8                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 3/4"            | 12           | 19       | 0022G12           | 31,4                      | One-Piece         | NO SKIVE          |              |              | 32                         |
| 1"              | 16           | 25       | 0022G16           | 38,9                      | One-Piece         | NO SKIVE          |              |              | 40                         |
| 1.1/4"          | 20           | 31       | 0022G20           | 47,2                      | One-Piece         | NO SKIVE          |              |              | 47                         |
| 1.1/2"          | 24           | 38       | 0022G24           | 55,0                      | One-Piece         | NO SKIVE          |              |              | 57                         |
| 2"              | 32           | 51       | 0022G32           | 68,0                      | One-Piece         | NO SKIVE          |              |              | 64                         |

## Hypress Easy K 1SC (TFA201KI)

## Easy K 1SC

EN 857 1SC - ISO 11237 1SC

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 15,7                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 5/16"           | 05           | 8        | 0022G05           | 17,4                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 19,0                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 23,0                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 5/8"            | 10           | 16       | 0022G10           | 26,2                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 3/4"            | 12           | 19       | 0022G12           | 31,0                      | One-Piece         | NO SKIVE          |              |              | 32                         |
| 1"              | 16           | 25       | 0022G16           | 37,8                      | One-Piece         | NO SKIVE          |              |              | 40                         |

## Hypress Easy K 2SC (TFA202KI)

## Easy K 2SC

EN 857 2SC - ISO 11237 2SC

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 16,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 5/16"           | 05           | 8        | 0022G05           | 18,4                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 20,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 23,5                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 5/8"            | 10           | 16       | 0022G10           | 26,8                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 3/4"            | 12           | 19       | 0022G12           | 31,4                      | One-Piece         | NO SKIVE          |              |              | 32                         |
| 1"              | 16           | 25       | 0022G16           | 38,9                      | One-Piece         | NO SKIVE          |              |              | 40                         |

## TFS0017

## R17

SAE 100 R17 (3000 PSI) - ISO 11237 R17

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 15,7                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 5/16"           | 05           | 8        | 0022G05           | 17,4                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 19,0                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |

TFS0017

**R17**

SAE 100 R17 (3000 PSI) - ISO 11237 R17

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/2"            | 08           | 12       | 0022G08           | 23,4                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 5/8"            | 10           | 16       | 0022G10           | 26,8                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 3/4"            | 12           | 19       | 0022G12           | 31,4                      | One-Piece         | NO SKIVE          |              |              | 32                         |
| 1"              | 16           | 25       | 0022G16           | 39,3                      | One-Piece         | NO SKIVE          |              |              | 40                         |

Marathon 2SC (THE2M2K-THEYM2K-THEVM2K)

**2MC**

EN 857 2SC

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 16,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 5/16"           | 05           | 8        | 0022G05           | 18,4                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 20,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 24,0                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 5/8"            | 10           | 16       | 0022G10           | 26,8                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 3/4"            | 12           | 19       | 0022G12           | 31,4                      | One-Piece         | NO SKIVE          |              |              | 32                         |
| 1"              | 16           | 25       | 0022G16           | 39,4                      | One-Piece         | NO SKIVE          |              |              | 40                         |

Jet 1SC (TFN001K - TFB001K); JetPlus 1SC (THN001K - THB001K)

**JET / JET PLUS 1SC**

JET / JET PLUS 1SC

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 15,7                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 5/16"           | 05           | 8        | 0022G05           | 17,4                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 19,0                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 23,0                      | One-Piece         | NO SKIVE          |              |              | 25                         |

Jet 2SC; TFN002K; TFB002K; JetPlus 2SC; THN002K; THB002K

## JET / JET PLUS 2SC

JET / JET PLUS 2SC

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 16,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 5/16"           | 05           | 8        | 0022G05           | 18,4                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 20,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 24,0                      | One-Piece         | NO SKIVE          |              |              | 25                         |

HyWasher (TEB0E42-TEN0E42); HyWasher Plus (TCB2E42-TCN2E42)

## Hy-W / Hy-W Plus 420

HyWasher 420 bar

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 16,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 5/16"           | 05           | 8        | 0022G05           | 18,4                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 19,7                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 23,8                      | One-Piece         | NO SKIVE          |              |              | 25                         |

Hytruck 200 bar (TTRK200)

## HYTRUCK 200

HyTruck 200

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4"            | 12           | 19       | 0022G12           | 31,0                      | One-Piece         | NO SKIVE          |              |              | 32                         |
| 1"              | 16           | 25       | 0022G16           | 38,9                      | One-Piece         | NO SKIVE          |              |              | 40                         |

Hytruck 250 bar (TTRK250)

## HYTRUCK 250

HyTruck 250

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4"            | 12           | 19       | 0022G12           | 31,0                      | One-Piece         | NO SKIVE          |              |              | 32                         |

## Hytruck 250 bar (TTRK250)

## HYTRUCK 250

HyTruck 250

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1"              | 16           | 25       | 0022G16           | 38,9                      | One-Piece         | NO SKIVE          |              |              | 40                         |

## Hytruck 350 bar (TTRK350)

## HYTRUCK 350

HyTruck 350

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4"            | 12           | 19       | 0022G12           | 31,4                      | One-Piece         | NO SKIVE          |              |              | 32                         |
| 1"              | 16           | 25       | 0022G16           | 38,9                      | One-Piece         | NO SKIVE          |              |              | 40                         |

## HyGreen R15 (TFDG015-TFDR015)

## R15

ISO 3862 R15 - SAE 100 R15 (6000 PSI)

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4"            | 12           | 19       | BMC4-12           | 37,0                      | One-Piece         | NO SKIVE          |              |              | 46,5                       |
| 1"              | 16           | 25       | BMC4-16           | 47,1                      | One-Piece         | NO SKIVE          |              |              | 61                         |
| 1.1/4"          | 20           | 31       | BMC6-20           | 57,5                      | One-Piece         | NO SKIVE          |              |              | 67,5                       |
| 1.1/2"          | 24           | 38       | BMC6-24           | 64,8                      | One-Piece         | NO SKIVE          |              |              | 72                         |
| 2"              | 32           | 51       | BMC6-32           | 80,5                      | One-Piece         | NO SKIVE          |              |              | 96                         |

## HyGreen R13 (TFDG013 - TFDR013)

## R13

EN 856 R13 - SAE 100 R13 (5000 PSI) - ISO 3862 R13

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4"            | 12           | 19       | BMC4-12           | 37,0                      | One-Piece         | NO SKIVE          |              |              | 46,5                       |
| 1"              | 16           | 25       | BMC4-16           | 47,1                      | One-Piece         | NO SKIVE          |              |              | 61                         |
| 1.1/4"          | 20           | 31       | BMC6-20           | 57,5                      | One-Piece         | NO SKIVE          |              |              | 67,5                       |

## HyGreen R13 (TFDG013 - TFDRO13)

### R13

EN 856 R13 - SAE 100 R13 (5000 PSI) - ISO 3862 R13

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1.1/2"          | 24           | 38       | BMC6-24           | 64,8                      | One-Piece         | NO SKIVE          |              |              | 72                         |
| 2"              | 32           | 51       | BMC6-32           | 80,5                      | One-Piece         | NO SKIVE          |              |              | 96                         |

## HyGreen 4SH (TFDR4SH - TFDG4SH)

### 4SH

EN 856 4SH - ISO 3862 4SH

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4"            | 12           | 19       | BMC4-12           | 37,0                      | One-Piece         | NO SKIVE          |              |              | 46,5                       |
|                 |              |          | ONI4-12           | 36,8                      | One-Piece         | NO SKIVE          |              |              | 41,5                       |
| 1"              | 16           | 25       | BMC4-16           | 46,7                      | One-Piece         | NO SKIVE          |              |              | 61                         |
|                 |              |          | ONI4-16           | 44,6                      | One-Piece         | NO SKIVE          |              |              | 49                         |
| 1.1/4"          | 20           | 31       | BMC6-20           | 54,5                      | One-Piece         | NO SKIVE          |              |              | 67,5                       |
|                 |              |          | ONI4-20           | 51,7                      | One-Piece         | NO SKIVE          |              |              | 57,5                       |
| 1.1/2"          | 24           | 38       | BMC6-24           | 61,0                      | One-Piece         | NO SKIVE          |              |              | 72                         |
| 2"              | 32           | 51       | BMC6-32           | 77,5                      | One-Piece         | NO SKIVE          |              |              | 96                         |

## Hypress 4SP (TFDM4SP)

### 4SP

EN 856 4SP - ISO 3862 4SP

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4"            | 12           | 19       | BMC4-12           | 37,0                      | One-Piece         | NO SKIVE          |              |              | 46,5                       |
| 1"              | 16           | 25       | BMC4-16           | 46,8                      | One-Piece         | NO SKIVE          |              |              | 61                         |
| 1.1/4"          | 20           | 31       | BMC6-20           | 57,5                      | One-Piece         | NO SKIVE          |              |              | 67,5                       |
| 1.1/2"          | 24           | 38       | BMC6-24           | 64,0                      | One-Piece         | NO SKIVE          |              |              | 72                         |

## HySOpress 3k (TIB2021-TIBY021-TIBV021)

**IB21**

HySOpress 3k ISO 18752 / Braided

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 15,7                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 5/16"           | 05           | 8        | 0022G05           | 17,4                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 19,0                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 23,5                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 5/8"            | 10           | 16       | 0022G10           | 26,8                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 3/4"            | 12           | 19       | 0022G12           | 31,4                      | One-Piece         | NO SKIVE          |              |              | 32                         |
| 1"              | 16           | 25       | 0022G16           | 38,9                      | One-Piece         | NO SKIVE          |              |              | 40                         |

## HySOpress 4k (TIB2028-TIBY028-TIBV028)

**IB28**

HySOpress ISO 18752 / Braided

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 16,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 20,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 23,7                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 5/8"            | 10           | 16       | 0022G10           | 26,8                      | One-Piece         | NO SKIVE          |              |              | 25                         |
| 3/4"            | 12           | 19       | 0022G12           | 31,4                      | One-Piece         | NO SKIVE          |              |              | 32                         |

## HySOpress 5k (TIB2035-TIBY035-TIBV035)

**IB35**

HySOpress 5k ISO 18752 / Braided

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 16,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 3/8"            | 06           | 10       | 0022G06           | 20,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |
| 1/2"            | 08           | 12       | 0022G08           | 24,0                      | One-Piece         | NO SKIVE          |              |              | 25                         |



## HySOpress 6k (TIB2042-TIBY042-TIBV042)

**IB42**

HySOpress 6k ISO 18752 / Braided

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4"            | 04           | 6        | 0022G04           | 16,1                      | One-Piece         | NO SKIVE          |              |              | 22,5                       |

## HySOpress 3k (TIS0021-TISM021-TISV021)

**IS21**

HySOpress 3k ISO 18752 / Spiral

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1.1/4"          | 20           | 31       | ONI4-20           | 51,7                      | One-Piece         | NO SKIVE          |              |              | 57,5                       |
| 2"              | 32           | 51       | ONI4-32           | 73,8                      | One-Piece         | NO SKIVE          |              |              |                            |

## HySOpress 4k (TIS0028-TISM028-TISM028)

**IS28**

HySOpress 4k ISO 18752 / Spiral

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/8"            | 06           | 10       | ONI4-06           | 24,3                      | One-Piece         | NO SKIVE          |              |              | 29,5                       |
| 1/2"            | 08           | 12       | ONI4-08           | 26,9                      | One-Piece         | NO SKIVE          |              |              | 30                         |
| 5/8"            | 10           | 16       | ONI4-10           | 30,8                      | One-Piece         | NO SKIVE          |              |              | 38                         |
| 3/4"            | 12           | 19       | ONI4-12           | 36,2                      | One-Piece         | NO SKIVE          |              |              | 41,5                       |
| 1"              | 16           | 25       | ONI4-16           | 44,0                      | One-Piece         | NO SKIVE          |              |              | 49                         |
| 1.1/4"          | 20           | 31       | ONI4-20           | 51,7                      | One-Piece         | NO SKIVE          |              |              | 57,5                       |
| 1.1/2"          | 24           | 38       | ONI4-24           | 59,4                      | One-Piece         | NO SKIVE          |              |              | 65,5                       |
| 2"              | 32           | 51       | ONI4-32           | 74,3                      | One-Piece         | NO SKIVE          |              |              |                            |

## HySOpress 5k (TIS0035-TISM035-TISM035)

**IS35**

HySOpress 5k ISO 18752 / Spiral

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|

## HySopress 5k (TIS0035-TISM035-TISM035)

**IS35**

HySopress 5k ISO 18752 / Spiral

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/8"            | 06           | 10       | ONI4-06           | 24,3                      | One-Piece         | NO SKIVE          |              |              | 29,5                       |
| 1/2"            | 08           | 12       | ONI4-08           | 26,9                      | One-Piece         | NO SKIVE          |              |              | 30                         |
| 5/8"            | 10           | 16       | ONI4-10           | 30,8                      | One-Piece         | NO SKIVE          |              |              | 38                         |
| 3/4"            | 12           | 19       | ONI4-12           | 36,2                      | One-Piece         | NO SKIVE          |              |              | 41,5                       |
| 1"              | 16           | 25       | ONI4-16           | 44,0                      | One-Piece         | NO SKIVE          |              |              | 49                         |
| 1.1/4"          | 20           | 31       | ONI4-20           | 52,1                      | One-Piece         | NO SKIVE          |              |              | 57,5                       |
| 1.1/2"          | 24           | 38       | ONI4-24           | 59,2                      | One-Piece         | NO SKIVE          |              |              | 65,5                       |

## HySopress 6k (TIS0042-TISM042-TISV042)

**IS42**

HySopress 6k ISO 18752 / Spiral

| Pollici<br>Inch | Dash<br>Dash | DN<br>DN | Ghiera<br>Ferrule | Ø Pressatura<br>Swaging Ø | Inserto<br>Insert | Pelatura<br>Skive | Est.<br>Ext. | Int.<br>Int. | Lung. Ins.<br>Insert Depth |
|-----------------|--------------|----------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1.1/2"          | 24           | 38       | ONI6-24           | 62,2                      | One-Piece         | NO SKIVE          |              |              |                            |
| 3/8"            | 06           | 10       | ONI4-06           | 24,3                      | One-Piece         | NO SKIVE          |              |              | 29,5                       |
| 1/2"            | 08           | 12       | ONI4-08           | 26,9                      | One-Piece         | NO SKIVE          |              |              | 30                         |
| 5/8"            | 10           | 16       | ONI4-10           | 30,8                      | One-Piece         | NO SKIVE          |              |              | 38                         |
| 3/4"            | 12           | 19       | ONI4-12           | 36,8                      | One-Piece         | NO SKIVE          |              |              | 41,5                       |
| 1"              | 16           | 25       | ONI4-16           | 44,6                      | One-Piece         | NO SKIVE          |              |              | 49                         |
| 1.1/4"          | 20           | 31       | ONI6-20           | 54,7                      | One-Piece         | NO SKIVE          |              |              | 57,5                       |