

Accessories

in

SR1P - Hose storage rack



Product features and specifications

MATERIAL	Steel
SURFACE TREATMENT	Powder coating
DIMENSIONS LxWxH [mm]	1000x1000x2000
NOTE	4 steering wheels, of which 2 braked 2 shelves rests fittings 18 zinc pivots included

SR07 - Seven slots hose reel

Product features and specifications



MATERIAL	Steel
SURFACE TREATMENT	Zinc plated
WEIGHT [Kg]	160
DIMENSIONS LxWxH [mm]	1250 x 1050 x 2200
MAX COIL NUMBER	7
MAX COIL WEIGHT [Kg]	80
MIN INT. COIL Ø [mm]	300
MAX EXT COIL Ø [mm]	850
MAX COIL HEIGHT [mm]	200
NOTE	Single rotating hose reel

COILS MAX LENGHT (25N HOSE) SIZE	MAX LENGTH [m]
05	260
06	200
08	180
10	140
12	120
16	95
20	80
25	55

SR - One/two disk manual hose coiler/uncoiler

Description

Trolley to facilitate the operations of manual winding and unwinding coils of hydraulic hoses. It is available in both single and double disk versions.. It is possible to adjust the internal diameter of coils in the following size: 200 mm, 250 mm, 325 mm and 400 mm. By tilting the plane it is possible to lock it in the more convenient position in order to make easy the coils loading and unloading operations. The rotating plates are equipped with an adjustable brake system to provide more or less resistance to the rotary movement and are also equipped with shaped slots arranged at 120° to facilitate the binding of the coils.

SR1R/SR2R- coiler/uncoiler



SR1R



SR2R

Product features and specifications

PART NUMBER	SR1R	SR2R
N° OF DISKS	1	2
DISK DIAMETER [mm]	1000	
DIMENSIONS LxWxH [mm]	1100x1000x1000	2276x1000x1000
WEIGHT [Kg]	90	180
MAX LOAD ON SINGLE DISK [Kg]	250	
N° OF ROTATING DISK	2	
INTERNAL COILING DIAMETER [mm]	FROM 200 TO 400	

OPTIONAL

Counter meter up to for 2" hoses (cod. CHC2) with support (cod. SRSCM-S)

SR2R1M - Two disk powered hose coiler/uncoiler

Description

Motorized hose reel with double disk allow simplifying the operations of coiling and uncoiling of hydraulic hoses. It is possible to adjust the internal diameter of the skeins in the following size: 200 mm, 250 mm, 325 mm and 400 mm. The motorized version has only one rotating plane connected to a motor to make easy the step of unwinding or winding. It is operated by a foot pedal with the emergency button incorporated. By tilting the plane it is possible to lock it in the best position in order to make easy the loading and unloading of the coils. The rotating planes are equipped with an adjustable pre-load to provide more or less resistance to the rotary movement and are also equipped with shaped slits arranged at 120° to facilitate the binding of the skeins. The meter counter is available as an optional in double winders version and its position is adjustable according to the diameter of the tube to be rolled up. The structure has a large load capacity and stability.



SR2R1M

Product features and specifications

PART NUMBER	SR2R1M
N° OF DISKS	2
DISK DIAMETER [mm]	1000
DIMENSIONS LxWxH [mm]	2276x1000x1000
WEIGHT [kg]	230
MAX LOAD ON SINGLE DISK[kg]	250
N° OF ROTATING DISK	1 motorized 1 conducted
INTERNAL COILING DIAMETER [mm]	FROM 200 TO 400
MOTOR	0.35 kW 230/400 V - 50Hz

OPTIONAL

Meter counter for 2" diameter hoses (cod. CHC2) with support (cod. SRSCM-S)

CHC2 - Counter Meter

Description

Tool for measuring hose length up to 2" , it is ideal for hose coiling/uncoiling and cutting workstation. It can also be mounted on hose cutting machine without its base. The base can be fixed to the floor and the height can be adjusted for better ergonomics.



CHC2 + CHBC

Product features and specifications

MAX MEASURABLE LENGHT [m]	9999.99
MAX HOSE SPEED [m/min]	200
HOSE DIAMETER [inch]	3/16" to 2"
WEIGHT CHC2 [kg]	6
WEIGHT CHBC [kg]	7

OPTIONAL

Base (code CHBC)

ASP-IFS-2PF – Air cleaner system

ASP-IFS-2PF Air cleaner unit specific for fumes 0,37kW 400V 50Hz, designed to be combined with CH80/CH80P cutting machines. Package includes centrifuge, pocket, HEPA filters and flexible hoses for connecting it to cutter.

Description

ASP-IFS-2PF air cleaner system is suited solution for working with CH80 e CH80P cutting machines; it let to clean air from fumes generated by hydraulic hose cuttings, guaranteeing a healthy working environment. Machine is equipped with centrifuge, pocket, HEPA filters and flexible hoses for quick connecting it to cutter. It is possible to suit it with activated carbon cell (optional).



ASP-IFS-2PF

Product features and specifications

FILTERING STAGES	TYPE	EFFICIENCY GRADE
Pre	Metallic	> 95%
1°	Centrifuge filter auto-cleaning	
2°	Pocket filter with coalescence effect	Fino a 95%
3°	HEPA filter	Fino a 99,995%
(Optional)	Activated carbon cell	

MOTOR [kW]	0.37
ELECTRICAL CONFIGURATIONS	400V 3PH 50Hz
MAX FLOW RATE [m ³ /h]	500
NOISE [dB]	67
EXTRACTION PORT SIZE [mm]	Ø100
NET WEIGHT [kg]	43
DIMENSIONS LxWxH [mm]	370x370x770

OPTIONAL

Activated carbon cell (cod. CELL-CAAT)

HSMA2/HSMB1 - Oven for heat-shrink caps

Description

Oven for heating shrink caps to be applied on ends of I.M.M. hoses, suited to protect them from external contamination.



HSMB1



HSMA2

Product features and specifications

PART NUMBER	HSMA2	HSMB1
VERSION	Manual, with support	Bench mounted
WEIGHT [kg]	2	3
DIMENSIONS LxWxH [mm]	480x180x320	480x150x220
MATERIAL	stainless steel	
VOLTAGE [V]	230	
POWER [W]	1000	

MHSXA001 - Universal hose splitter for twin and multiline hoses

Description

An easy-to-use twin hose splitter, it has a basic profile that allows fixing it to any vice. To change blade is very easy; this Al device is lightweight and not subject to corrosive effects due to machine wear.



Product features and specifications

WEIGHT [kg]	2.29
-------------	------

DSTH - Hose splitter bricks for twin and multiline hoses

Description

The DSTH bricks are practical and functional tools, they are indispensable to divide twin and multiline hoses (15C and 25C). There is a specific module for each size, which can be purchased separately depending on the application for which it is suitable.

- For 15C and 25C hoses up to size 12.
- Effective and easy to use equipment.
- Bricks can be ordered individually depending on the application.



Product features and specifications

PART NUMBER	DESCRIPTION
DSTH1K04	TWIN AND MULTILINE HOSE SPLITTER BRICK FOR - 15C06
DSTH1K05-2K04	TWIN AND MULTILINE HOSE SPLITTER BRICK FOR - 15C08-25C06
DSTH1K06-2K05	TWIN AND MULTILINE HOSE SPLITTER BRICK FOR - 15C10-25C08
DSTH1K08	TWIN AND MULTILINE HOSE SPLITTER BRICK FOR - 15C12
DSTH2K06	TWIN AND MULTILINE HOSE SPLITTER BRICK FOR - 25C10
DSTH2K08	TWIN AND MULTILINE HOSE SPLITTER BRICK FOR - 25C12
DSTH2K08-M	TWIN AND MULTILINE HOSE SPLITTER BRICK FOR - 25C12 MARATHON