

Hypress ONE 1SN: TFD0012;TFD2012; HyFreeze: TFDL012N

ONE

Hypress One 1SN - EN 853 - SAE100R1AT - ISO 1436

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 15,7 | One-Piece | NO SKIVE | | | 22,5 |
| 5/16" | 05 | 0022G05 | 18,0 | One-Piece | NO SKIVE | | | 22,5 |
| 3/8" | 06 | 0022G06 | 19,7 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 23,4 | One-Piece | NO SKIVE | | | 25 |
| 5/8" | 10 | 0022G10 | 26,6 | One-Piece | NO SKIVE | | | 25 |
| 3/4" | 12 | 0022G12 | 30,8 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 38,6 | One-Piece | NO SKIVE | | | 40 |
| 1.1/4" | 20 | 0022G20 | 46,0 | One-Piece | NO SKIVE | | | 47 |
| 1.1/2" | 24 | 0022G24 | 54,2 | One-Piece | NO SKIVE | | | 57 |
| 2" | 32 | 0022G32 | 67,6 | One-Piece | NO SKIVE | | | 64 |

Hypress TWO 2SN: TFD0022;TFD2022; HyFreeze: TFDL022N

TWO

Hypress Two 2SN - EN 853 - SAE100R2AT - ISO 1436

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 16,9 | One-Piece | NO SKIVE | | | 22,5 |
| 5/16" | 05 | 0022G05 | 18,8 | One-Piece | NO SKIVE | | | 22,5 |
| 3/8" | 06 | 0022G06 | 20,5 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 24,4 | One-Piece | NO SKIVE | | | 25 |
| 5/8" | 10 | 0022G10 | 27,7 | One-Piece | NO SKIVE | | | 25 |
| 3/4" | 12 | 0022G12 | 32,1 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 39,6 | One-Piece | NO SKIVE | | | 40 |
| 1.1/4" | 20 | 0022G20 | 48,6 | One-Piece | NO SKIVE | | | 47 |
| 1.1/2" | 24 | 0022G24 | 56,4 | One-Piece | NO SKIVE | | | 57 |
| 2" | 32 | 0022G32 | 69,5 | One-Piece | NO SKIVE | | | 64 |

Hypress 1SC: TFE001K; TFE201K; Hipac 1SC: THE001K; Longlife 1SC: THE201K;
LongLift 1SC: THL101K; THL201K; LongLife Dual 1SC: T2E101K

1SC

EN 857 1SC ISO 11237 1SC

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 15,7 | One-Piece | NO SKIVE | | | 22,5 |
| 5/16" | 05 | 0022G05 | 17,4 | One-Piece | NO SKIVE | | | 22,5 |

IMM SWAGING CHART

Tabella dei diametri di pressatura consigliati
Chart of recommended swaging diameters

Revisione: Rev. R12.9 del
11/09/2023

Emessa da: Mauro

Approvata da: Lorenzo Panzone

Hypress 1SC: TFE001K; TFE201K; Hipac 1SC: THE001K; Longlife 1SC: THE201K;
LongLift 1SC: THL101K; THL201K; LongLife Dual 1SC: T2E101K

1SC

EN 857 1SC ISO 11237 1SC

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/8" | 06 | 0022G06 | 19,0 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 23,2 | One-Piece | NO SKIVE | | | 25 |
| 5/8" | 10 | 0022G10 | 26,6 | One-Piece | NO SKIVE | | | 25 |
| 3/4" | 12 | 0022G12 | 31,0 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 37,8 | One-Piece | NO SKIVE | | | 40 |
| 1.1/4" | 20 | 0022G20 | 45,8 | One-Piece | NO SKIVE | | | 47 |
| 1.1/2" | 24 | 0022G24 | 53,2 | One-Piece | NO SKIVE | | | 57 |
| 2" | 32 | 0022G32 | 66,4 | One-Piece | NO SKIVE | | | 64 |

Hypress 2SC: TFE002K; TFE202K; Hipac 2SC: THE002K; THEM02K; Longlife 2SC: THE202K;
LongLift 2SC: THL102K; THL202K; LongLife Dual 2SC: T2E101K

2SC

EN 857 2SC - ISO 11237 2SC - SAE 100R16

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 16,7 | One-Piece | NO SKIVE | | | 22,5 |
| 5/16" | 05 | 0022G05 | 18,4 | One-Piece | NO SKIVE | | | 22,5 |
| 3/8" | 06 | 0022G06 | 20,1 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 24,3 | One-Piece | NO SKIVE | | | 25 |
| 5/8" | 10 | 0022G10 | 26,8 | One-Piece | NO SKIVE | | | 25 |
| 3/4" | 12 | 0022G12 | 31,4 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 38,9 | One-Piece | NO SKIVE | | | 40 |
| 1.1/4" | 20 | 0022G20 | 47,2 | One-Piece | NO SKIVE | | | 47 |
| 1.1/2" | 24 | 0022G24 | 55,0 | One-Piece | NO SKIVE | | | 57 |
| 2" | 32 | 0022G32 | 68,0 | One-Piece | NO SKIVE | | | 64 |

Hypress Easy K 1SC: TFA201KI

Easy K 1SC

EN 857 1SC - ISO 11237 1SC

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 15,7 | One-Piece | NO SKIVE | | | 22,5 |
| 5/16" | 05 | 0022G05 | 17,4 | One-Piece | NO SKIVE | | | 22,5 |
| 3/8" | 06 | 0022G06 | 19,0 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 23,2 | One-Piece | NO SKIVE | | | 25 |
| 5/8" | 10 | 0022G10 | 26,2 | One-Piece | NO SKIVE | | | 25 |

Hypress Easy K 1SC; TFA201KI

Easy K 1SC

EN 857 1SC - ISO 11237 1SC

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4" | 12 | 0022G12 | 31,0 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 37,8 | One-Piece | NO SKIVE | | | 40 |

Hypress Easy K 2SC: TFA202KI

Easy K 2SC

EN 857 2SC - ISO 11237 2SC

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 16,7 | One-Piece | NO SKIVE | | | 22,5 |
| 5/16" | 05 | 0022G05 | 18,4 | One-Piece | NO SKIVE | | | 22,5 |
| 3/8" | 06 | 0022G06 | 20,1 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 23,5 | One-Piece | NO SKIVE | | | 25 |
| 5/8" | 10 | 0022G10 | 26,8 | One-Piece | NO SKIVE | | | 25 |
| 3/4" | 12 | 0022G12 | 31,4 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 38,9 | One-Piece | NO SKIVE | | | 40 |

TFS0017

R17

SAE 100 R17 (3000 PSI) - ISO 11237 R17

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 15,7 | One-Piece | NO SKIVE | | | 22,5 |
| 5/16" | 05 | 0022G05 | 17,4 | One-Piece | NO SKIVE | | | 22,5 |
| 3/8" | 06 | 0022G06 | 19,0 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 23,6 | One-Piece | NO SKIVE | | | 25 |
| 5/8" | 10 | 0022G10 | 26,8 | One-Piece | NO SKIVE | | | 25 |
| 3/4" | 12 | 0022G12 | 31,4 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 39,9 | One-Piece | NO SKIVE | | | 40 |

IMM SWAGING CHART

Tabella dei diametri di pressatura consigliati
Chart of recommended swaging diameters

Revisione: Rev. R12.9 del
11/09/2023

Emessa da: Mauro

Approvata da: Lorenzo Panzone

Marathon 2SC: THE0M2K; THEM2K; THE2M2K

2MC

EN 857 2SC

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 16,7 | One-Piece | NO SKIVE | | | 22,5 |
| 5/16" | 05 | 0022G05 | 18,4 | One-Piece | NO SKIVE | | | 22,5 |
| 3/8" | 06 | 0022G06 | 20,1 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 24,3 | One-Piece | NO SKIVE | | | 25 |
| 5/8" | 10 | 0022G10 | 26,8 | One-Piece | NO SKIVE | | | 25 |
| 3/4" | 12 | 0022G12 | 31,4 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 39,4 | One-Piece | NO SKIVE | | | 40 |

Jet 1SC: TFN001K; TFB001K; JetPlus 1SC: THN001K; THB001K

JET / JET PLUS 1SC

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 15,7 | One-Piece | NO SKIVE | | | 22,5 |
| 5/16" | 05 | 0022G05 | 17,4 | One-Piece | NO SKIVE | | | 22,5 |
| 3/8" | 06 | 0022G06 | 19,0 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 23,2 | One-Piece | NO SKIVE | | | 25 |

Jet 2SC: TFN002K; TFB002K; JetPlus 2SC: THN002K; THB002K

JET / JET PLUS 2SC

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 16,7 | One-Piece | NO SKIVE | | | 22,5 |
| 5/16" | 05 | 0022G05 | 18,4 | One-Piece | NO SKIVE | | | 22,5 |
| 3/8" | 06 | 0022G06 | 20,1 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 24,3 | One-Piece | NO SKIVE | | | 25 |

TSW2280

SEWERJET 280

SewerJet 280 bar

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|

TSW2280

SEWERJET 280

SewerJet 280 bar

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/8" | 06 | 0022G06 | 19,0 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 24,3 | One-Piece | NO SKIVE | | | 25 |
| 3/4" | 12 | 0022G12 | 31,4 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 38,9 | One-Piece | NO SKIVE | | | 40 |
| 1.1/4" | 20 | 0022G20 | 47,2 | One-Piece | NO SKIVE | | | 47 |

Hytruck 200 bar: TTRK200

HYTRUCK 200

HyTruck 200

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4" | 12 | 0022G12 | 31,0 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 38,9 | One-Piece | NO SKIVE | | | 40 |

Hytruck 250 bar: TTRK250

HYTRUCK 250

HyTruck 250

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4" | 12 | 0022G12 | 31,0 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 38,9 | One-Piece | NO SKIVE | | | 40 |

Hytruck 350 bar: TTRK350

HYTRUCK 350

HyTruck 350

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4" | 12 | 0022G12 | 31,4 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 38,9 | One-Piece | NO SKIVE | | | 40 |

HyGreen R15: TFDG015;TFDR015
R15

ISO 3862 R15 - SAE 100 R15 (6000 PSI)

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4" | 12 | BMC4-12 | 37,0 | One-Piece | NO SKIVE | | | 46,5 |
| 1" | 16 | BMC4-16 | 47,1 | One-Piece | NO SKIVE | | | 61 |
| 1.1/4" | 20 | BMC6-20 | 57,5 | One-Piece | NO SKIVE | | | 67,5 |
| 1.1/2" | 24 | BMC6-24 | 64,8 | One-Piece | NO SKIVE | | | 72 |
| 2" | 32 | BMC6-32 | 80,5 | One-Piece | NO SKIVE | | | 96 |

HyGreen R13: TFDG013; TFDR013
R13

EN 856 R13 - SAE 100 R13 (5000 PSI) - ISO 3862 R13

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4" | 12 | BMC4-12 | 37,0 | One-Piece | NO SKIVE | | | 46,5 |
| 1" | 16 | BMC4-16 | 47,1 | One-Piece | NO SKIVE | | | 61 |
| 1.1/4" | 20 | BMC6-20 | 57,5 | One-Piece | NO SKIVE | | | 67,5 |
| 1.1/2" | 24 | BMC6-24 | 64,8 | One-Piece | NO SKIVE | | | 72 |
| 2" | 32 | BMC6-32 | 80,5 | One-Piece | NO SKIVE | | | 96 |

Hypress 4SH: TFD4SH; TFD04SH; HyGreen 4SH: TFDG4SH; TFDR4SH
4SH

EN 856 4SH - ISO 3862 4SH

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4" | 12 | BMC4-12 | 37,0 | One-Piece | NO SKIVE | | | 46,5 |
| 1" | 16 | BMC4-16 | 46,7 | One-Piece | NO SKIVE | | | 61 |
| 1.1/4" | 20 | BMC6-20 | 54,5 | One-Piece | NO SKIVE | | | 67,5 |
| 1.1/2" | 24 | BMC6-24 | 61,0 | One-Piece | NO SKIVE | | | 72 |
| 2" | 32 | BMC6-32 | 77,5 | One-Piece | NO SKIVE | | | 96 |

Hypress 4SP: TFD4SP; TFD04SP
4SP

EN 856 4SP - ISO 3862 4SP

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|

Hypress 4SP; TFDM4SP; TFD04SP
4SP

EN 856 4SP - ISO 3862 4SP

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/4" | 12 | BMC4-12 | 37,0 | One-Piece | NO SKIVE | | | 46,5 |
| 1" | 16 | BMC4-16 | 46,8 | One-Piece | NO SKIVE | | | 61 |
| 1.1/4" | 20 | BMC6-20 | 57,5 | One-Piece | NO SKIVE | | | 67,5 |
| 1.1/2" | 24 | BMC6-24 | 64,0 | One-Piece | NO SKIVE | | | 72 |

Hysoflex 3k: TIB2021;TIBY021
IB21

Hysoflex 3k ISO 18752 / Braided

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 15,7 | One-Piece | NO SKIVE | | | 22,5 |
| 5/16" | 05 | 0022G05 | 17,4 | One-Piece | NO SKIVE | | | 22,5 |
| 3/8" | 06 | 0022G06 | 19,0 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 23,5 | One-Piece | NO SKIVE | | | 25 |
| 5/8" | 10 | 0022G10 | 26,8 | One-Piece | NO SKIVE | | | 25 |
| 3/4" | 12 | 0022G12 | 31,4 | One-Piece | NO SKIVE | | | 32 |
| 1" | 16 | 0022G16 | 39,9 | One-Piece | NO SKIVE | | | 40 |

Hysoflex 4k: TIB2028;TIBY028
IB28

Hysoflex 4k ISO 18752 / Braided

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 16,7 | One-Piece | NO SKIVE | | | 22,5 |
| 3/8" | 06 | 0022G06 | 20,1 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 24,3 | One-Piece | NO SKIVE | | | 25 |
| 5/8" | 10 | 0022G10 | 26,8 | One-Piece | NO SKIVE | | | 25 |
| 3/4" | 12 | 0022G12 | 31,4 | One-Piece | NO SKIVE | | | 32 |

Hysoflex 5k: TIB2035;TIBY035

IB35

Hysoflex 5k ISO 18752 / Braided

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 16,7 | One-Piece | NO SKIVE | | | 22,5 |
| 3/8" | 06 | 0022G06 | 20,1 | One-Piece | NO SKIVE | | | 22,5 |
| 1/2" | 08 | 0022G08 | 24,3 | One-Piece | NO SKIVE | | | 25 |

Hysoflex 6k: TIB2042;TIBY042

IB42

Hysoflex 6k ISO 18752 / Braided

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1/4" | 04 | 0022G04 | 16,7 | One-Piece | NO SKIVE | | | 22,5 |

Hysoflex 3k: TIS0021;TISM021

IS21

Hysoflex 3k ISO 18752 / Spiral

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1.1/4" | 20 | ON14-20 | 51,7 | One-Piece | NO SKIVE | | | 57,5 |

Hysoflex 4k: TIS0028;TISM028

IS28

Hysoflex 4k ISO 18752 / Spiral

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/8" | 06 | ON14-06 | 24,3 | One-Piece | NO SKIVE | | | 29,5 |
| 1/2" | 08 | ON14-08 | 26,9 | One-Piece | NO SKIVE | | | 30 |
| 5/8" | 10 | ON14-10 | 30,8 | One-Piece | NO SKIVE | | | 38 |
| 3/4" | 12 | ON14-12 | 36,2 | One-Piece | NO SKIVE | | | 41,5 |
| 1" | 16 | ON14-16 | 44,0 | One-Piece | NO SKIVE | | | 49 |
| 1.1/4" | 20 | ON14-20 | 51,7 | One-Piece | NO SKIVE | | | 57,5 |
| 1.1/2" | 24 | ON14-24 | 59,4 | One-Piece | NO SKIVE | | | 65,5 |

Hysoflex 5k: TIS0035;TISM035

IS35

Hysoflex 5k ISO 18752 / Spiral

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 3/8" | 06 | ONI4-06 | 24,3 | One-Piece | NO SKIVE | | | 29,5 |
| 1/2" | 08 | ONI4-08 | 26,9 | One-Piece | NO SKIVE | | | 30 |
| 5/8" | 10 | ONI4-10 | 30,8 | One-Piece | NO SKIVE | | | 38 |
| 3/4" | 12 | ONI4-12 | 36,2 | One-Piece | NO SKIVE | | | 41,5 |
| 1" | 16 | ONI4-16 | 44,0 | One-Piece | NO SKIVE | | | 49 |
| 1.1/4" | 20 | ONI4-20 | 52,1 | One-Piece | NO SKIVE | | | 57,5 |
| 1.1/2" | 24 | ONI4-24 | 59,2 | One-Piece | NO SKIVE | | | 65,5 |

Hysoflex 6k: TIS0042;TISM042

IS42

Hysoflex 6k ISO 18752 / Spiral

| Pollici Inch | Dash Dash | Ghiera Ferrule | Ø Pressatura Swaging Ø | Inserto Insert | Pelatura Skive | Est. Ext. | Int. Int. | Lung. Ins. Insert Depth |
|-----------------|--------------|-------------------|---------------------------|-------------------|-------------------|--------------|--------------|----------------------------|
| 1.1/2" | 24 | ONI6-24 | 62,2 | One-Piece | NO SKIVE | | | |
| 3/8" | 06 | ONI4-06 | 24,3 | One-Piece | NO SKIVE | | | 29,5 |
| 1/2" | 08 | ONI4-08 | 26,9 | One-Piece | NO SKIVE | | | 30 |
| 5/8" | 10 | ONI4-10 | 30,8 | One-Piece | NO SKIVE | | | 38 |
| 3/4" | 12 | ONI4-12 | 36,8 | One-Piece | NO SKIVE | | | 41,5 |
| 1" | 16 | ONI4-16 | 44,6 | One-Piece | NO SKIVE | | | 49 |
| 1.1/4" | 20 | ONI6-20 | 54,7 | One-Piece | NO SKIVE | | | 57,5 |