INTERPUMP
FLUID SOLUTIONS

Powered by I.M.M. Hydraulics

Hydraulic Hoses and Accessories

2020

Hydraulic Hoses and Accessories

International Standard
High Performance
Solution for Applications
Thermoplastic Hoses
P.T.F.E. Hoses
Accessories

We have also available the following catalogues

Carbon Steel fittings

One-Piece fittings

Stainless Steel fittings

Premium Adaptors & Tube Connectors

Machines

Quick Couplings

MGQUIX

International Standard



Index

Single / Double Wire Braid

TFD0012



Hypress One 1SN

4

TFD0022



Hypress Two 2SN

5

TFE001K



INTERPUMP Hypress 1SC

6

TFE002K



INTERPUMP Hypress 2SC

7

Isobaric

TFA201K



Hypress EASY K 1SC

8

TFA202K



Hypress EASY K 2SC

9

TFS0017



INTERPUMP Hypress R17

10

Four Wire Spiral

Textile

TFD04SP



Hypress 4SP

11

TFDM4SP



INTERPUMP Hypress 4SP

12

TFSM012



INTERPUMP Hypress R12

13

TFS0006



Hypress UniLock

14

Suction Line

TFE02TE



Hypress 2TE

15

TFS0003



EN854 SAE 100R3

16

TFD03TE



EN 854 3TE

17

TFS0004



INTEPUMP Hy-VA-CUUM - SAE 100R4

18

Dimensions and general characteristics may be changed at any time, data contained here in are only for information purpose only and it does not enlarge, amend or imply any warranty other than provided by us with the product. Any use of the product not in conformance with our instructions may be dangerous.

Single Wire Braid Textile Cover

TFS0005



SAE 100R5

19

Dimensions and general characteristics may be changed at any time, data contained here in are only for information purpose only and it does not enlarge, amend or imply any warranty other than provided by us with the product. Any use of thr product not in conformance with our instructions may be dangerous.

INTERPUMP Hypress One 1SN

TFD0012

APPLICATIONS :





APPLICABLE SPECS. :

EXCEEDS EN 853 1SN - SAE 100R1AT - ISO 1436 1SN

NO-SKIVE hose. Exceed Burst specification. Impulse tested up to double requirement. Reduced bending radius. Lightness.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 steel wire braid.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C (intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFD0012-04	1/4"	6.4	12.8	225	3263	900	13052	50	1.97	0.198	0.133	001C-04
TFD0012-05	5/16"	8.0	14.4	215	3118	860	12472	60	2.36	0.237	0.159	001C-05
TFD0012-06	3/8"	9.5	16.9	180	2610	720	10440	70	2.76	0.301	0.202	001C-06
TFD0012-08	1/2"	12.7	19.9	160	2320	640	9280	90	3.54	0.361	0.242	001C-08
TFD0012-10	5/8"	16.0	23.1	130	1885	520	7540	100	3.94	0.456	0.305	001C-10
TFD0012-12	3/4"	19.0	27.2	105	1523	420	6092	120	4.72	0.574	0.384	001C-12
TFD0012-16	1 "	25.4	35.2	88	1276	352	5104	150	5.91	0.848	0.568	001C-16
TFD0012-20	1.1/4"	31.8	42.6	63	914	250	3625	210	8.27	1.080	0.723	001C-20
TFD0012-24	1.1/2"	38.1	49.6	50	725	200	2900	250	9.84	1.340	0.897	001C-24
TFD0012-32	2"	50.8	63.0	40	580	160	2320	320	12.60	1.840	1.232	001C-32



Available with steel plated braided sleeve version (in case of order use code TFC0012) or stainless steel braided sleeve version (in case of order use code TFI0012)

MARKING: Available also embossed brand version. In case of order use TFD0012N.

INTERPUMP Hypress Two 2SN
TFD0022

APPLICATIONS :





APPLICABLE SPECS. :

EXCEEDS EN 853 2SN - SAE 100R2AT - ISO 1436 2SN

NO-SKIVE hose. Exceed Burst specification. Impulse tested up to double requirement. Reduced bending radius. Lightness.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C (intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFD0022-04	1/4"	6.4	14.3	400	5800	1600	23200	50	1.97	0.323	0.216	0022-04
TFD0022-05	5/16"	8.0	15.9	350	5075	1400	20300	60	2.36	0.380	0.254	0022-05
TFD0022-06	3/8"	9.5	18.5	330	4785	1320	19200	70	2.76	0.474	0.317	0022-06
TFD0022-08	1/2"	12.7	21.5	275	3988	1100	15952	90	3.54	0.561	0.376	0022-08
TFD0022-10	5/8"	16.0	24.7	250	3625	1000	14500	100	3.94	0.623	0.437	0022-10
TFD0022-12	3/4"	19.0	28.8	215	3118	860	12472	120	4.72	0.850	0.569	0022-12
TFD0022-16	1 "	25.4	37.2	165	2393	660	9572	150	5.91	1.279	0.856	0022-16
TFD0022-20	1.1/4"	31.8	46.5	125	1813	500	7250	210	8.27	1.855	1.242	0022-20
TFD0022-24	1.1/2"	38.1	53.1	90	1305	360	5220	250	9.84	2.015	1.349	0022-24
TFD0022-32	2"	50.8	65.8	80	1160	320	4640	320	12.60	2.690	1.800	0022-32



Available with steel plated braided sleeve version (in case of order use code TFC0022) or stainless steel braided sleeve version (in case of order use code TFI0022)

Available also embossed brand version. In case of order use TFD0022N.

INTERPUMP Hypress 1SC

TFE001K



APPLICATIONS :



APPLICABLE SPECS. :

EXCEED EN 857 1SC - ISO 11237

NO-SKIVE hose. Exceed Burst specification. Impulse tested up to double requirements.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 steel wire braid.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFE001K-03	3/16"	4.8	10.7	225	3263	900	13050	40	1,57	0.150	0.101	001C-03
TFE001K-04	1/4"	6.4	12.3	225	3263	900	13050	50	1.969	0.182	0.122	001C-04
TFE001K-05	5/16"	8.0	13.5	215	3118	860	12325	55	2.165	0.203	0.136	001C-05
TFE001K-06	3/8"	9.5	15.7	180	2610	720	10440	60	2.362	0.248	0.167	001C-06
TFE001K-08	1/2"	12.7	18.9	160	2320	640	9280	70	2.756	0.341	0.229	001C-08
TFE001K-10	5/8"	16.0	22.4	130	1885	520	7540	90	3.543	0.421	0.283	001C-10
TFE001K-12	3/4"	19.0	25.9	105	1523	420	6090	100	3.937	0.492	0.330	001C-12
TFE001K-16	1 "	25.4	33.7	88	1276	352	5104	180	7.087	0.742	0.499	001C-16

MARKING: Available also embossed brand version. In case of order use code TFE001KN.

INTERPUMP Hypress 1SC EN 857 - DN 12 I.D. 1/2" - W.P. 160 BAR/2320 PSI

INTERPUMP Hypress 2SC
TFE002K

APPLICATIONS :



TYPE APPROVAL :
LLOYD'S



APPLICABLE SPECS. :
EXCEED EN 857 2SC - SAE 100 R16 - ISO 11237

Compact hose with low bend radius (R16). NO-SKIVE solution. Exceed standard Burst requirements. Impulse tested up to double requirements.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.


Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.


Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFE002K-04	1/4"	6.4	13.3	400	5800	1600	23200	50	1.969	0.281	0.189	001C-04
TFE002K-05	5/16"	8.0	14.8	350	5075	1400	20300	55	2.165	0.327	0.220	001C-05
TFE002K-06	3/8"	9.5	17.1	330	4785	1320	19140	65	2.559	0.418	0.281	001C-06
TFE002K-08	1/2"	12.7	20.4	275	3988	1100	15950	90	3.543	0.525	0.353	001C-08
TFE002K-10	5/8"	16.0	23.5	250	3625	1000	14500	100	3.937	0.627	0.421	001C-10
TFE002K-12	3/4"	19.0	27.6	215	3118	860	12470	120	4.724	0.782	0.526	001C-12
TFE002K-16	1 "	25.4	35.8	165	2393	660	9570	150	5.906	1.176	0.790	001C-16

Available also embossed brand version. In case of order use TFE002KN.

Hypress EASY K 1SC
TFA201K



APPLICATIONS :



APPLICABLE SPECS. :
EN 857 1SC - ISO 11237

Compact hose according to EN 857 ISO 11237. NO-SKIVE solution. Smooth cover.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.
Reinforcement: 1 high tensile steel wire braids.
Covering: Smooth synthetic rubber, resistant to oils, fuels and atmospheric conditions
Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.
Operating temperature: from -40 to +100°C, from -40 to +70° C for water based fluids, from 0 to +70°C water.


Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFA201K-04	1/4"	6.4	12.3	225	3263	900	13050	75	2.953	0.182	0.122	001C-04
TFA201K-05	5/16"	8.0	13.5	215	3118	860	12470	85	3.346	0.203	0.136	001C-05
TFA201K-06	3/8"	9.5	15.7	180	2610	720	10440	90	3.543	0.248	0.167	001C-06
TFA201K-08	1/2"	12.7	18.9	160	2320	640	9280	130	5.118	0.341	0.229	001C-08
TFA201K-10	5/8"	16.0	22.4	130	1885	520	7540	150	5.906	0.421	0.283	001C-10
TFA201K-12	3/4"	19.0	25.9	105	1523	420	6090	180	7.087	0.491	0.330	001C-12
TFA201K-16	1 "	25.4	33.7	88	1276	352	5104	230	9.056	0.740	0.499	001C-16

MARKING: Mylar version

Hypress Easy K EN 857 - 1SC DN 19 I.D. 3/4" - W.P. 105 BAR/3118 PSI

Hypress EASY K 2SC
TFA202K

APPLICATIONS :





APPLICABLE SPECS. :
EN 857 2SC - ISO 11237

Compact hose according to EN 857 ISO 11237. NO-SKIVE solution. Smooth cover.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.
Reinforcement: 2 high tensile steel wire braids.
Covering: Smooth synthetic rubber, resistant to oils, fuels and atmospheric conditions.
Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.
Operating temperature: from -40 to +100°C, from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFA202K-04	1/4"	6.4	13.3	400	5800	1600	23200	75	2.953	0.281	0.189	001C-04
TFA202K-05	5/16"	8.0	14.8	350	5075	1400	20300	85	3.346	0.327	0.220	001C-05
TFA202K-06	3/8"	9.5	17.1	330	4785	1320	19140	90	3.543	0.418	0.281	001C-06
TFA202K-08	1/2"	12.7	20.0	275	3988	1100	15950	130	5.118	0.525	0.353	001C-08
TFA202K-10	5/8"	16.0	23.2	250	3625	1000	14500	170	6.693	0.627	0.421	001C-10
TFA202K-12	3/4"	19.0	27.6	215	3118	860	12470	200	7.874	0.782	0.526	001C-12
TFA202K-16	1 "	25.4	35.8	165	2393	660	9570	250	9.843	1.176	0.790	001C-16

Mylar version

Hypress Easy K EN 857 - 2SC DN 6 I.D. 1/4" - W.P. 400 BAR/5800 PSI

INTERPUMP Hypress R17

TFS0017

APPLICATIONS :





APPLICABLE SPECS. :

SAE 100R17 - SAE J 517 - ISO 11237 R17

Isobaric pressure rating 210 bar/3000 psi. No skive compact hose.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: High tensile steel. 1 braid up to size 1/2", 2 braids from size 5/8" onwards.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C (intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS0017-03	3/16"	4.8	10.5	210	3045	840	12180	40	0.787	0.150	0.101	001C-03
TFS0017-04	1/4"	6.4	12.3	210	3045	840	12180	50	1.969	0.185	0.124	001C-04
TFS0017-05	5/16"	7.9	13.5	210	3045	840	12180	55	2.165	0.196	0.132	001C-05
TFS0017-06	3/8"	9.5	15.7	210	3045	840	12180	65	2.559	0.256	0.172	001C-06
TFS0017-08	1/2"	12.7	19.4	210	3045	840	12180	90	3.543	0.378	0.254	001C-08
TFS0017-10	5/8"	16.0	23.5	210	3045	840	12180	100	3.937	0.624	0.419	001C-10
TFS0017-12	3/4"	19.0	27.6	210	3045	840	12180	120	4.724	0.764	0.513	001C-12
TFS0017-16	1 "	25.4	36.2	210	3045	840	12180	150	5.906	1.233	0.829	001C-16

MARKING: Available also embossed brand version. In case of order use code TFS0017N.

INTERPUMP Hypress R17 SAE 100R17 - DN 6 I.D. 1/4" - W.P. 210 BAR/3045 PSI

Hypress 4SP
TFD04SP

APPLICATIONS :





APPLICABLE SPECS. :
EN 856 4SP - ISO 3862 4SP

4 high tensile spiral high flexibility. High ozone and abrasion resistance.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 4 steel wire spirals.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Hydraulic fluids petroleum based (mineral oils), glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C (intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight	
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft
TFD04SP-04	1/4"	6.4	17.8	450	6525	1800	26100	150	5.906	0.592	0.398
TFD04SP-06	3/8"	9.5	21.2	445	6453	1780	25810	180	7.087	0.790	0.531
TFD04SP-08	1/2"	12.7	24.3	415	6018	1660	24070	230	9.055	0.940	0.632
TFD04SP-10	5/8"	16.0	28.0	350	5075	1400	20300	250	9.843	1.125	0.756
***TFD04SP-12	3/4"	19.0	32.0	350	5075	1400	20300	300	11.811	1.497	1.006
***TFD04SP-16	1 "	25.4	39.5	280	4060	1120	16240	340	13.386	2.150	1.445
***TFD04SP-20	1.1/4"	31.8	50.8	210	3045	840	12180	460	18.11	3.157	2.122
***TFD04SP-24	1.1/2"	38.1	57.2	185	2683	740	10730	560	22.047	3.713	2.495
***TFD04SP-32	2 "	50.8	69.8	165	2393	660	9570	660	25.984	4.870	3.273

Available with steel plated braided sleeve version (in case of order use code TFCM4SP) or stainless steel braided sleeve version (in case of order use code TFIM4SP)

***Biological oils compatibility

Available also embossed brand version. In case of order use TFD04SPN.

INTERPUMP Hypress 4SP

TFDM4SP

APPLICATIONS :





TYPE APPROVAL :
MED, DNV - GL, BV, MSHA

APPLICABLE SPECS. :
EN 856 4SP - ISO 3862 4SP

4 high tensile spiral high flexibility. MSHA cover. Exceeding bust requirements.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 4 steel wire spirals.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Hydraulic fluids petroleum based (mineral oils), glicol-water based, water, lubricants.

Operating temperature: from -40 to + 100° C petroleum based fluids (Intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight	
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft
TFDM4SP-04	1/4"	6.4	17.8	450	6525	1800	26100	150	5.906	0.592	0.398
TFDM4SP-06	3/8"	9.5	21.2	445	6453	1780	25810	180	7.087	0.790	0.531
TFDM4SP-08	1/2"	12.7	24.3	415	6018	1660	24070	230	9.055	0.940	0.632
TFDM4SP-10	5/8"	16.0	28.0	350	5075	1400	20300	250	9.843	1.125	0.756
TFDM4SP-12	3/4"	19.0	32.0	350	5075	1400	20300	300	11.811	1.497	1.006
TFDM4SP-16	1 "	25.4	39.5	280	4060	1120	16240	340	13.386	2.150	1.445
TFDM4SP-20	1.1/4"	31.8	50.8	210	3045	840	12180	460	18.11	3.157	2.122
TFDM4SP-24	1.1/2"	38.1	57.2	185	2683	740	10730	560	22.047	3.713	2.495
TFDM4SP-32	2 "	50.8	69.8	165	2393	660	9570	660	25.984	4.870	3.273

Available with steel plated braided sleeve version (in case of order use code TFCM4SP) or stainless steel braided sleeve version (in case of order use code TFIM4SP)

MARKING: Available also embossed brand version. In case of order use code TFDM4SPN.

INTERPUMP Hypress 4SP ISO 3862/EN 856 - DN 10 I.D. 3/8" - W.P. 445 BAR/6453

INTERPUMP Hypress R12

TFSM012

APPLICATIONS :





TYPE APPROVAL :

MSHA

APPLICABLE SPECS. :

EN 856 R12 - SAE 100R12 - ISO 3862 R12

High flexibility. Burst pressure exceeding standards. MSHA cover.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 4 steel wire spirals.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions. MSHA Cover.

Recommended fluid: Hydraulic fluids petroleum based (mineral oils), glicol-water based, water, lubricants.

Operating temperature: from -40 to + 121° C petroleum based fluids (Intermittent 125°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFSM012-06	3/8″	9.5	20.2	280	4060	1580	22910	95	3.74	0.717	0.482	0009-06
TFSM012-08	1/2″	12.7	23.8	280	4060	1400	20300	110	4.331	0.881	0.592	0009-08
TFSM012-10	5/8″	16.0	27.4	280	4060	1300	18850	130	5.118	1.049	0.705	0009-10
TFSM012-12	3/4″	19.0	30.6	280	4060	1300	18850	145	5.709	1.222	0.821	0009-12 (*)
TFSM012-16	1 ″	25.4	37.9	280	4060	1200	17400	210	8.268	1.795	1.207	0009-16 (*)
TFSM012-20	1.1/4″	31.8	47.5	210	3045	1000	14500	240	9.449	2.780	1.868	0009-20
TFSM012-24	1.1/2″	38.1	53.8	176	2552	1000	14500	480	18.898	3.230	2.171	0009-24
TFSM012-32	2 ″	50.8	67.0	176	2552	850	12325	600	23.622	4.290	2.883	004H-32

(*) Available no skive solutions with ferrule BMC1-12, BMC1-16

Available also embossed brand version. In case of order use TFSM012N.

INTERPUMP Hypress R12 ISO 3862/EN 856 - DN 16 I.D. 5/8" - W.P. 280 BAR/4060 PSI - MSHA IC-242/2

Hypress UniLock
TFS0006



APPLICATIONS :



APPLICABLE SPECS. :
SAE 100R6 - EN 854 1TE

Unilock fittings series, easy assembly, no tools or clamps required. Safety factor 4:1. Do not use for compressed air braking systems and circuits subject to high pressure impulses.

Internal hose: Oil resistant synthetic rubber.

Reinforcement: 1 textile braid.

Covering: Synthetic rubber resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Hydraulic fluids petroleum based (mineral oils), glicol-water based, water, lubricants.


Operating temperature: from -40 to + 100° C petroleum based fluids, from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		Max WP		Max WP Unilock		Min BR		Weight		Ferrule
	in	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS0006I03	3/16"	4.8	34	490	-	-	50	1.969	0.099	0.067	0007-03
TFS0006I04	1/4"	6.4	28	400	28	400	65	2.559	0.100	0.067	0007-04
TFS0006I05	5/16"	8.0	28	400	* - on request		75	2.953	0.125	0.084	0007-05
TFS0006I06	3/8"	9.5	28	400	28	400	75	2.953	0.150	0.101	0007-06
TFS0006I08	1/2"	12.7	28	400	28	400	100	3.937	0.200	0.134	0007-08
TFS0006I10	5/8"	16.0	24	350	-	-	125	4.921	0.250	0.168	0007-10
TFS0006I12	3/4"	19.0	21	300	21	305	150	5.906	0.300	0.202	0007-12
TFS0006I16	1 "	25.4	20	290	12	174	135	5.315	0.450	0.302	0007-16

MARKING: White ink-jet branded (customization not possible)

Hypress 2TE
TFE02TEI

APPLICATIONS :





APPLICABLE SPECS. :
EN 854 2TE

Braided hose textile.

Internal hose: Oil resistant synthetic rubber.

Reinforcement: 2 textile braids.

Covering: Synthetic rubber resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Hydraulic fluids petroleum based (mineral oils), glicol-water based, water, lubricants.

Operating temperature: from -40 to + 100° C petroleum based fluids, from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFE02TEI03	3/16″	4.8	11.8	80	1160	320	4640	35	1.378	0.118	0.079	0003-03
TFE02TEI04	1/4″	6.4	13.4	75	1088	300	4350	40	1.575	0.140	0.094	0007-04
TFE02TEI05	5/16″	8.0	14.9	68	986	272	3944	50	1.969	0.154	0.103	0007-05
TFE02TEI06	3/8″	9.5	16.5	63	914	252	3654	60	2.362	0.179	0.120	0007-06
TFE02TEI08	1/2″	12.7	19.7	58	841	232	3364	70	2.756	0.226	0.152	0007-08
TFE02TEI10	5/8″	16.0	23.9	50	725	200	2900	90	3.543	0.312	0.210	0007-10
TFE02TEI12	3/4″	19.0	27.0	45	653	180	2610	110	4.331	0.342	0.230	0007-12
TFE02TEI16	1 ″	25.4	34.4	40	580	160	2320	150	5.906	0.483	0.325	0007-16

MARKING: White ink-jet branded (customization not possible)

EN854 SAE 100R3
TFS0003



APPLICATIONS :





APPLICABLE SPECS. :
SAE 100R3 - ISO 4079


Braided hose textile.

Internal hose: Oil resistant synthetic rubber.
Reinforcement: 2 textile braids.
Covering: Synthetic rubber resistant to oils, fuels and atmospheric conditions.
Recommended fluid: Hydraulic fluids petroleum based (mineral oils), glicol-water based, water, lubricants.
Operating temperature: from -40 to + 100° C petroleum based fluids, from -40 to +70° C for water based fluids.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS0003-03	3/16″	4.8	12.7	103	1494	412	5974	76	2.992	0.129	0.087	0003-03
TFS0003-04	1/4″	6.4	14.3	86	1247	344	4988	80	3.15	0.160	0.108	0003-04
TFS0003-05	5/16″	8.0	17.5	83	1204	332	4814	102	4.016	0.250	0.168	0003-05
TFS0003-06	3/8″	9.5	19.1	78	1131	312	4524	102	4.016	0.280	0.188	0003-06
TFS0003-08	1/2″	12.7	23.8	69	1001	276	4002	127	5	0.410	0.276	0003-08
TFS0003-10	5/8″	16.0	27.0	60	870	240	3480	140	5.512	0.470	0.316	0003-10
TFS0003-12	3/4″	19.0	31.8	52	754	208	3016	152	5.984	0.650	0.437	0003-12
TFS0003-16	1 ‟	25.4	38.1	39	566	156	2262	203	7.992	0.830	0.558	0003-16
TFS0003-20	1.1/4″	31.8	44.5	26	377	104	1508	254	10	1.000	0.672	0003-20

EN 854 3TE
TFD03TE

APPLICATIONS :





APPLICABLE SPECS. :

EN 854 3TE

Braided hose textile.

Internal hose: Oil resistant synthetic rubber.

Reinforcement: Textile braids.

Covering: Synthetic rubber resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Hydraulic fluids petroleum based, glicol-water based, lubrificant.

Operating temperature: from -40 to + 100° C petroleum based fluids, from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFD03TE-03	3/16″	4.8	12.8	160	2320	640	9280	40	1.575	0.200	0.134	0003-03
TFD03TE-04	1/4″	6.4	14.4	145	2103	580	8410	45	1.772	0.180	0.121	0003-04
TFD03TE-05	5/16″	8.0	16.9	130	1885	520	7540	55	2.165	0.240	0.161	0003-05
TFD03TE-06	3/8″	9.5	18.5	110	1595	440	6380	70	2.756	0.260	0.175	0003-06
TFD03TE-08	1/2″	12.7	21.7	93	1349	372	5394	85	3.346	0.330	0.222	0003-08
TFD03TE-10	5/8″	16.0	25.9	80	1160	320	4640	105	4.134	0.440	0.296	0003-10
TFD03TE-12	3/4″	19.0	29.0	70	1015	280	4060	130	5.118	0.490	0.329	0003-12
TFD03TE-16	1 ″	25.4	35.9	55	798	220	3190	150	5.906	0.670	0.450	0003-16
TFD03TE-20	1.1/4″	31.8	42.3	45	653	180	2610	190	7.48	0.830	0.558	0003-20
TFD03TE-24	1.1/2″	38.1	49.6	40	580	160	2320	240	9.449	1.050	0.706	0003-24
TFD03TE-32	2 ″	50.8	62.3	33	479	132	1914	300	11.811	0.200	0.134	*

INTEPUMP Hy-VACUUM - SAE 100R4

TFS0004



APPLICATIONS :



APPLICABLE SPECS. :
SAE 100R4

Biological oils compatibility - High Ozone Resistance - Half Bend Radius

Internal hose: Oil resistant synthetic rubber.
Reinforcement: 2 textile braids + 1 spiral braid.
Covering: Synthetic rubber resistant to oils, fuels and atmospheric conditions.
Recommended fluid: Hydraulic fluids petroleum based, glicol-water based, lubrificants.
Operating temperature: from -40 to +100°C continuous +70°C for water based fluids

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS0004-12	3/4"	19.0	29.0	21	315	84	1260	60	2.4	0.610	0.410	012N-12
TFS0004-16	1 "	25.0	35.0	17	255	68	1020	75	3.0	0.750	0.510	012N-16
TFS0004-20	1.1/4"	32.0	42.0	14	210	56	840	100	3.9	0.920	0.620	012N-20
TFS0004-24	1.1/2"	38.0	48.5	10	158	42	630	127	5.0	1.140	0.770	012N-24
TFS0004-32	2 "	51.0	63.0	7	105	28	420	150	5.9	1.810	1.210	012N-32
TFS0004-40	2.1/2"	63.5	76.0	4	60	16	240	178	7.0	2.430	1.640	012N-40
TFS0004-48	3 "	76.0	89.0	4	60	16	240	230	9.1	2.990	2.010	012N-48

Available with steel plated braided sleeve version (in case of order use code TFC0004) or stainless steel braided sleeve version (in case of order use code TFI0004)

MARKING: Available only "mylar"

INTERPUMP Hy-Vacuum SAE 100 R4 - DN 63 I.D. 21/2" - W.P. 4 BAR/62 PSI

SAE 100R5
TFS0005

APPLICATIONS :





APPLICABLE SPECS. :

SAE 100R5

Abrasion resistant textile braid cover. NO -SKIVE solution available.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 steel wire braid.

Covering: Textile braided cover.

Recommended fluid: Hydraulic fluids petroleum based (mineral oils), glicol-water based, water, lubricants.

Operating temperature: from -40 to + 100° C petroleum based fluids (Intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS0005-04	3/16"	4.8	13.2	210	3045	840	12180	75	2.953	0.190	0.128	0003-03
TFS0005-05	1/4"	6.4	14.8	210	3045	840	12180	85	3.346	0.224	0.151	0003-04
TFS0005-06	5/16"	7.9	17.2	157	2277	628	9106	100	3.937	0.283	0.190	0003-05
TFS0005-08	13/32"	10.3	19.5	140	2030	560	8120	115	4.528	0.350	0.235	0003-06
TFS0005-10	1/2"	12.7	23.4	122	1769	488	7076	140	5.512	0.473	0.318	0003-08
TFS0005-12	5/8"	15.9	27.4	105	1523	420	6090	165	6.496	0.617	0.415	0003-10
TFS0005-16	7/8"	22.2	31.4	56	812	224	3248	185	7.283	0.570	0.383	0003-12
TFS0005-20	1.1/8"	28.6	38.1	43	624	172	2494	230	9.055	0.795	0.534	*
TFS0005-24	1.3/8"	34.9	44.5	35	508	140	2030	265	10.433	1.020	0.685	*
TFS0005-32	1.13/16"	46.0	56.4	24	348	96	1392	335	13.189	1.420	0.954	*

* Ask to our Technical Dept.

MARKING: White ink-jet branded (customization not possible)

High Performance



Index

Compressor

TFDC011B



INTERPUMP COMPRESSOR

23

PREMIUM LINE

High Temperature

TFDH011B



INTERPUMP HyCelsius 1SN

24

TFDH021B



INTERPUMP HyCelsius 2SN

25

PREMIUM LINE

Low Temperature

TFDL011N



INTERPUMP HyFreeze 1SN

26

TFDL021N



INTERPUMP HyFreeze 2SN

27

PREMIUM LINE

HyOzone

TFEM02KN



INTERPUMP HyOzone

28

Pilot

TFE2PF2



INTERPUMP PilotFlex 120

29

TFE0P15



INTERPUMP Pilot Plus 150

30

PREMIUM LINE

KAIZEN 2SN

THD0021



INTERPUMP Kaizen 2SN

31

PREMIUM LINE

HIPAC

THE001K



INTERPUMP Hipac 1SC

32

THE002K



INTERPUMP Hipac 2SC

33

THE003K



INTERPUMP Hipac 3SC

34

PREMIUM LINE

LONGLIFE

Dimensions and general characteristics may be changed at any time, data contained here in are only for information purpose only and it does not enlarge, amend or imply any warranty other than provided by us with the product. Any use of thr product not in conformance with our instructions may be dangerous.

THE201K



INTERPUMP LongLife 1SC

35

THE202K



INTERPUMP LongLife 2SC

36

MARATHON

THE2M2K



INTERPUMP MARATHON 2SC

37

Green Spirals

THDB4SH



BIO - FLEX

38

TFDR4SH



INTERPUMP HyGreen 4SH

39

TFDG013



INTERPUMP HyGreen R13

40

TFDG015



INTERPUMP HyGreen R15


41

INTERPUMP COMPRESSOR

TFDC011B

APPLICATIONS :





APPLICABLE SPECS. :
IMM - EXCEED EN 853 1SN

Pin pricked hose for compressor. Do not use with bio-oil.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 steel wire braid.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral oils, glycols and polyglycols, trasmission fluids, air, air with oil vapours, mineral oils in aqueous emulsion (up to +212°F/ + 100°C).

Operating temperature: from -40 to +120°C (intermittent 135°C).

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFDC011B04	1/4"	6.4	13.4	225	3263	900	13050	100	3.937	0.24	0.161	0001-04
TFDC011B05	5/16"	8.0	15.0	215	3118	850	12325	115	4.528	0.278	0.187	0001-05
TFDC011B06	3/8"	9.5	17.4	180	2610	720	10440	130	5.118	0.367	0.247	0001-06
TFDC011B08	1/2"	12.7	20.6	160	2320	640	9280	180	7.087	0.437	0.294	0001-08
TFDC011B10	5/8"	16.0	23.7	130	1885	520	7540	200	7.874	0.524	0.352	0001-10
TFDC011B12	3/4"	19.0	27.7	105	1523	420	6090	240	9.449	0.653	0.439	0001-12
TFDC011B16	1 "	25.4	35.6	88	1276	350	5075	300	11.811	1.001	0.673	0001-16
TFDC011B20	1.1/4"	31.8	43.5	63	914	250	3625	420	16.535	1.435	0.964	0001-20
TFDC011B24	1.1/2"	38.1	54.6	50	725	200	2900	500	19.685	1.711	1.150	0001-24
TFDC011B32	2 "	50.8	66.9	40	580	160	2320	630	24.803	2.357	1.584	0001-32


Compressed air applications require additional safety devices. Hoses are not designed and not approved for "air brake" applications.

MARKING: Available only embossed)

INTERPUMP HyCelsius 1SN
TFDH011B

APPLICATIONS :





APPLICABLE SPECS. :
EN 853 1SN SAE 100R1AT

Wide range temperature resistance. Hoses are not designed and not approved for “air brake” applications on railway and/or mobile equipment. Do not use with compressor.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 steel wire braid.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Hydraulic fluids petroleum based (mineral oils), glicol-water based, water, lubricants.

Operating temperature: from -40 to +135°C (intermittent 140°C).


Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFDH011B04	1/4”	6.4	13.4	225	3263	900	13050	100	3.937	0,225	0.151	0001-04
TFDH011B05	5/16”	8.0	15.0	215	3118	860	12325	115	4.528	0,252	0.169	0001-05
TFDH011B06	3/8”	9.5	17.4	180	2610	720	10440	130	5.118	0,337	0.226	0001-06
TFDH011B08	1/2”	12.7	20.6	160	2320	640	9280	180	7.087	0,404	0.271	0001-08
TFDH011B10	5/8”	16.0	23.7	130	1885	520	7540	200	7.874	0,476	0.320	0001-10
TFDH011B12	3/4”	19.0	27.7	105	1523	420	6090	240	9.449	0,601	0.404	0001-12
TFDH011B16	1 “	25.4	35.6	88	1276	352	5075	300	11.811	0,903	0.607	0001-16
TFDH011B20	1.1/4”	31.8	43.5	63	914	252	3625	420	16.535	1,272	0.855	0001-20
TFDH011B24	1.1/2”	38.1	50.8	50	725	200	2900	500	19.685	1,596	1.073	0001-24
TFDH011B32	2 “	50.8	63.6	40	580	160	2320	630	24.803	2,222	1.493	0001-32
TFDH011B40	2.1/2”	63.5	77.4	30	435	120	1741	760	29.921	2.755	1.851	0001-40

Available also with black cover. In case of order use TFDH011N.

MARKING: Available only embossed)

INTERPUMP HyCelsius 2SN

TFDH021B



APPLICATIONS :



APPLICABLE SPECS. :
EN 853 2SN - SAE 100R2AT

Wide range temperature resistance. Hoses are not designed and not approved for "air brake" applications on railway and/or mobile equipment. Do not use with compressor.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Hydraulic fluids petroleum based (mineral oils), glicol-water based, water, lubricants.

Operating temperature: from -40 to +135°C (intermittent 140°C).

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFDH021B04	1/4"	6.4	15.0	400	5800	1600	23200	100	3.937	0,357	0.240	0002-04
TFDH021B05	5/16"	8.0	16.6	350	5075	1400	20300	115	4.528	0,413	0.278	0002-05
TFDH021B06	3/8"	9.5	19.0	330	4785	1320	19140	130	5.118	0,521	0.350	0002-06
TFDH021B08	1/2"	12.7	22.2	275	3988	1100	15950	180	7.087	0,616	0.414	0002-08
TFDH021B10	5/8"	16.0	25.4	250	3625	1000	14500	200	7.874	0,749	0.503	0002-10
TFDH021B12	3/4"	19.0	29.3	215	3118	850	12325	240	9.449	0,920	0.618	0002-12
TFDH021B16	1 "	25.4	38.1	165	2393	650	9425	300	11.811	1,375	0.924	0002-16

Available also with black cover. In case of order use TFDH021N.

MARKING: Available only embossed)

INTERPUMP HyFreeze 1SN

TFDL011N

APPLICATIONS :





APPLICABLE SPECS. :

EN 853 1SN - SAE 100R1AT

Suitable for very cold enviroments.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 steel wire braid.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C, min. external temperature -50°C.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFDL011N04	1/4"	6.4	13.4	225	3263	900	13050	100	3.937	0.231	0.155	0001-04
TFDL011N05	5/16"	8.0	15.0	215	3118	850	12325	115	4.528	0.254	0.171	0001-05
TFDL011N06	3/8"	9.5	17.4	180	2610	720	10440	130	5.118	0.338	0.227	0001-06
TFDL011N08	1/2"	12.7	20.6	160	2320	640	9280	180	7.087	0.415	0.279	0001-08
TFDL011N10	5/8"	16.0	23.7	130	1885	520	7540	200	7.874	0.477	0.321	0001-10
TFDL011N12	3/4"	19.0	27.7	105	1523	420	6090	240	9.449	0.618	0.415	0001-12
TFDL011N16	1 "	25.4	35.6	88	1276	350	5075	300	11.811	0.901	0.605	0001-16

MARKING: Available only embossed)

INTERPUMP HyFreeze 2SN

TFDL021N



APPLICATIONS :



APPLICABLE SPECS. :

EN 853 2SN - SAE 100R2AT

Suitable for very cold enviroments.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C, min. external temperature -50°C.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFDL021N04	1/4"	6.4	15.0	400	5800	1600	23200	100	3.937	0.36	0.242	0002-04
TFDL021N05	5/16"	8.0	16.6	350	5075	1400	20300	115	4.528	0.416	0.280	0002-05
TFDL021N06	3/8"	9.5	19.0	330	4785	1320	19140	130	5.118	0.525	0.353	0002-06
TFDL021N08	1/2"	12.7	22.2	275	3988	1100	15950	180	7.087	0.62	0.417	0002-08
TFDL021N10	5/8"	16.0	25.4	250	3625	1000	14500	200	7.874	0.752	0.505	0002-10
TFDL021N12	3/4"	19.0	29.3	215	3118	850	12325	240	9.449	0.923	0.620	0002-12
TFDL021N16	1 "	25.4	38.1	165	2393	650	9425	300	11.811	1.377	0.925	0002-16
TFDL021N20	1.1/4"	31.8	48.3	125	1813	500	7250	420	16.535	1.99	1.337	0002-20
TFDL021N24	1.1/2"	38.1	54.6	90	1305	360	5220	500	19.685	2.318	1.557	0002-24
TFDL021N32	2 "	50.8	66.9	80	1160	320	4640	630	24.803	3.15	2.117	0002-32


MARKING: Available only embossed)

INTERPUMP HyOzone
TFEM02KN

APPLICATIONS :



TYPE APPROVAL :
MSHA



APPLICABLE SPECS. :
EXCEED EN 857 2SC - SAE 100R16

Compact hose with low bend radius. Outstanding ozone resistance. Superior weather and UV resistance.


Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.
Reinforcement: 2 high tensile steel wire braids.
Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.
Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.
Operating temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFEM02KN04	1/4"	6.4	13.3	400	5800	1600	23200	50	1.969	0.281	0.189	001C-04
TFEM02KN05	5/16"	8.0	14.8	350	5075	1400	20300	55	2.165	0.33	0.222	001C-05
TFEM02KN06	3/8"	9.5	17.1	330	4785	1320	19140	65	2.559	0.418	0.281	001C-06
TFEM02KN08	1/2"	12.7	20.4	275	3988	1100	15950	90	3.543	0.525	0.353	001C-08
TFEM02KN10	5/8"	16.0	23.5	250	3625	1000	14500	100	3.937	0.627	0.421	001C-10
TFEM02KN12	3/4"	19.0	27.6	215	3118	860	12470	120	4.724	0.782	0.526	001C-12
TFEM02KN16	1 "	25.4	35.8	165	2393	660	9570	150	5.906	1.176	0.790	001C-16

MARKING: Available only embossed)

INTERPUMP PilotFlex 120

TFE2PF2



APPLICATIONS :



APPLICABLE SPECS. :

IMM SPECIFICATION

Smooth cover with high abrasion resistance. User friendly and Easy to Handle configuration. Extreme compactness and flexibility with the lowest bend radius. Tested up 1.000.000 cycles. Safety factor 4:1.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 high tensile steel wire braid.

Covering: Smooth synthetic rubber, resistant to oils, fuelsa and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C (intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFE2PF2-03	3/16"	4.8	9.0	120	1750	480	7000	20	0.787	0.10	0.067	0007-03
TFE2PF2-04	1/4"	6.4	10.7	120	1750	480	7000	25	0.984	0.13	0.087	001C-04
TFE2PF2-05	5/16"	8.0	13.0	120	1750	480	7000	30	1.181	0.19	0.130	001C-05

Size 03 and 04 available with reduced fittings 001C-03SW and 001C-04SW / 0350-03-02SW and 0350-04-02SW.

MARKING: Available only "mylar"

INTERPUMP Pilot Flex 120 DN 5 I.D. 3/16" - W.P. 12 MPa/1750 psi

INTERPUMP Pilot Plus 150
TFE0P15

APPLICATIONS :





APPLICABLE SPECS. :
IMM SPECIFICATION

Lightweight. Compact design. High flexibility. Tested up 1.000.000 impulse cycles at rated working pressure.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 high tensile steel wire braid.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFE0P15-03	3/16″	4.8	10.5	150	2175	600	8700	20	0.787	0.15	0.101	001C-03
TFE0P15-04	1/4″	6.4	11.5	150	2175	600	8700	25	0.984	0.163	0.109	001C-04
TFE0P15-05	5/16″	8.0	13.1	150	2175	600	8700	30	1.181	0.193	0.130	001C-05
TFE0P15-06	3/8″	9.5	14.8	150	2175	600	8700	40	1.575	0.224	0.150	001C-06
TFE0P15-08	1/2″	12.7	17.5	150	2175	600	8700	50	1.969	0.251	0.168	001C-08

Available on request in the version with smooth cover (in case of order use the code TFE1P15)

MARKING: Available only "mylar"


INTERPUMP Pilot Plus150 DN 5 I.D. 3/16" - W.P. 15 MPa/2175 PSI

INTERPUMP Kaizen 2SN

THD0021



APPLICATIONS :



TYPE APPROVAL :
MED, DNV - GL, RINA, BV, LLOYD'S

APPLICABLE SPECS. :
IMM - EXCEED EN 853 2SN - ISO 1436 2SN

NO-SKIVE hose. Exceed EN specification. Impulse tested up to 1.000.000 cycles MED certificate (ISO 15540/15541).

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THD0021-03	3/16"	4.8	13.5	420	6090	1750	25375	50	1.969	0.317	0.213	0022-03
THD0021-04	1/4"	6.4	15.0	420	6090	1750	25375	50	1.969	0.353	0.237	0022-04
THD0021-05	5/16"	8.0	16.6	360	5220	1500	21750	60	2.362	0.416	0.280	0022-05
THD0021-06	3/8"	9.5	19.0	350	5075	1450	21025	70	2.756	0,515	0.346	0022-06
THD0021-08	1/2"	12.7	22.2	290	4205	1200	17400	90	3.543	0,608	0.409	0022-08
THD0021-10	5/8"	16.0	25.4	250	3625	1100	15950	110	4.331	0,740	0.497	0022-10
THD0021-12	3/4"	19.0	29.3	215	3118	900	13050	130	5.118	0,909	0.611	0022-12
THD0021-16	1 "	25.4	38.1	175	2538	700	10150	170	6.693	1,355	0.911	0022-16
THD0021-20	1.1/4"	31.8	48.3	140	2030	560	8120	390	15.354	2.035	1.368	0022-20
THD0021-24	1.1/2"	38.1	54.6	125	1813	500	7250	460	18.110	2.3	1.546	0022-24
THD0021-32	2 "	50.8	66.9	90	1305	420	6090	600	23.622	3.14	2.110	0022-32

MARKING: Available also embossed brand version. In case of order use code THD0021N.

INTERPUMP Hipac 1SC
THE001K



APPLICATIONS :



TYPE APPROVAL :
BV, NKK, KR

APPLICABLE SPECS. :
EXCEED EN 857 1SC, ISO 11237 1SC

NO-SKIVE tube. High abrasion resistance. Exceeding standard operating and burst pressure. Easy assembly.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 high tensile steel wire braids.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE001KN04	1/4"	6.4	12.3	250	3625	1120	16240	50	1.969	0.182	0.122	001C-04
THE001KN05	5/16"	8.0	13.5	250	3625	1000	14500	55	2.165	0.210	0.141	001C-05
THE001KN06	3/8"	9.5	15.7	250	3625	1000	14500	60	2.362	0.248	0.167	001C-06
THE001KN08	1/2"	12.7	18.9	200	2900	800	11600	70	2.756	0.391	0.263	001C-08
THE001KN10	5/8"	16.0	22.4	150	2175	600	8700	90	3.453	0.410	0.276	001C-10
THE001KN12	3/4"	19.0	26.0	150	2175	600	8700	100	3.937	0.534	0.359	001C-12
THE001KN16	1 "	25.4	33.7	110	1595	440	6380	180	7.087	0.742	0.499	001C-16
THE001KN20	1.1/4"	31.8	41.1	100	1450	400	5800	210	8.268	1.11	0.746	001C-20
THE001KN24	1.1/2"	38.1	48.6	90	1305	360	5220	300	11.811	1.39	0.934	001C-24
THE001KN32	2 "	50.8	61.5	75	1088	300	4350	400	15.748	1.94	1.304	001C-32
THE001KN40	2.1/2"	63.5	73.5	50	725	200	2900	700	29.134	2.22	1.492	001C-40
THE001KN48	3"	76.2	86.0	40	580	160	2320	860	33.858	2.315	1.556	001C-48


MARKING: Available only embossed)

INTERPUMP Hipac 2SC

THE002K



APPLICATIONS :



TYPE APPROVAL :

MED, DNV - GL, RINA, BV, LLOYD'S

APPLICABLE SPECS. :

IMM - EXCEED DIN EN 857 2SC - ISO 11237 2SC

NO-SKIVE hose. Exceed EN specification. Impulse tested up to 1.000.000 cycles MED certificate (ISO 15540/15541).

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.


Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE002K-04	1/4"	6.4	13.3	430	6235	1720	24940	50	1.969	0.285	0.191	001C-04
THE002K-05	5/16"	8.0	14.8	400	5800	1600	23200	60	2.362	0.329	0.221	001C-05
THE002K-06	3/8"	9.5	17.1	350	5075	1400	20300	70	2.756	0.422	0.283	001C-06
THE002K-08	1/2"	12.7	20.4	310	4495	1240	17980	80	3.150	0.517	0.347	001C-08
THE002K-10	5/8"	16.0	23.5	280	4060	1120	16240	100	3.937	0.626	0.421	001C-10
THE002K-12	3/4"	19.0	27.6	240	3480	960	13920	120	4.724	0.765	0.514	001C-12
THE002K-16	1 "	25.4	35.8	210	3045	840	12180	160	6.299	1.171	0.787	001C-16
THE002K-20	1.1/4"	31.8	43.1	160	2320	640	9280	250	9.843	1.53	1.028	001C-20
THE002K-24	1.1/2"	38.1	50.6	150	2175	600	8700	260	10.236	2.12	1.425	001C-24
THE002K-32	2 "	50.8	63.5	100	1450	400	5800	360	14.173	2.795	1.878	001C-32
THE002K-40	2.1/2"	63.5	75.6	80	1160	320	4640	600	23.622	3.224	2.167	001C-40
THE002K-48	3"	76.2	88.0	65	943	260	3770	760	29.921	3.471	2.333	001C-48


MARKING: Available also embossed brand version. In case of order use THE002KN.



INTERPUMP Hipac 3SC
THE003K

APPLICATIONS :





APPLICABLE SPECS. :
IMM

Compact hose. NO-SKIVE construction. NBR tube compound compatible with several fluids. Approved up to 500.000 impulse cycles. Tested at 120% Max WP.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 3 high tensile steel wire braids.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to + 100° C petroleum based fluids (Intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE003K-06	3/8"	9.5	18.8	500	7250	2000	29000	110	4.331	0.617	0.415	*
THE003K-08	1/2"	12.7	22.4	475	6888	1900	27550	140	5.512	0.817	0.549	*
THE003K-10	5/8"	16.0	25.8	420	6090	1680	24360	200	7.874	0.931	0.625	*
THE003K-12	3/4"	19.0	29.7	380	5510	1520	22040	240	9.449	1.188	0.799	*
THE003K-16	1 "	25.4	38.8	315	4568	1260	18270	300	11.811	1.946	1.308	*

* Ask to our Technical Dept.

Available also embossed brand version. In case of order use code THE003KN.

INTERPUMP HIPAC - 3SC DN 10 I.D. 3/8" - W.P. 500 BAR/7250 PSI

INTERPUMP LongLife 1SC

THE201K



APPLICATIONS :



TYPE APPROVAL :
NKK, BV, KR

APPLICABLE SPECS. :
EXCEED EN 857 1SC- ISO 11237 1SC

No-SKIVE hose. High abrasion resistance. Pressure rating exceeding standards. Easy to install. SMOOTH COVER.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 high tensile steel wire braids.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE201K-04	1/4″	6.4	12.3	250	3625	1120	16240	50	1.969	0.182	0.122	001C-04
THE201K-05	5/16″	8.0	13.5	250	3625	1000	14500	55	2.165	0.21	0.141	001C-05
THE201K-06	3/8″	9.5	15.7	250	3625	1000	14500	60	2.362	0.248	0.167	001C-06
THE201K-08	1/2″	12.7	18.9	200	2900	800	11600	70	2.756	0.391	0.263	001C-08
THE201K-10	5/8″	16.0	22.4	150	2175	600	8700	90	3.543	0.41	0.276	001C-10
THE201K-12	3/4″	19.0	26.0	150	2175	600	8700	100	3.937	0.534	0.359	001C-12
THE201K-16	1″	25.4	33.7	110	1595	440	6380	180	7.087	0.742	0.499	001C-16

MARKING: Available only "mylar"

INTERPUMP Long Life EXCEEDS EN 857 - 1SC DN 6 I.D. 1/4" - W.P. 25,0 MPa/3625 PSI

INTERPUMP LongLife 2SC
THE202K

APPLICATIONS :



TYPE APPROVAL :
BV, NKK, KR

APPLICABLE SPECS. :
EXCEED EN 857 2SC - ISO 11237



No-SKIVE hose. High abrasion resistance. Pressure rating exceeding standards. Easy to install. SMOOTH COVER.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE202K-04	1/4″	6.4	13.3	430	6235	1720	24940	50	1.969	0.283	0.190	001C-04
THE202K-05	5/16″	8.0	14.8	400	5800	1600	23200	60	2.362	0.324	0.218	001C-05
THE202K-06	3/8″	9.5	17.1	350	5075	1400	20300	70	2.756	0.418	0.281	001C-06
THE202K-08	1/2″	12.7	20.4	310	4495	1240	17980	80	3.150	0.521	0.350	001C-08
THE202K-10	5/8″	16.0	23.5	280	4060	1120	16240	100	3.937	0.626	0.421	001C-10
THE202K-12	3/4″	19.0	27.6	240	3480	960	13920	120	4.724	0.764	0.513	001C-12
THE202K-16	1″	25.4	35.8	210	3045	840	12180	160	6.299	1.171	0.787	001C-16

INTERPUMP LongLife EXCEEDS EN 857 - 2SC DN 6 I.D. 1/4" - W.P. 43,0 MPa/6235 PSI

INTERPUMP MARATHON 2SC

THE2M2K



APPLICATIONS :



APPLICABLE SPECS. :
IMM - EXCEED EN 857 2SC - ISO 11237 2SC

NO-SKIVE hose. Exceed EN specification. Impulse tested up to 1.000.000 cycles.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE2M2K-04	1/4"	6.4	13.3	450	6525	1800	26100	50	1.969	0.285	0.192	001C-04
THE2M2K-05	5/16"	8.0	14.8	420	6090	1680	24360	60	2.362	0.33	0.222	001C-05
THE2M2K-06	3/8"	9.5	17.1	385	55825	1540	22330	70	2.756	0.422	0.284	001C-06
THE2M2K-08	1/2"	12.7	20.4	350	5075	1500	21750	80	3.150	0.566	0.349	001C-08
THE2M2K-10*	5/8"	16.0	23.5	350	5075	1400	20300	90	3.543	0.665	0.447	001C-10
THE2M2K-12	3/4"	19.0	27.6	280	4060	1120	16240	120	4.725	0.865	0.531	001C-12
THE2M2K-16*	1"	25.4	36.0	250	3625	1000	14500	140	5.512	1.39	0.934	0022-16

Lenghts exceeding EN-specification

*Impulse tested according to EN857 2SC

BIO - FLEX
THDB4SH

APPLICATIONS :





APPLICABLE SPECS. :
EXCEED EN 856 4SH - ISO 3862 4SH

Compatible with organic oils. EN norms tested. Impulse tested up to 1,000,000 cycles. Reduced bending radiius. High abrasion resistance. High ozone resistance.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 4 steel wire spirals.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions. MSHA cover.

Recommended fluid: Biological and mineral oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to + 100° C petroleum based fluids (Intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THDB4SHN12	3/4"	19.0	32.0	420	6090	1680	24360	130	5.118	1.537	1.033	004N-12

Available with steel plated braided sleeve version (in case of order use code THCB4SH) or stainless steel braided sleeve version (in case of order use code THIB4SH)


MARKING: Available only embossed)

INTERPUMP HyGreen 4SH

TFDR4SH



APPLICATIONS :



TYPE APPROVAL :
DNV - GL, BV, LLOYD'S, ABS, NKK, KR, MED

APPLICABLE SPECS. :
EXCEED EN 856 4SH - ISO 3862 4SH

Biological oils compatibility. Exceed EN standard. Impulse tested up to 1.000.000 impulse cycles. High ozone and abrasion resistance.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 4 steel wire spirals.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions. MSHA Cover.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants, compressed air

Operating temperature: from -40 to +100°C (intermittent 120°C),

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFDR4SH-12	3/4"	19.0	32.0	420	6090	1780	25810	210	8.268	1.572	1.056	004N-12/X Series
TFDR4SH-16	1 "	25.4	38.4	385	5583	1750	25375	220	8.661	2.104	1.414	004N-16/X Series
TFDR4SH-20	1.1/4"	31.8	45.8	350	5075	1400	20300	400	15.748	2.550	1.714	004N-20/X Series
TFDR4SH-24	1.1/2"	38.1	53.5	300	4350	1250	18125	560	22.047	3.225	2.167	004N-24/X Series
TFDR4SH-32	2 "	50.8	68.0	250	3625	1000	14500	700	27.559	4.600	3.091	004N-32/X Series

Available also in NON-MSHA version. In case of order use code TFDG4SH.


MARKING: Available also embossed brand version. In case of order use code TFDR4SHN.

INTERPUMP HyGreen 4SH ISO 3862/EN 856 - DN 19 I.D. 3/4" - W.P. 420 bar/6090 psi - MADE IN ITALY

INTERPUMP HyGreen R13

TFDR013

APPLICATIONS :



TYPE APPROVAL :

DNV - GL, BV, LLOYD'S, ABS, NKK, KR, MED

APPLICABLE SPECS. :

EXCEED EN 856 SAE 100R13 - ISO 3862 R13



Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 4 high tensile steel wire spiral up to size 1", 6 spiral from size 1,1/4.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions. MSHA cover.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants, compressed air

Operating temperature: from -40 to + 121° C (Intermittent 125°C)

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFDR013-12	3/4"	19.0	32.1	350	5075	1920	27840	120	4.725	1.641	1.103	004N-12/X Series
TFDR013-16	1 "	25.4	38.7	350	5075	1660	24070	150	5.905	2.106	1.415	0013-16/X Series
TFDR013-20	1.1/4"	31.8	49.7	350	5075	1520	22040	210	8.248	3.891	2.615	0013-20/X Series
TFDR013-24	1.1/2"	38.1	57.8	350	5075	1600	23200	310	12.205	5.210	3.501	0013-24/X Series
TFDR013-32	2 "	50.8	71.5	350	5075	1500	21750	590	23.228	6.840	4.596	0013-32/X Series

Available also in NON-MSHA version. In case of order use code TFDG013.

Available also embossed brand version. In case of order use code TFDR013N.


INTERPUMP HyGreen R13 ISO 3862/SAE 100R13 - DN 19 I.D. 3/4" - W.P. 350 bar/5075 psi - MADE IN ITALY

INTERPUMP HyGreen R15

TFDR015



APPLICATIONS :



TYPE APPROVAL :

DNV - GL, BV, LLOYD'S, ABS, NKK, KR, MED

APPLICABLE SPECS. :

EXCEED SAE 100R15 - ISO 3862

Biological oils compatibility. Exceed EN standard. Impulse tested up to 1.000.000 impulse cycles.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.
Reinforcement: 4 high tensile steel wire spiral up to size 1", 6 spiral from size 1,1/4.
Covering: Abrasion resistant synthetic rubber resistant to oils, fuels, atmospheric conditions. MSHA.
Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants, compressed air
Operating temperature: from -40 to + 121° C (Intermittent 125°C)

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFDR015-10	5/8"	16.0	26.8	420	6090	1750	25375	150	5.901	0.705	0.474	0013-10/X Series
TFDR015-12	3/4"	19.0	32.0	420	6090	1750	25375	210	8.268	1.573	1.057	004N-12/X Series
TFDR015-16	1 "	25.4	38.7	420	6090	1700	24650	240	9.449	2.116	1.422	0013-16/X Series
TFDR015-20	1.1/4"	31.8	49.7	420	6090	1680	24360	265	10.433	3.891	2.615	0013-20/X Series
TFDR015-24	1.1/2"	38.1	57.8	420	6090	1680	24360	310	12.205	5.182	3.482	0013-24/X Series
TFDR015-32	2 "	50.8	72.0	420	6090	1680	24360	590	23.228	6.892	4.631	0013-32/X Series

Available also in NON-MSHA version. In case of order use code TFDG015.

MARKING: Available also embossed brand version. In case of order use code TFDR015N.

INTERPUMP HyGreen R15 EXCEEDS ISO 3862/SAE 100R15 - DN 19 I.D. 3/4" - W.P. 420 bar/6090 psi - MADE IN ITALY

Solution for Applications

Index

Cleaning Jet

TFN0011/TFB0011



INTERPUMP Jet 1SN

48


TFN002/TFB0021



INTERPUMP Jet 2SN

49

TFN001K/TFB001K



INTERPUMP Jet 1SC

50

TFN002K/TFB002K




INTERPUMP Jet 2SC

51

Cleaning Jet Plus

THN0011/THB0011



INTERPUMP Jet Plus 1SN

52


THN0021/THB0021



INTERPUMP Jet Plus 2SN

53

THN001K/THB001K



INTERPUMP Jet Plus 1SC

54

THN002K/THB002K



INTERPUMP Jet Plus 2SC

55

SEWERJET 280

TSW2280



INTERPUMP SEWERJET 280

46

Hyblast

TFW0070



INTERPUMP Hyblast 10k

57

TFW0085



INTERPUMP Hyblast 12k

58

TFW0110/TFW0100



INTERPUMP Hyblast 15k

59

TFW0125/TFW0120



INTERPUMP Hyblast 18k

60

TFW0145/TFW0135



INTERPUMP Hyblast 20k

61

LongLift 1SC/2SC

THL101K



INTERPUMP LongLift 1SC

62

THL102K



INTERPUMP LongLift 2SC

63

LongLife Dual 1SC/2SC

T2E101K



INTERPUMP LongLife Dual 1SC

64

T2E102K



INTERPUMP LongLife Dual 2SC

65

Dimensions and general characteristics may be changed at any time, data contained here in are only for information purpose only and it does not enlarge, amend or imply any warranty other than provided by us with the product. Any use of the product not in conformance with our instructions may be dangerous.

Index

PREMIUM LINE
Railway

TFDE011



HyRail - Fire resistant

66

PREMIUM LINE
Power Lift

THE0L1K/THE0L2K



INTERPUMP Power Lift - 1SC/2SC

67

PREMIUM LINE
HYJACK

THE2J2K



INTERPUMP HYJACK

68

PREMIUM LINE
Snow Storm

THEPS1K



Hypress Snow Storm 1SC

69

PREMIUM LINE
HyTruck

TTRK200



INTERPUMP HyTruck 200 bar

70

TTRK250



INTERPUMP HyTruck 250 bar

71

TTRK350



INTERPUMP HyTruck 350 bar

72

PREMIUM LINE
MEGADRILL

THEMMDR



INTERPUMP Mega Drill

73

PREMIUM LINE
MEGAJET

TFS04JG/THS00JG



INTERPUMP Mega Jet

74

PREMIUM LINE
BOP

TBOP350



INTERPUMP BOP FIRESCREEN 5000

75

PREMIUM LINE
HyGear 1SC

THE0G1K



HyGear 1SC


66

Dimensions and general characteristics may be changed at any time, data contained here in are only for information purpose only and it does not enlarge, amend or imply any warranty other than provided by us with the product. Any use of the product not in conformance with our instructions may be dangerous.

INTERPUMP Jet 1SN

TFN0011 TFB0011





APPLICATIONS :



APPLICABLE SPECS. :
EN 853 1SN - ISO 7751

Dimensions according to EN 853 1SN. NO-SKIVE flexible line. Safety factor exceeding ISO 7751. Product designed for pressure wash applications. Any different use may reduce service life.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 steel wire braid.

Covering: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Water, water-soap based, glicol-water based.

Operating temperature: from -40 to +135°C (intermittent 155°C).

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFN0011N04	1/4"	6.4	13.4	250	3625	900	13050	100	3.937	0.231	0.155	001C-04
TFN0011N05	5/16"	8.0	15.0	250	3625	840	12180	115	4.528	0.254	0.171	001C-05
TFN0011N06	3/8"	9.5	17.4	250	3625	720	10440	130	5.118	0.338	0.227	001C-06
TFN0011N08	1/2"	12.7	20.6	250	3625	640	9280	180	7.087	0.415	0.279	001C-08
TFB0011N04	1/4"	6.4	13.4	250	3625	900	13050	100	3.937	0.231	0.155	001C-04
TFB0011N05	5/16"	8.0	15.0	250	3625	840	12180	115	4.528	0.254	0.171	001C-05
TFB0011N06	3/8"	9.5	17.4	250	3625	720	10440	130	5.118	0.338	0.227	001C-06
TFB0011N08	1/2"	12.7	20.6	250	3625	640	9280	180	7.087	0.415	0.279	001C-08


MARKING: Available only embossed)

INTERPUMP Jet 2SN

TFN0021 TFB0021

APPLICATIONS :





APPLICABLE SPECS. :
EN 853 2SN - ISO 7751

Dimensions according to EN 853 2SN. NO-SKIVE flexible line. Safety factor exceeding ISO 7751. Product designed for pressure wash applications. Any different use may reduce service life.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Covering: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Water, water-soap based, glicol-water based.

Operating temperature: from -40 to +135°C (intermittent 155°C).


Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFN0021N04	1/4"	6.5	15.0	400	5800	1600	23200	100	3.937	0.359	0.241	0022-04
TFN0021N05	5/16"	8.0	16.6	400	5800	1400	20300	115	4.528	0.415	0.279	0022-05
TFN0021N06	3/8"	9.5	19.0	400	5800	1320	19140	130	5.118	0.525	0.353	0022-06
TFN0021N08	1/2"	12.7	22.2	400	5800	1100	15950	180	7.087	0.620	0.417	0022-08
TFB0021N04	1/4"	6.5	15.0	400	5800	1600	23200	100	3.937	0.359	0.241	0022-04
TFB0021N05	5/16"	8.0	16.6	400	5800	1400	20300	115	4.528	0.415	0.279	0022-05
TFB0021N06	3/8"	9.5	19.0	400	5800	1320	19140	130	5.118	0.525	0.353	0022-06
TFB0021N08	1/2"	12.7	22.2	400	5800	1100	15950	180	7.087	0.620	0.417	0022-08

MARKING: Available only embossed)

INTERPUMP Jet 1SC

TFN001K TFB001K





APPLICATIONS :



APPLICABLE SPECS. :
EN 857 1SC - ISO 7751

Dimensions according to EN 857 1SC. NO-SKIVE flexible line. Safety factor exceeding ISO 7751. Product designed for pressure wash applications. Any different use may reduce service life.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 steel wire braid.

Covering: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Water, water-soap based, glicol-water based.

Operating temperature: from -40 to +135°C (intermittent 155°C).

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFN001KN04	1/4"	6.4	12.3	250	3625	900	13050	75	2.953	0.182	0.122	001C-04
TFN001KN05	5/16"	8.0	14.0	250	3625	840	12180	85	3.346	0.203	0.136	001C-05
TFN001KN06	3/8"	9.5	15.6	250	3625	720	10440	90	3.543	0.256	0.172	001C-06
TFN001KN08	1/2"	12.7	18.7	250	3625	640	9280	130	5.118	0.341	0.229	001C-08
TFB001KN04	1/4"	6.4	12.3	250	3625	900	13050	75	2.953	0.182	0.122	001C-04
TFB001KN05	5/16"	8.0	14.0	250	3625	840	12180	85	3.346	0.203	0.136	001C-05
TFB001KN06	3/8"	9.5	15.6	250	3625	720	10440	90	3.543	0.256	0.172	001C-06
TFB001KN08	1/2"	12.7	18.7	250	3625	640	9280	130	5.118	0.341	0.229	001C-08


MARKING: Available only embossed)

INTERPUMP Jet 2SC

TFN002K TFB002K

APPLICATIONS :





APPLICABLE SPECS. :
EN 857 2SC - ISO 7751

Dimensions according to EN 857 2SC. NO-SKIVE flexible line. Safety factor exceeding ISO 7751. Product designed for pressure wash applications. Any different use may reduce service life.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Covering: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Water, water-soap based, glicol-water based.


Operating temperature: from -40 to +135°C (intermittent 155°C).

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFN002KN04	1/4"	6.5	13.3	400	5800	1600	23200	75	2.953	0.281	0.189	001C-04
TFN002KN05	5/16"	8.0	14.8	400	5800	1400	20300	85	3.346	0.327	0.220	001C-05
TFN002KN06	3/8"	9.5	17.1	400	5800	1320	19140	90	3.543	0.418	0.281	001C-06
TFN002KN08	1/2"	12.7	20.4	400	5800	1100	15950	130	5.118	0.525	0.353	001C-08
TFB002KN04	1/4"	6.5	13.3	400	5800	1600	23200	75	2.953	0.281	0.189	001C-04
TFB002KN05	5/16"	8.0	14.8	400	5800	1400	20300	85	3.346	0.327	0.220	001C-05
TFB002KN06	3/8"	9.5	17.1	400	5800	1320	19140	90	3.543	0.418	0.281	001C-06
TFB002KN08	1/2"	12.7	20.4	400	5800	1100	15950	130	5.118	0.525	0.353	001C-08

MARKING: Available only embossed)

INTERPUMP Jet Plus 1SN

THN2011 THB2011



APPLICATIONS :



APPLICABLE SPECS. :
EN 853 1SN - ISO 7751

Dimensions according to EN 853 1SN. NO SKIVE flexible line. Safety factor exceeding 4:1. Product designed for pressure wash applications. Any different use may reduce service life.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 high tensile steel wire braid.

Recommended fluid: Water, water-soap based, glicol-water based.

Operating temperature: from -40 to +135°C (intermittent 155°C).

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THN2011-04	1/4"	6.4	13.4	250	3625	1000	14500	100	3.937	0.231	0.155	001C-04
THN2011-05	5/16"	8.0	15.0	250	3625	1000	14500	115	4.528	0.254	0.171	001C-05
THN2011-06	3/8"	9.5	17.4	250	3625	1000	14500	130	5.118	0.338	0.227	001C-06
THN2011-08	1/2"	12.7	20.6	250	3625	1000	14500	180	7.087	0.415	0.279	001C-08
THB2011-04	1/4"	6.4	13.4	250	3625	1000	14500	100	3.937	0.231	0.155	001C-04
THB2011-05	5/16"	8.0	15.0	250	3625	1000	14500	115	4.528	0.254	0.171	001C-05
THB2011-06	3/8"	9.5	17.4	250	3625	1000	14500	130	5.118	0.338	0.227	001C-06
THB2011-08	1/2"	12.7	20.6	250	3625	1000	14500	180	7.087	0.415	0.279	001C-08

MARKING: Available only "mylar"


INTERPUMP JETplus 1SN DN 12 I.D. 1/2" - W.P. 250 bar/3625 psi - MAX 155 °C

INTERPUMP Jet Plus 2SN

THN2021 THB2021

APPLICATIONS :





APPLICABLE SPECS. :
EN 853 2SN - ISO 7751

Dimensions according to EN 853 2SN. NO SKIVE flexible line. Safety factor exceeding 4:1. Product designed for pressure wash applications. Any different use may reduce service life.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Recommended fluid: Water, water-soap based, glicol-water based.

Operating temperature: from -40 to +135°C (intermittent 155°C).


Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THN2021-04	1/4"	6.5	15.0	400	5800	1600	23200	100	3.937	0.359	0.241	0022-04
THN2021-05	5/16"	8.0	16.6	400	5800	1600	23200	115	4.528	0.415	0.279	0022-05
THN2021-06	3/8"	9.5	19.0	400	5800	1600	23200	130	5.118	0.525	0.353	0022-06
THN0021-08	1/2"	12.7	22.2	400	5800	1600	23200	180	7.087	0.620	0.417	0022-08
THB2021-04	1/4"	6.5	15.0	400	5800	1600	23200	100	3.937	0.359	0.241	0022-04
THB2021-05	5/16"	8.0	16.6	400	5800	1600	23200	115	4.528	0.415	0.279	0022-05
THB2021-06	3/8"	9.5	19.0	400	5800	1600	23200	130	5.118	0.525	0.353	0022-06
THB2021-08	1/2"	12.7	22.2	400	5800	1600	23200	180	7.087	0.620	0.417	0022-08

MARKING: Available only "mylar"

INTERPUMP JETplus 2SN DN 12 I.D. 1/2" - W.P. 400 bar/5800 psi - MAX 155 °C

INTERPUMP Jet Plus 1SC

THN201K THB201K



APPLICATIONS :



APPLICABLE SPECS. :
EN 857 1SC - ISO 7751

Dimensions according to EN 857 1SC. NO SKIVE flexible line. Safety factor exceeding 4:1. Product designed for pressure wash applications. Any different use may reduce service life.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 steel wire braid.

Recommended fluid: Water, water-soap based, glicol-water based.

Operating temperature: from -40 to +135°C (intermittent 155°C).

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THN201K-04	1/4"	6.4	12.3	250	3625	1000	14500	75	2.953	0.182	0.122	001C-04
THN201K-05	5/16"	8.0	14.0	250	3625	1000	14500	85	3.346	0.203	0.136	001C-05
THN201K-06	3/8"	9.5	15.6	250	3625	1000	14500	90	3.543	0.256	0.172	001C-06
THN201K-08	1/2"	12.7	18.7	250	3625	1000	14500	130	5.118	0.341	0.229	001C-08
THB201K-04	1/4"	6.4	12.3	250	3625	1000	14500	75	2.953	0.182	0.122	001C-04
THB201K-05	5/16"	8.0	14.0	250	3625	1000	14500	85	3.346	0.203	0.136	001C-05
THB201K-06	3/8"	9.5	15.6	250	3625	1000	14500	90	3.543	0.256	0.172	001C-06
THB201K-08	1/2"	12.7	18.7	250	3625	1000	14500	130	5.118	0.341	0.229	001C-08

MARKING: Available only "mylar"


INTERPUMP JETplus 1SC DN 12 I.D. 1/2" - W.P. 250 bar/3625 psi - MAX 155 °C

INTERPUMP Jet Plus 2SC

THN202K THB202K

APPLICATIONS :





APPLICABLE SPECS. :
EN 857 2SC - ISO 7751

Dimensions according to EN 857 2SC. NO SKIVE flexible line. Safety factor exceeding 4:1. Product designed for pressure wash applications. Any different use may reduce service life.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Recommended fluid: Water, water-soap based, glicol-water based.

Operating temperature: from -40 to +135°C (intermittent 155°C).


Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THN202K-04	1/4″	6.5	13.4	400	5800	1600	23200	75	2.953	0.281	0.189	001C-04
THN202K-05	5/16″	8.0	15.0	400	5800	1600	23200	85	3.346	0.327	0.220	001C-05
THN202K-06	3/8″	9.5	17.4	400	5800	1600	23200	90	3.543	0.418	0.281	001C-06
THN202K-08	1/2″	12.7	20.6	400	5800	1600	23200	130	5.118	0.574	0.385	001C-08
THB202K-04	1/4″	6.5	13.4	400	5800	1600	23200	75	2.953	0.281	0.189	001C-04
THB202K-05	5/16″	8.0	15.0	400	5800	1600	23200	85	3.346	0.327	0.220	001C-05
THB202K-06	3/8″	9.5	17.4	400	5800	1600	23200	90	3.543	0.418	0.281	001C-06
THB202K-08	1/2″	12.7	20.6	400	5800	1600	23200	130	5.118	0.574	0.385	001C-08

MARKING: Available only "mylar"

INTERPUMP JETplus 2SC DN 12 I.D. 1/2" - W.P. 400 bar/5800 psi - MAX 155 °C

INTERPUMP SEWERJET 280

TSW2280



APPLICATIONS :



APPLICABLE SPECS. :
IMM SPECS - ISO 7751

A line dedicated to jet application, especially in clean up. Safety factor 2,5:1. NO-SKIVE compact tube. SMOOTH COVER. High abrasion resistance. Easy installation.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 or 2 high tensile steel wire braids.

Covering: Smooth synthetic rubber, resistant to oils, fuelsa and atmospheric conditions.

Recommended fluid: Water, water based fluids.

Operating temperature: 0°C÷+70°C for water, -40 °C ÷ +70°C for water based fluids.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TSW2280-06	3/8″	9.5	15.7	280	4000	700	10000	60	2.362	0.250	0.168	001C-06
TSW2280-08	1/2″	12.7	20.4	280	4000	700	10000	90	3.543	0.530	0.356	001C-08
TSW2280-12	3/4″	19.0	27.6	280	4000	700	10000	100	3.937	0.780	0.524	001C-12
TSW2280-16	1″	25.4	35.8	280	4000	700	10000	130	5.118	1.170	0.787	001C-16
(*)TSW2280-20	1.1/4″	31.8	43.1	280	4000	700	10000	200	7.874	1.530	1.028	001C-20

MARKING: Available only "mylar"

INTERPUMP SEWERJET 280 DN 19 I.D. 3/4" - W.P. 280 BAR/4000 PSI

INTERPUMP Hyblast 10k

TFW0070

APPLICATIONS :





APPLICABLE SPECS. :

IMM SPEC. - ISO 7751

Safety factor 2,5:1. Light and compact. ISO 7751.

Internal hose: Water resistant synthetic rubber.

Reinforcement: 4 steel wire spirals.

Covering: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Water, water-soap based, glicol-water based.

Operating temperature: from -10 to +70°C, Max 100°C.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule	Coupling Series
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft		
TFW0070-16	1 "	25.4	38.8	700	10150	1750	25375	280	11.024	2.100	1.413	00S4-16	W series

MARKING:Available also embossed brand version. In case of order use code TFW0070N.

INTERPUMP HY-BLAST 10k ISO 7751/S.F. 2,5 - DN 25 I.D. 1" - W.P. 700 BAR/10150 PSI

INTERPUMP Hyblast 12k

TFW0085



APPLICATIONS :



APPLICABLE SPECS. :
IMM SPEC. - ISO 7751

Safety factor 2,5:1. Light and compact. ISO 7751. Reliability and high performances.

Internal hose: Water resistant synthetic rubber.
Reinforcement: 4-6 high tensile steel wire spiral.
Covering: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.
Recommended fluid: Water, water-soap based, glicol-water based.
Operating temperature: from -10 to +70°C, Max 100°C.

Part number	ID		Max WP		Min BP		Min BR		Weight		Ferrule	Coupling Series
	in	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft		
TFW0085-04	1/4"	6.4	850	12325	30813	2125	110	4.331	0.570	0.384	0019-04	M series
TFW0085-06	3/8"	9.5	850	12325	30813	2125	140	5.512	0.730	0.491	00S4-06	W series
TFW0085-08	1/2"	12.7	850	12325	30813	2125	170	6.693	0.840	0.565	00S4-08	W series
TFW0085-12	3/4"	19.0	850	12325	30813	2125	220	8.661	1.690	1.137	00S4-12	W series
TFW0085-16	1"	25.4	850	12325	30813	2125	330	12.992	3.200	2.150	00Y6-16	Y series

MARKING: Available also embossed brand version. In case of order use TFW0085N.

INTERPUMP HY-BLAST 12k ISO 7751/S.F. 2,5 - DN 12 I.D. 1/2" - W.P. 850 BAR/12325 PSI

INTERPUMP Hyblast 15k

TFW0110 TFW0100

APPLICATIONS :





APPLICABLE SPECS. :

IMM SPEC. - ISO 7751

Safety factor 2,5:1. Light and compact. ISO 7751. Reliability and high performances.

Internal hose: Water resistant synthetic rubber.

Reinforcement: 4 steel wire spirals.

Covering: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Water, water-soap based, glicol-water based.

Operating temperature: from -10 to +70°C, Max 100°C.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule	Coupling Series
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft		
TFW0110-04	1/4"	6.4	17.0	1100	15950	2750	39875	110	4.331	0.570	0.384	0019-04	M series
TFW0110-06	3/8"	9.5	20.7	1100	15950	2750	39875	140	5.512	0.890	0.599	00S4-06	W series
TFW0110-08	1/2"	12.7	24.0	1100	15950	2750	39875	180	7.087	1.150	0.774	00S4-08	W series
TFW0100-12	3/4"	19.0	31.6	1000	14500	2500	36250	240	9.449	1.800	1.211	00Y4-12	Y series

MARKING: Available also embossed brand version. In case of order use code TFW0110N.

INTERPUMP HY-BLAST 15k ISO 7751/S.F. 2,5 - DN 10 I.D. 3/8" - W.P. 1100 BAR/15950 PSI

INTERPUMP Hyblast 18k

TFW0125 TFW0120



APPLICATIONS :



APPLICABLE SPECS. :
IMM SPEC. - ISO 7751

Safety factor 2,5:1. Light and compact. ISO 7751. Reliability and high performances.

Internal hose: Water resistant synthetic rubber.
Reinforcement: 4 steel wire spirals.
Covering: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.
Recommended fluid: Water, water-soap based, glicol-water based.
Operating temperature: from -10 to +70°C, Max 100°C.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule	Coupling Series
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft		
TFW0125-06	3/8″	9.5	20.7	1250	18125	3125	45313	160	6.229	0.920	0.619	00Y4-06	Y series
TFW0120-08	1/2″	12.7	24.0	1200	17400	3000	43500	200	7.874	1.190	0.801	00Y4-08	Y series

MARKING: Available also embossed brand version. In case of order use code TFW0125N.


INTERPUMP HY-BLAST 18k ISO 7751/S.F. 2,5 - DN 10 I.D. 3/8" - W.P. 1250 BAR/18125 PSI

INTERPUMP Hyblast 20k

TFW0145 TFW0135

APPLICATIONS :





APPLICABLE SPECS. :

IMM SPEC. - ISO 7751

Safety factor 2,5:1. Light and compact. ISO 7751. Reliability and high performances.

Internal hose: Water resistant synthetic rubber.

Reinforcement: 6 steel wire spirals.

Covering: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Water, water-soap based, glicol-water based.

Operating temperature: from -10 to +70°C, Max 100°C.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule	Coupling Series
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft		
TFW0145-06	3/8"	9.5	23.3	1450	21025	3625	52563	180	7.087	1.350	0.909	00Y6-06	Y series
TFW0145-08	1/2"	12.7	27.0	1450	21025	3625	52563	220	8.661	1.800	1.211	00Y6-08	Y series
TFW0135-12	3/4"	19.0	35.0	1350	19575	3375	48938	260	10.236	2.670	1.797	00Y6-12	Y series

MARKING: Available also embossed brand version. In case of order use code TFW0145N.

INTERPUMP HY-BLAST 20k ISO 7751/S.F. 2,5 - DN 12 I.D. 1/2" - W.P. 1450 BAR/21025 PSI

INTERPUMP LongLift 1SC

THL201K



APPLICATIONS :

APPLICABLE SPECS. :
EXCEED EN 857 1SC- ISO 112237 1SC

NO-SKIVE hose. High abrasion resistance. Pressure rating exceeding standards. Easy to install. Approved and released for lift truck application. High resistance and elasticity. High flexibility at small bend radius. SMOOTH COVER.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 high tensile steel wire braids.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to + 120° C (Intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THL201K-04	1/4″	6.4	12.3	250	3625	1120	16240	50	1.969	0.182	0.122	001C-04
THL201K-05	5/16″	8.0	13.5	250	3625	1000	14500	55	2.165	0.210	0.141	001C-05
THL201K-06	3/8″	9.5	15.7	250	3625	1000	14500	60	2.362	0.248	0.167	001C-06
THL201K-08	1/2″	12.7	18.9	200	2900	800	11600	70	2.756	0.391	0.263	001C-08
THL201K-10	5/8″	16.0	22.4	150	2175	600	8700	90	3.543	0.410	0.276	001C-10
THL201K-12	3/4″	19.0	26.0	150	2175	600	8700	100	3.937	0.534	0.359	001C-12
THL201K-16	1″	25.4	33.7	110	1595	440	6380	180	7.087	0.742	0.499	001C-16

MARKING: Available only "mylar"

INTERPUMP LongLift EXCEEDS EN857 - 1SC DN10 I.D. 3/8" W.P. 25,0 Mpa (3600 PSI)

INTERPUMP LongLift 2SC

THL202K

APPLICATIONS :





APPLICABLE SPECS. :

EXCEED EN 857 2SC - ISO 11237

NO-SKIVE hose. High abrasion resistance. Pressure rating exceeding standards. Easy to install. Approved and released for lift truck application. High resistance and elasticity. High flexibility at small bend radius. SMOOTH COVER.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Covering: Smooth synthetic rubber, resistant to oils, fuelsa and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to + 120° C (Intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.


Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THL202K-04	1/4"	6.4	13.3	430	6235	1720	24940	50	1.969	0.283	0.190	001C-04
THL202K-05	5/16"	8.0	14.8	400	5800	1600	23200	60	2.362	0.324	0.218	001C-05
THL202K-06	3/8"	9.5	17.1	350	5075	1400	20300	70	2.756	0.418	0.281	001C-06
THL202K-08	1/2"	12.7	20.4	310	4495	1240	17980	80	3.150	0.521	0.350	001C-08
THL202K-10	5/8"	16.0	23.5	280	4060	1120	16240	100	3.937	0.626	0.421	001C-10
THL202K-12	3/4"	19.0	27.6	240	3480	960	13920	120	4.724	0.764	0.513	001C-12
THL202K-16	1"	25.4	35.8	210	3045	840	12180	160	6.299	1.171	0.787	001C-16

MARKING: Available only "mylar"


INTERPUMP LongLift EXCEEDS EN857 - 2SC DN 19 I.D. 3/4" W.P. 24,0 MPa (3480 psi) - MADE IN ITALY

INTERPUMP LongLife Dual 1SC

T2E101K



APPLICATIONS :



APPLICABLE SPECS. :
EXCEED EN 857 - ISO 11237

No-SKIVE hose. High abrasion resistance. Pressure rating exceeding standards. Easy to install. SMOOTH COVER.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.
Reinforcement: 1 or 2 high tensile steel wire braids.
Covering: Smooth synthetic rubber, resistant to oils, fuelsa and atmospheric conditions.
Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.
Operating temperature: from -40 to + 120° C (Intermittent 135°C), from -40 to +70° C for water based fluids.

Part number	ID		OD	T.H	T.H. Max	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
T2E101K-04	1/4	6.4	12.4	24.8	26	250	3625	1120	16240	50	1.969	0.364	0.244	001C-04
T2E101K-05	5/16	8.0	13.5	27.0	28.2	250	3625	1000	14500	55	2.165	0.420	0.282	001C-05
T2E101K-06	3/8	9.5	15.6	31.2	32.6	250	3625	1000	14500	60	2.362	0.490	0.330	001C-06
T2E101K-08	1/2	12.7	19.0	38	39.4	200	2900	800	11600	70	2.756	0.782	0.525	001C-08

A specific machine is available to split the twin hose . In case of order use code MHSXA001.




MARKING: Available also white ink-jet brand version. In case of order use code T2E101KI.

INTERPUMP LongLife Dual EXCEEDS EN 857 - 1SC DN 10 I.D. 3/8" - W.P. 25,0 MPa/3625 PSI

INTERPUMP LongLife Dual 2SC

T2E102K

APPLICATIONS :





APPLICABLE SPECS. :

EXCEED EN 857 - ISO 11237 2SC

No-SKIVE hose. High abrasion resistance. Pressure rating exceeding standards. Easy to install. SMOOTH COVER.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 or 2 high tensile steel wire braids.

Covering: Smooth synthetic rubber, resistant to oils, fuelsa and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to + 120° C (Intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	T.H	T.H. Max	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
T2E102K-04	1/4	6.4	13.3	26.6	27.8	430	6235	1720	24940	60	2.362	0.566	0.380	001C-04
T2E102K-06	3/8	9.5	17.1	34.2	32.6	350	5075	1400	20300	70	2.756	0.836	0.561	001C-06
T2E102K-08	1/2	12.7	20.5	41	42.4	310	4495	1240	17980	80	3.150	1.042	0.699	001C-08

A specific machine is available to split the twin hose . In case of order use code MHSXA001.



.

MARKING: Available also white ink-jet brand version. In case of order use code T2E102KI.

INTERPUMP Long Life Dual EXCEEDS EN857 - 2SC DN10 I.D. 3/8" W.P. 35,0 Mpa (5075 PSI)

INTERPUMP HyRail

TFDE011



APPLICATIONS :



TYPE APPROVAL :
ISO 11925, EN 45545-2

APPLICABLE SPECS. :
IMM - SAE 100R1AT - EN 853 1SN - ISO 1436

Pressure, dimensions and bend radius ratings in accordance with EN 853 1SN, ISO 1436 1SN and SAE 100R1AT. Fire Retardant Cover. For air or gas application hose cover pin-priked.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 steel wire braid.

Covering: Synthetic rubber fire resistant

Recommended fluid: Mineral and biological oils, water, water based fluids, compressed air.

Operating temperature: from -40 to +100°C (intermittent 120°C) for oils, from -40 to 70°C for water based fluids and compressed air, from 0 to +70°C for water,.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFDE011-04	1/4"	6.4	13.4	225	3263	900	13050	100	3.937	0.231	0.155	001C-04
TFDE011-05	5/16"	8.0	15.0	215	3118	860	12470	115	4.528	0.254	0.171	001C-05
TFDE011-06	3/8"	9.5	17.4	180	2610	720	10440	125	4.921	0.338	0.227	001C-06
TFDE011-08	1/2"	12.7	20.6	160	2320	640	9280	180	7.087	0.415	0.279	001C-08
TFDE011-10	5/8"	16.0	23.7	130	1885	520	7540	200	7.874	0.477	0.321	001C-10
TFDE011-12	3/4"	19.0	27.7	105	1523	420	6090	240	9.449	0.618	0.415	001C-12
TFDE011-16	1 "	25.4	35.6	88	1276	352	5104	300	11.811	0.901	0.605	001C-16


MARKING: Available also embossed brand version. In case of order use TFDE011N.

INTERPUMP HyRail DN 8 I.D. 5/16" - W.P. 215 bar/3118 psi - EN 45545 - MADE IN ITALY

INTERPUMP Power Lift - 1SC/2SC

APPLICATIONS :

THE0L1K THE0L2K



APPLICABLE SPECS. :

UNI EN 81-20 - EXCEED EN 857 - ISO 11237

Compact hose with low bend radius. For lift solutions. Safety factor 8:1.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 or 2 high tensile steel wire braids.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C (intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE0L1K-16	1 "	25.4	33.7	50	725	400	5800	180	7.087	0.750	0.504	001C-16
THE0L1K-20	1.1/4"	31.8	41.1	50	725	400	5800	210	8.268	1.280	0.860	001C-20
THE0L1K-24	1.1/2"	38.1	48.6	45	653	360	5220	300	11.811	1.390	0.934	001C-24
THE0L2K-24	1.1/2"	38.1	50.6	50	725	400	5800	300	11.811	2.100	1.411	001C-24
THE0L2K-32	2 "	50.8	63.5	50	725	400	5800	400	15.748	1.176	0.790	001C-32

MARKING: Available only "mylar"


INTERPUMP POWERLIFT EXCEEDS - ISO 11237/EN 857 - EN 81.2 1SC DN 38 I.D. 1.1/2" - W.P. 45 BAR/653 PSI

INTERPUMP HYJACK

THE2J2K



APPLICATIONS :



APPLICABLE SPECS. :
IMM SPECS

Tested for jack applications up to a static pressure of 760 bar/11000 psi. Compact version. Safety factor> 2: 1. Smooth cover. Tested and released with dedicated fitting (002M bushing + Multispiral couplings).

Internal hose: Oil resistant synthetic rubber.
Reinforcement: 2 high-load steel wire braids.
Covering: Synthetic rubber resistant to oils, fuels, atmospheric conditions and abrasion.
Recommended fluid: Mineral and biological oils.
Operating temperature: from -40 to +100°C.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE2J2K-04	1/4"	6.4	13.3	760	11000	1672	24200	75	2.953	0.281	0.189	002M-04
THE2J2K-06	3/8"	9.5	17.1	725	10500	1595	23100	90	3.543	0.422	0.284	002M-06

MARKING: Available only "mylar"




Hypress Snow Storm 1SC

THEPS1K

APPLICATIONS :





APPLICABLE SPECS. :
IMM - ISO 7751

Great performance with air. water and under thermal shock. Excellent resistance to UV, ozone and abrasion. Safety factor 2.5:1.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 high tensile steel wire braids.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions with UHMWPE film.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.


Operating temperature: from -40 to +100°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THEPS1KB16	1 "	25.4	34.2	100	1450	250	3625	200	7.874	0.742	0.499	001C-16
THEPS1KB24	1.1/2"	38.1	47.7	100	1450	250	3625	400	15.748	1.390	0.934	001C-24
THEPS1KB32	2 "	50.8	61.5	100	1450	250	3625	500	19.685	1.940	1.304	001C-32

Also available in black color THEPS1KN.

INTERPUMP HyTruck 200 bar

TTRK200



APPLICATIONS :

APPLICABLE SPECS. :
IMM SPECS

NO-SKIVE hose. A line dedicated to tipper applications. Safety factor 2,5:1.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness oil and water resstant.

Reinforcement: 1 braid (DN19) or 2 braids (DN25) made of high tensile steel wire.

Covering: Synthetic rubber resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C (intermittent 125°). from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TTRK200-12	3/4"	19.0	26.0	200	2900	500	7250	180	7.087	0.492	0.330	001C-12
TTRK200-16	1"	25.4	35.8	200	2900	500	7250	250	9.843	1.171	0.787	001C-16


INTERPUMP HYTRUCK DN 25 I.D. 1" W.P. 200 bar/2900 psi - S.F. 2,5:1

INTERPUMP HyTruck 250 bar

TTRK250

APPLICATIONS :





APPLICABLE SPECS. :
IMM SPECS

NO-SKIVE hose. A line dedicated to tipper applications. Safety factor 2,5:1.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness oil and water resstant.

Reinforcement: 1 braid (DN19) or 2 braids (DN25) made of high tensile steel wire.

Covering: Synthetic rubber resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C (intermittent 125°), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TTRK250-12	3/4"	19.0	26.0	250	3625	625	9063	180	7.087	0.534	0.359	001C-12
TTRK250-16	1"	25.4	35.8	250	3625	625	9063	250	9.843	1.171	0.787	001C-16

INTERPUMP HYTRUCK DN 19 I.D. 3/4" W.P. 250 bar/3625 psi - S.F. 2,5:1

INTERPUMP HyTruck 350 bar

TTRK350



APPLICATIONS :



APPLICABLE SPECS. :
IMM SPECS

NO-SKIVE hose. A line dedicated to tipper applications. Safety factor 2,5:1.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness oil and water resstant.

Reinforcement: 2 high tensile steel wire braids.

Covering: Synthetic rubber resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.


Operating temperature: from -40 to +100°C (intermittent 125°), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TTRK350-12	3/4"	19.0	26.0	350	5075	875	12688	200	7.874	0.782	0.525	001C-12
TTRK350-16	1"	25.4	35.8	350	5075	875	12688	250	9.843	1.171	0.787	001C-16

INTERPUMP MEGADRILL

THEMMDR

APPLICATIONS :



TYPE APPROVAL :

MSHA



APPLICABLE SPECS. :

EXCEEDS ISO 3862 TYPE R13 - IMM SPECS

High pressure hoses. Power lines/severe applications. Perforations.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 6 high tensile steel wire spirals.

Covering: Abrasion resistant synthetic rubber resistant to oils, fuels, atmospheric conditions. MSHA.

Recommended fluid: Hydraulic fluids petroleum based (mineral oils), glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C (intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THEMMDRN40	2.1/2"	63.5	84.5	350	5075	1400	20300	900	35.430	8.173	5.492	0013-40
THEMMDRN48	3"	76.2	97.3	350 (*) / 210 (**)	5075 (*) / 3045 (**)	880	12760	1000	39.370	9.515	6.393	0013-48

MARKING: Available only "embossed"

INTERPUMP Mega Jet

TFS04JG THS00JG



APPLICATIONS :



APPLICABLE SPECS. :
IMM - ISO 7751

High performance structure. High ozone and weather conditions resistance. Safety factor 2,5:1 o 3,5:1 according to ISO 7751.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness, abrasion resistant.
Reinforcement: 4-6 high tensile steel wire spiral.
Covering: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.
Recommended fluid: Water, water-soap based, water grout based.
Operating temperature: from -40 to +100°C, from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS04JGN16	1″	25.4	38.4	550	7975	1375	19938	220	8.661	2.104	1.414	004N-16
TFS04JGN20	1.1/4″	31.8	45.8	450	6525	1125	16313	400	15.748	2.550	1.714	004N-20
TFS04JGN24	1.1/2″	38.1	53.5	450	6525	1125	16313	560	22.047	3.225	2.167	004N-24
TFS04JGN32	2″	50.8	67.0	420	6090	1050	15225	650	25.591	4.400	2.957	004N-32
THS00JGN16	1″	25.4	42.2	600	8700	2100	30450	330	12.992	3.200	2.151	00J6-16
THS00JGN20	1.1/4″	31.8	49.7	550	7975	1925	27913	265	10.433	3.891	2.615	0013-20
THS00JGN24	1.1/2″	38.1	57.8	500	7250	1750	25375	310	12.205	5.182	3.483	0013-24
THS00JGN32	2″	50.8	71.5	480	6960	1680	24360	600	23.623	6.700	4.503	0013-32

Available on request with external antiabrasion UHMWPE film (in case of order use code TFSP4JG)

MARKING: Available only "embossed"

INTERPUMP BOP FIRESCREEN 5000

TBOP350

APPLICATIONS :

TYPE APPROVAL :
API16-D, LLOY'D OD 1000/499



APPLICABLE SPECS. :
API16-D - LLOYD'S REGISTER OD 1000/499 REV.2

Isobaric line 5000 psi. Flame resistance tested iaw API 16-D Integrated with lloyd's register OD 1000/499 rev 2 Flame Resistance Test

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 6 high tensile steel wire spirals.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Hydraulic fluids petroleum based (mineral oils), glicol-water based, water, lubricants.

Operating temperature: from -40 to + 120° C petroleum based fluids (Intermittent 125°), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TBOP350N32	2"	50.8	71.5	350	5075	1400	20300	635	25.000	6.890	4.629	0013-32

MARKING: Available only "embossed"

INTERPUMP HyGEAR 1SC

THE0G1K



APPLICATIONS :

APPLICABLE SPECS. :
EXCEED EN 857 1SC, ISO 11237 1SC

NO-SKIVE tube. High abrasion resistance. Easy assembly. Suitable for the use with the "GearBox" and "ATF" oils. Exceeds EN 853 impulse test requirements.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 1 high tensile steel wire braids.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE0G1K-12	3/4"	19	26.0	105	1523	420	6090	120	4.724	0.546	0.367	001C-12
THE0G1K-16	1"	25.4	33.7	88	1276	352	5104	150	5.906	0.759	0.510	001C-16
THE0G1K-20	1.1/4"	31.8	41.1	82	1189	328	4756	210	8.268	1.110	0.746	001C-20
THE0G1K-24	1.1/2"	38.1	48.6	82	1190	328	4756	250	9.842	1.319	0.886	001C-24
THE0G1K-32	2 "	50.8	61.5	68	986	272	3944	315	12.402	1.767	1.187	001C-32
THE0G1K-40	2.1/2"	63.5	73.5	35	508	140	2030	500	19.685	2.108	1.417	001C-40

MARKING: Available also "embossed" brand version. In case of order use THE0G1KN

Thermoplastic Hoses

Index

SAE 100 R7

TFS0007



SAE 100R7 Double

77

SAE 100 R8

TFS0008



SAE 100R8

78

SAE 100 R7

TFS00H1



One high tensile steel wire braid

79

TFS00H2



Two high tensile steel wire braid

80

Very High Pressure

TFS00HP



INTERPUMP HyUltra

81

Low temperature

TFS0018



R18 - Isobaric - Low temperature

82

TFS00CP



Costant pressure low temperature

83

MICROBORE

TFS00MP



Mini-flexible hose

84

CO2

TI00CO2



INTERPUMP HyFire


85

Dimensions and general characteristics may be changed at any time, data contained here in are only for information purpose only and it does not enlarge, amend or imply any warranty other than provided by us with the product. Any use of the product not in conformance with our instructions may be dangerous.

SAE 100R7
TFS0007



APPLICATIONS :



TYPE APPROVAL :
MSHA

APPLICABLE SPECS. :
EXCEED SAE 100R7 - ISO 3949 R7

Exceeds SAE 100R7. Light and flexible, abrasion resistant. Limited change in lenght. Pinpricked cover.

Internal hose: Polyester elastomer.
Reinforcement: One or two braids of synthetic fiber.
Covering: Polyurethane, black, pinpricked, white ink-jet branding.
Recommended fluid: Hydraulic fluids petroleum based, glicol-water based, lubrificant.
Operating temperature: from -40 to +100°C continuous for air and water based fluids.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS0007-02	1/8"	4.0	8.3	210	3045	840	12180	25	0.984	0.050	0.034	*
TFS0007-03	3/16"	5.0	9.6	210	3045	840	12180	25	0.984	0.060	0.040	0007-03
TFS0007-04	1/4"	6.5	11.8	210	3045	840	12180	35	1.378	0.090	0.060	0007-04
TFS0007-05	5/16"	8.1	13.9	190	2755	760	11020	60	2.362	0.115	0.077	0007-05
TFS0007-06	3/8"	9.7	16.0	160	2320	640	9280	55	2.165	0.145	0.097	0007-06
TFS0007-08	1/2"	13.0	20.1	140	2030	560	8120	75	2.953	0.210	0.141	0007-08
TFS0007-10	5/8"	16.3	23.7	105	15225	420	6090	110	4.331	0.280	0.188	0007-10
TFS0007-12	3/4"	19.5	27.1	90	1305	360	5220	140	5.512	0.335	0.225	0007-12
TFS0007-16	1 "	25.9	34.0	70	1015	280	4060	190	7.480	0.455	0.305	0007-16

Available also in twin version (in case of order use code T2S0007)



Available also in 'No conductive' version - (in case of order use code TFS0NC7)



Available also in 'Neptune' version - marine application (in case of order use code TFS00M7)



Available also in 'Nautilus' version - off-shore equipment (in case of order use code TFS00Y7)




Available also in 'Solvent' version - (in case of order use code TFS00V7)



SAE 100R8
TFS0008

APPLICATIONS :





TYPE APPROVAL :
MSHA

APPLICABLE SPECS. :
EXCEED SAE 100R8 - ISO 3949 R8

Exceeds SAE 100R8. Light and flexible, abrasion resistant. Limited change in lenght. Pinpricked cover.

Internal hose: Polyester elastomer.
Reinforcement: One or two braids of aramid fiber.
Covering: Polyurethane, black, pinpricked, white ink-jet branding.
Recommended fluid: Hydraulic fluids petroleum based, glicol-water based, lubrificant.
Operating temperature: from -40 to +100°C continuous for air and water based fluids.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS0008-02	1/8"	4.0	8.0	420	6090	1680	24360	25	0.984	0.045	0.030	0008-02
TFS0008-03	3/16"	5.0	8.9	350	5075	1400	20300	30	1.181	0.050	0.034	0008-03
TFS0008-04	1/4"	6.5	11.5	350	5075	1400	20300	50	1.969	0.085	0.057	0008-04
TFS0008-05	5/16"	8.1	13.4	300	4350	1200	17400	55	2.165	0.105	0.071	0008-05
TFS0008-06	3/8"	9.7	15.5	280	4060	1120	16240	60	2.362	0.135	0.091	0008-06
TFS0008-08	1/2"	13.0	19.9	245	35525	980	14210	80	3.150	0.200	0.134	0008-08
TFS0008-10	5/8"	16.3	23.4	200	2900	800	11600	125	4.921	0.250	0.168	0008-10
TFS0008-12	3/4"	19.5	27.1	165	23925	660	9570	150	5.906	0.320	0.215	0008-12
TFS0008-16	1 "	25.9	34.2	140	2030	560	8120	200	7.874	0.435	0.292	0008-16

Available also in twin version (in case of order use code T2S0008).





Available also in 'Nautilus' version - off-shore equipment (in case of order use code TFS00Y8).





Available also in 'Neptune' version - marine application (in case of order use code TFS00M7).





Available also in 'Solvent' version (in case of order use code TFS00V8).



Available also in 'No conductive' version (in case of order use code TFS0NC8).



One high tensile steel wire braid

TFS00H1

APPLICATIONS :





TYPE APPROVAL :

MSHA

APPLICABLE SPECS. :

SAE 100R1 - MEETS OR EXCEEDS PRESSURE LEVEL OF EN 853 1SN - EN 857 1SC

Slim line construction for compact installation and flexibility. Lightweight. Steel braid offers low volumetric expansion and optimum in length characteristics. Abrasion resistant.

Internal hose: Polyester elastomer.

Reinforcement: One braid of steel wire.

Covering: Polyurethane, black, white ink-jet branding.

Recommended fluid: Hydraulic fluids petroleum based, glicol-water based, lubrificant.

Operating temperature: from -40 to +100°C continuous for air and water based fluids.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS00H1-03	3/16"	5.0	9.7	360	5220	1440	20880	30	1.181	0.120	0.081	0008-03
TFS00H1-04	1/4"	6.4	11.7	310	4495	1240	17980	40	1.575	0.165	0.111	0008-04
TFS00H1-05	5/16"	8.1	13.2	250	3625	1000	14500	55	2.165	0.190	0.128	0008-05
TFS00H1-06	3/8"	9.8	15.5	225	3263	900	13050	65	2.559	0.230	0.155	0008-06
TFS00H1-08	1/2"	13.0	18.8	190	2755	760	11020	85	3.346	0.300	0.202	0008-08
TFS00H1-10	5/8"	16.3	22.0	140	2030	560	8120	115	4.528	0.335	0.225	0008-10
TFS00H1-12	3/4"	19.5	25.8	115	1668	460	6670	145	5.709	0.460	0.309	0008-12
TFS00H1-16	1"	25.8	33.4	95	1378	380	5510	180	7.087	0.640	0.430	0008-16

Available also in "Neptune" version - marine application (in case of order use code TFS0H1M). NO MSHA.



Available also in 'Solvent' version (in case of order use code TFS00V1). NO MSHA.




Available also in twin version (in case of order use code T2S00H1)



Two high tensile steel wire braids

TFS00H2

APPLICATIONS :



TYPE APPROVAL :
MSHA



APPLICABLE SPECS. :
MEETS OR EXCEEDS SAE 100R2 PERFORMANCE

Rugged construction for HD application and prolonged lifetime. Suitable in harsh condition. Abrasion resistant.

Internal hose: Polyester elastomer.
Reinforcement: Two braid of steel wire.
Covering: Polyurethane, black, white ink-jet branding.
Recommended fluid: Hydraulic fluids petroleum based, glicol-water based, lubrificant.
Operating temperature: from -40 to +100°C continuous for air and water based fluids.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS00H2-04	1/4"	6.4	12.8	400	5800	1600	23200	40	1.575	0.245	0.165	0022-04
TFS00H2-06	3/8"	9.8	16.8	330	4785	1320	19140	65	2.559	0.370	0.249	0022-06
TFS00H2-08	1/2"	13.0	20.2	260	3770	1040	15080	85	3.346	0.455	0.306	0022-08
TFS00H2-10	5/8"	16.3	23.5	220	3190	880	12760	115	4.528	0.560	0.376	0022-10
TFS00H2-12	3/4"	19.5	27.5	150	2175	660	9570	170	6.693	0.700	0.470	0022-12

Available also in twin version (in case of order use code T2S00H2).



Available also in 'Solvent' version (in case of order use code TFS00V2). NO MSHA.



INTERPUMP HyUltra
TFS00HP



APPLICATIONS :



TYPE APPROVAL :
MSHA

APPLICABLE SPECS. :

Combined Aramid + Steel braid construction for compact design. Lightweight and flexible. Narrow bending radius for use on hose reels and in tight enviroments. Antiabrasion cover.

Internal hose: Polyester elastomer.
Reinforcement: One or two braid of aramid fiber plus one steel braid.
Covering: Polyurethane, black, white ink-jet branding.
Recommended fluid: Hydraulic fluids petroleum based, glicol-water based, lubrificant.
Operating temperature: from -40 to +100°C continuous for air and water based fluids.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS00HP-04	1/4"	6.6	12.7	700	10150	2800	40600	35	1.378	0.180	0.121	0019-04
TFS00HP-06	3/8"	9.8	18.7	700	10150	2800	40600	90	3.543	0.330	0.222	*

Available also in twin version (in case of order use code T2S00HP).



Available also in 'No conductive' version (in case of order use code TFSNCHP). NO MSHA.



R18 Low temperature
TFS0018

APPLICATIONS :





APPLICABLE SPECS. :

MEETS OR EXCEEDS SAE 100R18

Optimum bonding. Special polyester cover operating in cold enviroment. Tight bend radius. Microperforated covering.

Internal hose: Polyester elastomer.

Reinforcement: One or two braids of synthetic fiber.

Covering: Special polyester.

Recommended fluid: Hydraulic fluids petroleum based, glicol-water based, lubrificant.


Operating temperature: from -55 to +100°C continuous for air and water based fluids.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS0018-03	3/16"	5.0	9.6	210	3045	840	12180	25	0.984	0.060	0.040	0008-03
TFS0018-04	1/4"	6.5	12.2	210	3045	840	12180	35	1.378	0.095	0.064	0008-04
TFS0018-05	5/16"	8.1	14.3	210	3045	840	12180	45	1.772	0.130	0.087	0008-05
TFS0018-06	3/8"	9.7	16.6	210	3045	840	12180	45	1.772	0.165	0.111	0008-06
TFS0018-08	1/2"	13.0	22.5	210	3045	840	12180	70	2.756	0.295	0.198	*
TFS0018-10	5/8"	16.3	26.1	210	3045	840	12180	100	3.937	0.370	0.249	*


Available also in twin version (in case of order use code T2S0018).



Mini-flexible
TFS00MP



APPLICATIONS :



APPLICABLE SPECS. :

Very flexible and lightweight. Kink resistance. Antistick cover allow use of hose bundles for easy routing. Nipples fittings range.

Internal hose: Polyester elastomer.

Reinforcement: One braid of aramid fiber.

Covering: Antigrip polyurethane, black, pinpricked.

Recommended fluid: Hydraulic fluids petroleum based, glicol-water based, lubrificant.

Operating temperature: from -40 to +100°C continuous for air and water based fluids.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS00MP-012	5/64″	2.0	5.0	630	9135	1900	27550	20	0.787	0.020	0.013	*
TFS00MP-020	1/8″	3.0	6.0	630	9135	1900	27550	30	1.181	0.025	0.017	*
TFS00MP-025	5/32″	4.0	8.0	630	9135	1900	27550	40	1.575	0.045	0.030	*

Available also in twin version (in case of order use code T2S00MP).



INTERPUMP HyFire
TI00CO2

APPLICATIONS :



TYPE APPROVAL :

MSHA



APPLICABLE SPECS. :

MEETS OR EXCEEDS EN 853 1SN - EN 854 1SC - SAE 100R1 PERFOR-MANCE LEVEL

One steel braid design for increased mechanical and pressure resistance. Operating temperatures from -60°C to +93°C. Pinpricked cover. Also suitable for use of connection between bottles/valves and manifolds for CO2 main fire extinguishing systems. The low temperature resistance of cover increases lifetime of these hoses.

Internal hose: Polyester elastomer.

Reinforcement: One braid of steel wire.

Covering: Polyurethane, black, pinpricked, white ink-jet branding.

Operating temperature: from -60 to +93°C.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TI00CO2-03	3/16"	5.0	9.7	300	4350	1200	17400	30	1.181	0.125	0.084	*
TI00CO2-04	1/4"	6.4	11.7	275	3988	1100	15950	40	1.575	0.155	0.104	*
TI00CO2-05	5/16"	8.0	13.2	212	3074	848	12296	55	2.165	0.190	0.128	*
TI00CO2-06	3/8"	9.8	15.5	212	3074	848	12296	65	2.559	0.230	0.155	*
TI00CO2-08	1/2"	13.0	18.8	175	2538	700	10150	85	3.346	0.300	0.202	*
TI00CO2-10	5/8"	16.3	22.0	140	2030	560	8120	115	4.528	0.320	0.215	*

Available also in twin version (in case of order use code T2S00C02).



Costant pressure low temperature

TFS00CP



APPLICATIONS :



APPLICABLE SPECS. :

EXCEEDS SAE 100R18

Optimum bonding. Special polyester cover operating in cold enviroment. Tight bend radius. Microperforated covering.

Internal hose: Polyester elastomer.

Reinforcement: One or two braids of synthetic fiber.

Covering: Special polyester, pinprinked.

Recommended fluid: Hydraulic fluids petroleum based, glicol-water based, lubrificant.

Operating temperature: from -55 to +100°C continuous +70°C for water based fluids.

Part number	ID		OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm	mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFS00CP-03	3/16″	5.0	9.6	250	3600	1000	14400	25	0.984	0.060	0.040	0008-03
TFS00CP-04	1/4″	6.5	13.0	250	3600	1000	14400	35	1.378	0.115	0.077	0008-04
TFS00CP-05	5/16″	8.1	15.0	250	3600	1000	14400	45	1.772	0.145	0.097	0008-05
TFS00CP-06	3/8″	9.7	18.0	250	3600	1000	14400	55	2.170	0.205	0.138	0008-06

P.T.F.E. Hoses

PTFE Hoses

TF000T1



Tubo P.T.F.E. tipo T1

89

TF00TP1



Tubo P.T.F.E. tipo TP1

90

TF000T2



Tubo P.T.F.E. tipo T2

91

TF00THP



Tubo P.T.F.E. tipo THP

92

TF00LTC



Tubo P.T.F.E. corrugato tipo LTC

93


Dimensions and general characteristics may be changed at any time, data contained here in are only for information purpose only and it does not enlarge, amend or imply any warranty other than provided by us with the product. Any use of the product not in conformance with our instructions may be dangerous.

P.T.F.E. - T1

TF000T1



APPLICATIONS :



APPLICABLE SPECS. :

SAE 100 R14

Hose for use with IMM Hydraulics fittings.Standard tail.

Internal hose: Smooth P.T.F.E. thin wall.

Covering: 1 high tensile stainless steel AISI 304 wire braids


Operating temperature: from -70 to +260°C.

Part number	ID		OD	Min BR		Ferrule
	in	mm	mm	mm	inch	
TF000T1-03	3/16"	4,8	7.4	35	1.378	PTFE-03
TF000T1-04	1/4"	6,35	9	45	1.772	PTFE-04
TF000T1-05	5/16"	7,9	10.8	50	1.969	PTFE-05
TF000T1-06	3/8"	9,50	12.4	55	2.165	PTFE-06
TF000T1-08	1/2"	12,7	15.7	70	2.756	PTFE-08
TF000T1-10	5/8"	15,90	19.1	130	5.118	PTFE-10
TF000T1-12	3/4"	19,0	22.2	190	7.480	PTFE-12
TF000T1-16	1 "	25,40	29.7	270	10.630	PTFE-16

For temperature over 100°C, please contact our technical department

P.T.F.E. - TP1
TF00TP1

APPLICATIONS :





APPLICABLE SPECS. :

Hose for use with IMM Hydraulics fittings.Standard tail.

Internal hose: Smooth P.T.F.E. medium thickness wall.
Covering: 1 high tensile stainless steel AISI 304 wire braids
Operating temperature: from -70 to +260°C.

Part number	ID		OD	Min BR		Ferrule
	in	mm	mm	mm	inch	
TF00TP1-03	3/16"	4.8	7.8	35	1.378	*
TF00TP1-04	1/4"	6.35	9.4	45	1.772	*
TF00TP1-05	5/16"	7.9	11.2	50	1.969	*
TF00TP1-06	3/8"	9.5	12.8	55	2.165	*
TF00TP1-07	13/32"	10.3	13.6	65	2.559	*
TF00TP1-08	1/2"	12.7	16	70	2.756	*
TF00TP1-10	5/8"	15.9	19.4	130	5.118	*
TF00TP1-12	3/4"	19	22.5	190	7.480	*
TF00TP1-14	7/8"	22.2	26	250	9.843	*
TF00TP1-16	1"	25.4	29.4	270	10.630	*


(*) Ask to our Technical Office - For temperatures over 100 ° C contact our Technical office

P.T.F.E. - T2

TF000T2



APPLICATIONS :



APPLICABLE SPECS. :

Hose for use with IMM Hydraulics fittings.Standard tail.

Internal hose: Smooth P.T.F.E..

Covering: 2 high tensile stainless steel AISI 304 wire braids

Operating temperature: from -70 to +260°C.

Part number	ID		OD	Min BR		Weight	Ferrule
	in	mm	mm	mm	inch	lb/ft	
TF000T2-03	3/16"	4.8	8.8	30	1.181	0.094	*
TF000T2-04	1/4"	6.4	10.4	35	1.378	0.123	*
TF000T2-05	5/16"	7.9	12	40	1.575	0.141	*
TF000T2-06	3/8"	9.5	13.7	50	1.969	0.163	*
TF000T2-07	13/32"	10.3	14.6	60	2.362	0.173	*
TF000T2-08	1/2"	12.7	17	70	2.756	0.251	*
TF000T2-10	5/8"	15.9	20.5	110	4.331	0.304	*
TF000T2-12	3/4"	19	23.5	180	7.087	0.358	*
TF000T2-14	7/8"	22.2	27	200	7.874	0.470	*
TF000T2-16	1"	25.4	30.8	280	11.024	0.491	*

(*) Ask to our Technical Office - For temperatures over 100 ° C contact our Technical office

P.T.F.E. - THP
TF00THP

APPLICATIONS :





APPLICABLE SPECS. :
SAE 100 R8 - SAE 100 R9 - MIL. H38360

Hose for use with IMM Hydraulics fittings.Standard tail.


Internal hose: Conductive extruded black smooth P.T.F.E..
Covering: 1 high tensile stainless steel AISI 304 wire braids
Operating temperature: from -70 to +260°C.

Part number	ID		OD	Max WP	Min BR		Weight	Ferrule
	in	mm	mm	psi	mm	inch	lb/ft	
TF00THP-04	1/4"	6	9.9	5003	38	1.496	0.100	*
TF00THP-05	5/16"	8	12.4	5003	63	2.480	0.163	*
TF00THP-06	3/8"	9.5	15.6	5003	73	2.874	0.232	*
TF00THP-08	1/2"	13	18.5	5003	82	3.228	0.325	*
TF00THP-10	5/8"	16	25.1	5003	98	3.858	0.660	*
TF00THP-14	7/8"	22	32.2	5003	127	5.000	1.020	*
TF00THP-18	1.1/8"	28.5	42.1	5003	305	12.008	1.850	*
TF00THP-20	1.1/4"	32	48.2	4002	356	14.016	1.910	*


(*) - Ask to our Technical Office - For impulse pressure reduce the operating pressure by 69 bar. For use at a constant temperature of + 204 ° C, the max operating pressure for all diameters is 207 bar.

P.T.F.E. - LTC

TF00LTC



APPLICATIONS :



APPLICABLE SPECS. :

Hose for use with IMM Hydraulics fittings.Standard tail.

Internal hose: Convoluted P.T.F.E. core.

Covering: 1 high tensile stainless steel AISI 304 wire braids

Operating temperature: from -70 to +260°C.

Part number	ID		Min BR		Weight	Ferrule
	in	mm	mm	inch	lb/ft	
TF00LTC-06	3/8"	9.5	20	0.787	0.069	*
TF00LTC-08	1/2"	12.7	25	0.984	0.081	*
TF00LTC-10	5/8"	15.9	50	1.969	0.091	*
TF00LTC-12	3/4"	19	65	2.559	0.153	*
TF00LTC-16	1"	25.4	90	3.543	0.189	*
TF00LTC-20	1 1/4"	31.8	127	5.000	0.233	*
TF00LTC-24	1 1/2"	38.1	152	5.984	0.318	*
TF00LTC-32	2"	50.8	200	7.874	0.369	*

(*) - For temperature over 100C° and ferrule, please contact our technical department

Accessories

Index

Armour Guard Spirali

SPMP



Armour Guard

100

SPMW




Wire Guard

100

Handle Manopole

MANB



Handle (Blue)

101

MANN



Handle (Black)

101

SAPB



Armour Guard Black "Basic"

102

SKPB



Armour Guard Black "Endurance"

103

Sleeve and Cap Calze e capsule

TPRS



Protective textilestockings

104

GP085



Black PVC sheath+

105

CFVS



Glass fiber knitted slleve

106

CAFV



Braided Glass fiber sleeve

107

CTA



Heat shrink PVC caps

108

Heat machine Fornelli

HSMA1



Manual without bss

HSMA2



Manual with bss

HSMB1




Table mounted

109

Dimensions and general characteristics may be changed at any time, data contained here in are only for information purpose only and it does not enlarge, amend or imply any warranty other than provided by us with the product. Any use of thr product not in conformance with our instructions may be dangerous.

Plugs Tappi

PLM



Protection plugs

110


PLF



Protection plugs

111


PFS3



Protection plugs for SAE 3000 flanges

112

PFS6



Protection plugs for SAE 6000 flanges

112

POCG



Protection Plug

112

Gauges Tamponi




Go/Not go double gauges

113

Rondella Bonded

RM00 - RG00




Metric copper washer

114

Rondella Bonded


RBM0 - RB00



Metric Bonded Seal

115

RBMA - RBGA



Self-cent Bonded Seal

115

Guarnizioni Seal



Seals for adaptors and fittings

116-125

Valigie O-Ring Box O-Ring

BOXG-BS-70



O-Ring NBR70 shore british standard

126

BOXH-MS-70



O-Ring NBR70 shore Metric Standard

126

Bonded seals kit

BOXBG




BSP - Self-centering bonded seal kit

127


Dimensions and general characteristics may be changed at any time, data contained here in are only for information purpose only and it does not enlarge, amend or imply any warranty other than provided by us with the product. Any use of thr product not in conformance with our instructions may be dangerous.

Armour Guard



Part number	ID	Lenght
SPMP-13	13	4 MT.
SPMP-15	15	4 MT.
SPMP-16	16	4 MT.
SPMP-17	17	4 MT.
SPMP-18	18	4 MT.
SPMP-20	20	4 MT.
SPMP-22	22	4 MT.
SPMP-24	24	4 MT.
SPMP-26	26	4 MT.
SPMP-28	28	4 MT.
SPMP-30	30	4 MT.
SPMP-32	32	4 MT.
SPMP-34	34	4 MT.
SPMP-38	38	4 MT.
SPMP-40	40	4 MT.
SPMP-41	41	4 MT.
SPMP-42	42	4 MT.
SPMP-47	47	4 MT.
SPMP-48	48	4 MT.
SPMP-49	49	4 MT.
SPMP-52	52	4 MT.
SPMP-54	54	4 MT.
SPMP-58	58	4 MT.
SPMP-60	60	4 MT.
SPMP-68	68	4 MT.
SPMP-72	72	4 MT.

Wire Guard



Part number	ID	Thickness	Lenght
SPMW-13	13	2	4 MT.
SPMW-15	15	2	4 MT.
SPMW-16	16	2	4 MT.
SPMW-17	17	2	4 MT.
SPMW-18	18	2	4 MT.
SPMW-20	20	2	4 MT.
SPMW-22	22	2	4 MT.
SPMW-24	24	2	4 MT.
SPMW-26	26	2	4 MT.
SPMW-28	28	2	4 MT.
SPMW-30	30	2	4 MT.
SPMW-32	32	2,5	4 MT.
SPMW-34	34	2,5	4 MT.
SPMW-38	38	3	4 MT.
SPMW-40	40	3	4 MT.
SPMW-42	42	3	4 MT.
SPMW-52	52	3	4 MT.
SPMW-54	54	3	4 MT.
SPMW-60	60	3	4 MT.
SPMW-72	72	3	4 MT.

MANB

Handle (Blue)



Material: Rubber SBR+EPDM.
Operating temperature range: -20°C +150°C.
Hardness: shore A65.
High mechanical strength.

Part number	I.D.mm	Lenght(mt)
MANB-04	15	116
MANB-05	18	128
MANB-06	21	128
MANB-08	23	128

MANN

Handle (Black)




Material: Rubber SBR+EPDM.
Operating temperature range: -20°C +150°C.
Hardness: shore A65.
High mechanical strength.

Part number	I.D.mm	Lenght(mt)
MANN-04	15	116
MANN-05	18	128
MANN-06	21	128
MANN-08	23	128

SAPB

Armour Guard Black “Basic”



Material: rigid PVC no crash. (*)

Spiral: abrasion, crushing, UV, ozone and flame resistant conforming to UL94 V2 self-extinguishing class.

Operating temperature range: -10°C +70°C.

Hardness: shore A78.

Breaking stretching (ISO R527): 130%.

Breaking load (ISO R527): 40 kg/cm².

Part number	I.D.mm	lenght(mt)	Weight Kg/m
SAPB-08	8	50	0.05
SAPB-12	12	50	0.06
SAPB-16	16	50	0.08
SAPB-20	20	50	0.12
SAPB-24	24	50	0.19
SAPB-27	27	50	0.22
SAPB-30	30	50	0.25
SAPB-35	35	50	0.33
SAPB-44	44	25	0.48
SAPB-56	56	20	0,80
SAPB-67	67	20	0.88
SAPB-80	80	10	1.39
SAPB-100	100	7	1.90
SAPB-120	120	6	1.78

(*)Also available in HDPE version for protection of hydraulic hoses.
Temperature range: -60°C +100°C.
Spiral: abrasion crush, UV, ozone, low temperature.
Resistence: Acids, Oils, Solvents.

- Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.

Armour Guard Black “Endurance”

Spiralina in plastica nera ‘Endurance’



Bending creep: 110/30 Mpa (ISO 178).

Spiral: abrasion, crushing, UV, ozone and flame resistant conforming to UL94 V2 self-extinguishing class.
Electrical resistivity: 10 e13 Ω.

Test temperature: -25 ° C + 120 ° C.


Polyamide (PA) spiral for protection of hydraulic tubes and multiple pipe wiring where high temperature is required.

Part number	I.D.mm	Lenght(mt)	Weight Kg/m
SKPB-08	8	30	0.04
SKPB-13	12	30	0.05
SKPB-16	16	30	0.07
SKPB-19	20	30	0.09
SKPB-25	25	30	0.14
SKPB-27	27	30	0.15
SKPB-35	35	30	0.21
SKPB-45	45	30	0.32
SKPB-67	67	20	0.065
SKPB-80	80	10	0.95
SKPB-100	100	7	1.425

- Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.

TPRS

Protective textile stockings



USE: Ideal for grouping and protecting tube bundles, saving space, protecting operators from possible assemblage failures. Protect from abrasion and wear. Limited blockage or loss of assembly.

Features:

Elongation at break: from 24 to 34%.

Material: High density polypropylene (75% polypropylene - 25% Polyester).

Color: Black.

MSHA IC-242/05 (*MSHA IC-242/06).

Treatment: UV stabilization at 200 Kly.

Abrasion resistance: > 25000 cycles.

Maximum working temperature: 90°C (194°F).


Part number	Width Larghezza	ID	Roll
	mm	mm	lenght
TPRS-20	35	20	100
TPRS-22	40	22	100
TPRS-25	45	25	100
TPRS-28	50	28	100
TPRS-32	55	32	100
TPRS-35	60	35	100
TPRS-40	65	40	100
TPRS-45	80	45	100
TPRS-50	90	50	100
TPRS-70	120	70	100
TPRS-75	120	75	100
TPRS-90	150	90	100

*Also available in polyester version and Max operating temperature 130°C.

Black PVC sheath

Guaina nera in PVC

GP085



USE: Particularly suitable for grouping tube bundles. UV protection. Abrasion wear and tear. Waterproof to solvents, oils, etc ..

Features:

Flame propagation: self-extinguishing grade 0 (according to UL94).

Material: PVC 70.

Color: Black

Maximum operating temperature: 70 ° C according to CEI 23-14. UL94.

Originakl breaking load: 16.3 N/mm².

Original elongation at break: 250%.

Hardness shore: 75 a 15°.

Part number	ID mm	Wall thickness	Roll lenght
GP085-15	15	0.6	100
GP085-18	18	0.6	100
GP085-22	22	0.6	100
GP085-24	24	0.6	100
GP085-26	26	0.6	100
GP085-28	28	0.6	100
GP085-30	30	0.6	100
GP085-34	34	0.7	50
GP085-40	40	0.7	50

CFVS

Glass fiber knitted sleeve with red silicon coating



USE: Particularly suitable for steel mills, foundries, glass processing, shipyards, railways. Isolating for class H and class C motors, transformers. Cabling in ovens, welders. Specially designed for high and very high temperature resistance.

Features:

Maximum operating temperature: 1650 ° C (3000 ° F) exposure 15-30 seconds - 1093 ° C (2000 ° F) exposure 15-20 minutes - 260 ° C (500 ° F) to -54 ° C (-65 ° F) continuous exposure.

Flame Resistance ISO15540 & ISO15541.

Oil and fluid resistance: Resistant to most liquids including those based on hydrocarbons. Unmatched functionality after immersion for 120 hours at 80 ° F in MIL-L-6082 and Skydroll 500 liquid.

Compliance SAE AS1072E.

MSHA Certification.

Certified iaw UL 1441, VW1.

Tested iaw ISO 6940, ISO6530, BS 2576, EN373, EN388.

Rail Certification EN 45545-2:2013-08.

Part number	Size	Roll lenght*
CFVS-06	06	15
CFVS-10	10	15
CFVS-13	13	15
CFVS-16	16	15
CFVS-19	19	15
CFVS-22	22	15
CFVS-25	25	15
CFVS-29	29	15
CFVS-32	32	15
CFVS-35	35	15
CFVS-38	38	15
CFVS-41	41	15
CFVS-44	44	15
CFVS-51	51	15
CFVS-57	57	15
CFVS-64	64	15
CFVS-70	70	15

Part number	Size	Roll lenght*
CFVS-76	76	15
CFVS-89	89	15
CFVS-102	102	15
CFVS-114	114	15
CFVS-127	127	15

Braided glass fiber sleeve

CAFV



USE: Sleeving are braided to ensure elasticity and to be applicated easily on pipes. Used for heat insulation and protection of hoses. They can be treated externally with elastomers and silicone.

Features:

Good stability at high temperatures.

Maximum operating temperature: 538 ° C (continuous); 650 ° C (intermittent).

Low thermal conductivity.

Good dimensional stability.

Good resistence to chemical agents.

Good mechanical strength.

High flexibility.

Part number	Roll	
	Size	lenght
CAFV-13	13	300
CAFV-19	19	225
CAFV-22	22	195
CAFV-25	25	195
CAFV-32	32	135
CAFV-38	38	210
CAFV-51	51	75
CAFV-64	64	134
CAFV-76	76	60
CAFV-102	102	52

Cautionary notes: Extended exposure to water or other liquids causes weakining of the fibers. Loose fibers may cause some irritation to skin. Long sleeves, goggles and gloves are recommended during installation.

CTA HY-CAP Capsules in shrink-wrapping PVC



System for preventing the internal contamination of the assembled hose up to the time of assembly, equivalent and alternative to the traditional threaded plastic plug.

Features:

Environment: Reduction of plastic waste quantities.
Material: Thermoplastic polyvinyl chloride (PVC) foil leaf.
Range: Cover of all applications with only 7 capsules diameters.
Management: Controls, documenting and reordering only 7 codes.
Heat-shrinking times around the second.
Capsule color and logo customizable, for minimum order quantity.


Part number	Size	Lenght	Hexagonal covered	Q.ty Box
CTA2530AA	25	25	12/22	20000
CTA2850AA	28	28	22/24	8500
CTA3140AA	31	31	24/27	10000
CTA3440AA	34	34	27/30	12000
CTA3850AA	38	38	30/32	7000
CTA4660AA	46	46	32/41	4000
CTA7050AA	70	70	41/70	2800



Heat shrink machine HSM



HSMA1



HSMA2



HSMB1

Features:

230 V (1000 W).

Material: Stainless steel.


Versions: Table mounted (HSMB1).

Manual, with or without base support stand (bss) (HSMA1 and HSMA2).

Part number			Dimensions (mm)	
	Version	Weight Kg	A X B	h
HSMA1	Manual, without bss	1.5	240x100	240
HSMA2	Manual, with bss	2.0	240x180	320
HSMB1	Table mounted	3.0	480x150	220


Protection plugs

Male plug




Part number	Thread/Filetto				
	UNF/UN	BSPP/BSPT	NPTF	ORFS	METRIC
PLUG-01M	-	1/8”-28	1/8”-27	-	M10X1,5
PLUG-21M	7/16”-20	-	-	-	-
PLUG-02M	1/2”-20	1/4”-19	1/4”-18	-	M12X1,5
PLUG-23M	9/16”-18	-	-	9/16”-18	M14X1,5
PLUG-03M	5/8”-18	3/8”-19	3/8”-18	-	M16X1,5
PLUG-13M	-	-	-	11/16”-16	M18X1,5
PLUG-25M	3/4”-16	-	-	-	-
PLUG-04M	-	1/2”-14	1/2”-14	-	M20X1,5
PLUG-36M	-	-	-	13/16”-16	-
PLUG-05M	7/8”-14	5/8”-14	-	-	M22X1,5
PLUG-37M	-	-	-	1”-14	-
PLUG-20M	-	-	-	-	M24X1,5
PLUG-06M	1.1/16”-12	3/4”-14	3/4”-14	-	M26X1,5
PLUG-29M	1.3/16”-12	-	-	1.3/16”-12	M30X2/M30X1,5
PLUG-07M	1.5/16”-12	1”-11	1”-11.1/2	-	-
PLUG-15M	-	-	-	-	M36X2/M36X1,5
PLUG-38M	-	-	-	1.7/16”-12	-
PLUG-32M	-	-	-	-	M38X1,5
PLUG-27M	1.5/8”-12	-	-	-	-
PLUG-08M	-	1.1/4”-11	1.1/4”-11.1/2	-	-
PLUG-33M	-	-	-	-	M42X1,5
PLUG-16M	-	-	-	1.11/16”-12	M42X2
PLUG-17M	-	-	-	-	M45X1,5/M45X2
PLUG-09M	1.7/8”-12	1.1/2”-11	1.1/2”-11.1/2	-	-
PLUG-40M	-	-	-	2”-12	-
PLUG-18M	-	-	-	-	M52X2
PLUG-10M	-	2”-11	2”-11.1/2	-	-
PLUG-28M	2.1/2”-12	-	-	-	-

Female plug



Part number	Thread/Filetto				
	UNF/UN	BSPP/BSPT	NPTF	ORFS	METRIC
PLUG-01F	-	1/8"-28	1/8"-27	-	M10X1,5
PLUG-21F	7/16"-20	-	-	-	-
PLUG-11F	-	-	-	-	M12X1,5
PLUG-22F	1/2"-20	-	-	-	-
PLUG-02F	-	1/4"-19	1/4"-18	-	-
PLUG-23F	9/16"-18	-	-	9/16"-18	M14X1,5
PLUG-24F	5/8"-18	-	-	-	-
PLUG-12F	-	-	-	-	M16X1,5
PLUG-03F	-	3/8"-19	3/8"-18	-	-
PLUG-35F	-	-	-	11/16"-16	-
PLUG-13F	-	-	-	-	M18X1,5
PLUG-25F	3/4"-16	-	-	-	-
PLUG-19F	-	-	-	-	M20X1,5
PLUG-04F	-	1/2"-14	1/2"-14	13/16"-16	-
PLUG-26F	7/8"-14	-	-	-	M22X1,5
PLUG-05F	-	5/8"-14	-	-	-
PLUG-20F	-	-	-	-	M24X1,5
PLUG-37F	-	-	-	1"-14	-
PLUG-06F	1.1/16"-12	3/4"-14	3/4"-14	-	M26X1,5
PLUG-29F	1.3/16"-12	-	-	1'3/16	M30X1,5/M30X2
PLUG-07F	1.5/16"-12	1"-11	1"-11.1/2	-	-
PLUG-15F	-	-	-	-	M36X1,5/M36X2
PLUG-38F	-	-	-	1.7/16"-12	-
PLUG-32F	-	-	-	-	M38X1,5
PLUG-27F	1.5/8"-12	-	-	-	-
PLUG-08F	-	1.1/4"-11	1.1/4"-11.1/2	-	M42X1,5
PLUG-16F	-	-	-	-	M42X2
PLUG-39F	-	-	-	1.11/16"-12	-
PLUG-17F	-	-	-	-	M45X1,5/M45X2
PLUG-09F	1.7/8"-12	1'1/2	1.1/2"-11.1/2	-	-
PLUG-40F	-	-	-	2"-12	-
PLUG-18F	-	-	-	-	M52X2
PLUG-10F	-	2"-11	2"-11.1/2	-	-
PLUG-28F	2.1/2"-12	-	-	-	-

PFS3




Protection plugs for SAE 3000 flanges

Part number	Size
PFS3-08	1/2
PFS3-12	3/4
PFS3-16	1
PFS3-20	1.1/4
PFS3-24	1.1/2
PFS3-32	2
PFS3-40	2.1/2

PFS6

Protection plugs for SAE 6000 flanges



Part number	Size
PFS6-08	1/2
PFS6-12	3/4
PFS6-16	1
PFS6-20	1.1/4
PFS6-24	1.1/2
PFS6-32	2

POCG

Protection plugs BSP banjo



Part number	Size
POCG-04	1/4
POCG-06	3/4
POCG-08	1/2

Go/Not go double gauges


TMBS

Code	Tubo
TMBS-00-03	3/16″
TMBS-00-04	1/4″
TMBS-00-05	5/16″
TMBS-00-06	3/8″
TMBS-00-08	1/2″
TMBS-00-10	5/8″
TMBS-00-12	3/4″
TMBS-00-16	1″
TMBS-00-20	1,1/4″
TMBS-03-20	Kit 3/16″-1,1/4″
TMBS-00-24	1,1/2″
TMBS-00-32	2″
TMBS-03-32	Kit 3/16″-2″

Technical data/Dati tecnici	
Material/Materiale	steel/acciaio
Surface treatment/ Trattamento superficiale	nichel plated nichelato



User instructions





Correct swaging:

- Swaging phase is rightly made.
- "Go" side (signed with one line) is not stopped from internal deformation of insert.
- "Not Go" side (signed with two lines) is correctly stopped from internal deformation of insert.

Uncorrect swaging:

Swaging phase is not rightly made.
Both "Go" side (signed with one line) and "Not go" side (signed with two lines) are not stopped from internal deformation of insert.
Decrease swaging diameter (0,1 mm each step) until right swaging dimension.






Uncorrect swaging:

Item has been too swaged.
Both "Go" side (signed with one line) and "Not go" side (signed with two lines) are stopped from too high internal deformation of insert.
Too high change of internal shape cannot guarantee right performance on application.

RM00


Metric copper washer



Part number	Dimensions
	F
RM00-06	M6
RM00-08	M8
RM00-10	M10
RM00-12	M12
RM00-14	M14
RM00-16	M16
RM00-18	M18
RM00-20	M20
RM00-20-26	M20
RM00-22	M22
RM00-26	M26
RM00-28-34	M28
RM00-30	M30

RG00


BSPP copper washer



Part number	Dimensions
	F
RG00-02	G 1/8″
RG00-04	G 1/4″
RG00-06	G 3/8″
RG00-08	G 1/2″
RG00-10	G 5/8″
RG00-12	G 3/4″
RG00-16	G 1″
RG00-20	G 1.1/4″
RG00-24	G 1.1/2″
RG00-32	G 2″

RBM0


Metric Bonded Seal



Part number	Dimensions		
	F	D	H
RBM0-05	M5	8.4	1.2
RBM0-06	M6	13.2	1.2
RBM0-08	M8	14.2	1.2
RBM0-10	M10	18.4	2
RBM0-14	M14	22.2	2
RBM0-16	M16	25.4	2
RBM0-18	M18	26.9	2.3


RB00

BSPP seal bonded



Part number	Dimensions		
	F	D	H
RB00-02	G 1/8″	14	2
RB00-04	G 1/4″	20.6	2
RB00-06	G 3/8″	23.9	2
RB00-08	G 1/2″	28.7	2
RB00-10	G 5/8″	31.8	2
RB00-12	G 3/4″	35	2
RB00-16	G 1″	42.9	2.5
RB00-20	G 1.1/4″	52.5	2.5
RB00-24	G 1.1/2″	58.7	3.2
RB00-32	G 2″	73	2.5


RBMA



Metric Self-centering Bonded Seal

Part number	Dimensions					
	ID	OD	d4	d5	s	Thread
RBMA-04	4.5	7	5.4	3.3	1	M4
RBMA-08	8.7	14	10.4	6.4	1	M8
RBMA-10	10.7	16	12.4	8.05	1.5	M10
RBMA-12	12.7	18	14.4	10.2	1.5	M12
RBMA-14	14.7	22	16.4	11.38	1.5	M14
RBMA-16	16.7	24	18.4	13.41	1.5	M16
RBMA-18	18.7	26	20.4	14.76	1.5	M18
RBMA-20	20.7	28	22.5	16.76	1.5	M20
RBMA-22	22.7	30	24.4	18.74	2	M22

RBGA




BSP Self-centering Bonded Seal

Part number	Dimensions					
	ID	OD	d4	d5	s	Thread
RBGA-02	10.37	15.88	11.84	8.26	2	1/8
RBGA-04	13.74	20.57	15.21	11.18	2	1/4
RBGA-06	17.28	23.8	18.75	14.76	2	3/8
RBGA-08	21.54	28.58	23.01	18.24	2.47	1/2
RBGA-10	23.49	31.75	24.97	20.27	2.47	5/8
RBGA-12	27.05	34.93	28.53	23.83	2.47	3/4
RBGA-14	30.81	38.1	32.29	27.51	2.47	7/8
RBGA-16	33.89	42.8	36.88	29.92	3.4	1
RBGA-20	42.93	52.38	45.93	38.45	3.4	1.1/4
RBGA-24	48.44	58.6	51.39	44.45	3.4	1.1/2
RBGA-28	54.89	69.85	58.3	50.42	3.4	1.3/4
RBGA-32	60.58	73.03	63.63	56.26	3.4	2
RBGA-40	76.08	90.17	79.38	71.5	3.4	2.1/2


-Also available in 304 stainless steel version, code ex. XRBGA-02


O-Ring for SAE J 518 Flange (3000 PSI and 6000 PSI)



Part number					Flangia	
	rif. Usa	rif. Eng.	d1	d2	Pollici	dash
8-4075	2-210	4075	18.64	3.53	1/2	08
8-4100	2-214	4100	24.99	3.53	3/4	12
8-4131	2-219	4131	32.92	3.53	1	16
8-4150	2-222	4150	37.69	3.53	1-1/4	20
8-4187	2-225	4187	47.22	3.53	1-1/2	24
8-4225	2-228	4225	56.74	3.53	2	32
8-4275	2-232	4275	69.44	3.53	2-1/2	40
8-4337	2-237	4337	85.32	3.53	3	48
8-4387	2-241	4387	98.02	3.53	3-1/2	56
8-4437	2-245	4437	110.72	3.53	4	64


Elastomeric seal for Male BSP / Metric






Part number						FILETTATURA	
	SIZE	d6	d7	L5	L6	Metrica	Pollici
8-E10	10	8.4	11.9	1	0.5	M10x1	1/8”-28
8-E12	12	9.8	14.4	1.5	0.8	M12x1,5	-
8-E14	14	11.6	16.5	1.5	0.8	M14x1,5	1/4-19
8-E16	16	13.8	18.9	1.5	0.8	M16x1,5	-
8-E17	17	14.7	18.9	1.5	0.8	-	3/8-19
8-E18	18	15.7	20.9	1.5	0.8	M18x1,5	-
8-E20	20	17.8	22.9	1.5	0.8	M20x1,5	-
8-E21	21	18.5	23.9	1.5	0.8	-	1/2-14
8-E22	22	19.6	24.3	1.5	0.8	M22x1,5	-
8-E27	27	23.9	29.2	1.5	0.8	M26x1,5 M27x2	3/4-14
8-E33	33	29.7	35.7	2	1	M33x2	1-11
8-E42	42	38.8	45.8	2	1	M42x2	1.1/4-11
8-E48	48	44.7	50.7	2	1	M48x2	1.1/2-11


O-Ring for Metric Male (ISO 6149)






Part number			FILETTATURA	
	d1	d2	Metrica	dash
8MI-8-8.1X1.6	8.1	1.6	M10x1	10
8MI-8-9.3X2.2	9.3	2.2	M12x1,5	12
8MI-8-11.3X2.2	11.3	2.2	M14x1,5	14
8MI-8-13.3X2.2	13.3	2.2	M16x1,5	16
8MI-8-15.3X2.2	15.3	2.2	M18x1,5	18
8MI-8-19.3X2.2	19.3	2.2	M22x1,5	22
8MI-8-23.6X2.9	23.6	2.9	M27x2	27
8MI-8-29.6X2.9	29.6	2.9	M33x2	33
8MI-8-38.6X2.9	38.6	2.9	M42x2	42
8MI-8-44.6X2.9	44.6	2.9	M48x2	48


O-Ring for ORFS Male






Part number					FILETTATURA	
	rif. Usa	rif. Eng.	d1	d2	UNF	dash
8-107	2-11	2031	7.66	1.78	9/16x18	06
8-110	2-12	2037	9.25	1.78	11/16x16	09
8-2050	2-14	2050	12.42	1.78	13/16x16	11
8-2062	2-16	2062	15.6	1.78	1x14	13
8-2075	2-18	2075	18.77	1.78	1-3/16x12	14
8-2080	2-21	2080	23.52	1.78	1-7/16x12	15
8-2118	2-25	2118	29.87	1.78	1-11/16x12	21
8-2150	2-29	2150	37.82	1.78	2x12	32


O-Ring for BSPP cone






Part number					FILETTATURA	
	rif. Usa	rif. Eng.	d1	d2	Pollici	dash
8-5.5x1	-	-	5.5	1	1/4-19	04
8-7.1x1.6	-	-	7.1	1.6	3/8-19	06
8-11.1x1.6	-	-	11.1	1.6	1/2-14	08
8-2056	2-15	2056	14	1.78	5/8-14	10
8-15.1x1.6	-	-	15.1	1.6	3/4-14	12
8-2087	2-20	2087	21.95	1.78	1-11	16
8-2112	2-24	2112	28.3	1.78	1.1/4-11	20
8-2118	2-25	2118	29.87	1.78	1.1/2-11	24
8-2-32	2-32	2187	47.37	1.78	2-11	32

O-Ring for Metric 24°




Part number					
	d1	d2	DKOL	DKOS	tube
8-4x1.5	4	1.5	M12x1,5	M14x1,5	6
8-6x1.5	6	1.5	M14x1,5	M16x1,5	8
8-7.5x1.5	7.5	1.5	M16x1,5	M18x1,5	10
8-9x1.5	9	1.5	M18x1,5	M20x1,5	12
8-10x2	10	2	-	M22x1,5	14
8-12x2	12	2	M22x1,5	M24x1,5	15-16
8-15x2	15	2	M26x1,5	-	18
8-16.3x2.4	16.3	2.4	-	M30x2	20
8-20x2	20	2	M30x2	-	22
8-20.3x2.4	20.3	2.4	-	M36x2	25
8-26x2	26	2	M36x2	-	28
8-25.3x2.4	25.3	2.4	-	M42x2	30
8-32x2.5	32	2.5	M45x2	-	35
8-33.3x2.4	33.3	2.4	-	M52x2	38
8-38x2.5	38	2.5	M52x2	-	42

O-Ring for “K” male




Part number			FILETTATURA		
	d1	d2	Metrica	Pollici	dash
8-10x2	10	2	M22X1.5	1/8”-28	02

O-Ring for “K” insert (for gun)




Part number			FILETTATURA	
	d1	d2	Pollici	dash
8-105	**6.07**	**1.78**	**1/8”-28**	**02**

O-Ring for BSP MALE (ISO 1179-3)




Part number					FILETTATURA	
	rif. Usa	rif. Eng.	d1	d2	Pollici	dash
8-8X1.88	-	-	7.97	1.88	1/8-28	02
8-113	2-111	3043	10.78	2.62	1/4-19	04
8-118	2-113	3056	13.95	2.62	3/8-19	06
8-123	5-256	123	17.86	2.62	1/2-14	08
8-3093	2-119	3093	23.47	2.62	3/4-14	12
8-29.47X3.53	-	-	29.47	3.53	1-11	16
8-37.69X3.53	2-222	4150	37.69	3.53	1.1/4-11	20
8-4175	2-224	4175	44.04	3.53	1.1/2-11	24


Retaining Ring for BSP Male (ISO 1179-3)



Part number				FILETTATURA	
	d1	L	d2	Pollici	dash
8-R15X1.4	12.2	1.4	15	1/8-28	02
8-R19.5X1.9	16.15	1.9	19.5	1/4-19	04
8-R23.5X1.9	19.5	1.9	23.5	3/8-19	06
8-R28.5X1.9	23.3	1.9	28.5	1/2-14	08
8-R34.5X1.9	28.6	1.9	34.5	3/4-14	12
8-R43.5X2.6	36.6	2.6	43.5	1-11	16
8-R52.5X2.6	44.9	2.6	52.5	1.1/4-11	20
8-R60X2.6	50.9	2.6	60	1.1/2-11	24


O-Ring for Metric Male






Part number			FILETTATURA	
	d1	d2	Metrica	dash
8-8X1.8	8	1.8	M10x1	10
8-9.3X2.2	9.3	2.2	M12x1,5	12
8-11.3X2.2	11.3	2.2	M14x1,5	14
8-13.3X2.2	13.3	2.2	M16x1,5	16
8-3062	15.54	2.62	M18x1,5	18
8-19X2.65	19	2.65	M22x1,5	22
8-23.47X2.95	23.47	2.95	M27x2	27
8-29.4X3.1	29.4	3.1	M33x2	33
8-38X3.5	38	3.5	M42x2	42
8-4175	44.04	3.53	M48x2	48


Retaining Ring for Metric Male



Part number			FILETTATURA	
	L	D2	Metrica	dash
8-R14.8X1	1	14.8	M10x1	10
8-R17.8X1.3	1.3	17.8	M12x1,5	12
8-R19.8X1.3	1.3	19.8	M14x1,5	14
8-R21.8X1.5	1.5	21.8	M16x1,5	16
8-R23.8X2	2	23.8	M18x1,5	18
8-R27.8X1.3	1.3	27.8	M22x1,5	22
8-R32.8X2	2	32.8	M27x2	27
8-R39.8X2	2	39.8	M33x2	33
8-R49.8X2	2	49.8	M42x2	42
8-R55.8X2	2	55.8	M48x2	48

O-Ring for SAE Male (ISO 11926)






Part number			FILETTATURA	
	d1	d2	UNF	dash
8-8.92x1.83	8.92	1.83	7/16x20	04
8-10.52x1.83	10.52	1.83	1/2x20	05
8-11.89x1.98	11.89	1.98	9/16x18	06
8-16.36x2.21	16.36	2.21	3/4x16	08
8-19.18x2.46	19.18	2.46	7/8x14	10
8-23.47x2.95	23.47	2.95	1-1/16x12	12
8-29.74x2.95	29.74	2.95	1-5/16x12	16
8-37.47x3	37.47	3	1-5/8x12	20

GPP0

Polyurethane seal for SAE J 518 flange (3000 PSI and 6000 PSI) and Cat" flanges






Features:

- **Standard material:** Pu41 - Blue polyurethane 93 shore A
- **Max temperature:** -30°C + 100°C
- **Max working pressure:** 610 bar
- Good abrasion resistance
- Very high resistence to extrusion
- Low compression set
- The sealing edge offers a very good sealingfunctions
- Usable for rogh surface finish

Standard seals are supplied in NBR 70. On request even in NBR 90, FPM e in EPDM.

Part Number		Dimensions		
	Size	OD	S	T
GPP0-08	1/2"	25.5	3.8	3.4
GPP0-12	3/4"	31.8	3.8	3.4
GPP0-16	1"	39.6	3.8	3.4
GPP0-20	1.1/4"	44.5	3.8	3.4
GPP0-24	1.1/2"	53.8	3.8	3.4
GPP0-32	2"	63.4	3.8	3.4



		D	H	L
Size	DN	Min-Max	Min-Max	Min-Max
1/2"	13	25.40-25.83	2.79-2.92	3.94-4.45
3/4"	19	31.75-31.88	2.79-2.92	3.94-4.45
1"	25	39.62-39.75	2.79-2.92	3.94-4.45
1.1/4"	32	44.45-44.58	2.79-2.92	3.94-4.45
1.1/2"	38	53.72-53.98	2.79-2.92	3.94-4.45
2"	51	62.50-63.25	2.79-2.92	3.94-4.45

Comparison between different features of elastomers

MATERIAL:

Features	NBR	FPM	EPDM
Compression set	1	1	3
Resistance to tearing	2	2	3
Resistance to abrasion	2	2-3	2
Resistance to ageing	4	1	2
Ozone resistance	4	1	2
Resistance to oil and greasy	2	1	5
Resistance to combustibles	4**	2**	5
Resistance to hot water (°C)	80**	80**	130
Resistance to steam (°C)	-	-	130
Resistance to warmth standard materials (°C)	100	200	130
Resistance to warmth special materials (°C)	120	-	-
Resistance to standard materials low temperature (°C)	-30	-15	-45
Resistance to special materials low temperature (°C)	-50	-35	-

Legend:
1 Excellent / 2 good / 3 medium / 4 low / 5 weak
* short lenght / ** best result only with special materials

BOXG-BS-70

Box O-ring NBR 70 shore
British standard

ASTM D - 2000 SAE J200
30 Sizes = 382 PIECES



Part number	Nominal sizes			Q.ty
	I/D	O/D	Section	nr.
8-2012	2.90	6.46	1.78	20
8-102	3.68	7.24	1.78	20
8-103	4.48	8.04	1.78	20
8-2021	5.28	8.84	1.78	20
8-105	6.07	9.63	1.78	20
8-107	7.65	11.21	1.78	20
8-110	9.25	12.81	1.78	20
8-3037	9.19	14.43	2.62	13
8-113	10.77	16.01	2.62	13
8-3050	12.37	17.61	2.62	13
8-118	13.94	19.18	2.62	13
8-3062	15.54	20.78	2.62	13
8-3068	17.12	22.36	2.62	13
8-124	18.72	23.96	2.62	13
8-4075	18.64	25.70	3.53	10
8-4081	20.22	27.28	3.53	10
8-4087	21.82	28.88	3.53	10
8-4083	23.39	30.45	3.53	10
8-4100	24.99	32.05	3.53	10
8-4106	26.57	33.63	3.53	10
8-4112	28.17	35.23	3.53	10
8-29.74X3.53	29.74	36.80	3.53	10
8-4125	31.34	38.40	3.53	10
8-4131	32.92	39.98	3.53	10
8-4137	34.52	41.58	3.53	10
8-4143	36.09	43.15	3.53	10
8-37.69X3.53	37.69	44.75	3.53	10
8-6150	37.47	48.13	5.33	7
8-6162	40.64	51.30	5.33	7
8-6175	43.82	54.48	5.33	7

BOXH-MS-70

Box O-ring NBR 70 shore
Metric standard

ASTM D - 2000 SAE J200
30 Sizes = 382 PIECES



Part number	Nominal sizes			Q.ty
	I/D	O/D	Section	nr.
8-3X2	3.00	7.00	2.00	18
8-4X2	4.00	8.00	2.00	18
8-5X2	5.00	9.00	2.00	18
8-6X2	6.00	10.00	2.00	18
8-7X2	7.00	11.00	2.00	17
8-8X2	8.00	12.00	2.00	17
8-10X2	10.00	14.00	2.00	17
8-10X2.5	10.00	15.00	2.50	14
8-11X2.5	11.00	16.00	2.50	14
8-12X2.5	12.00	17.00	2.50	14
8-14X2.5	14.00	19.00	2.50	14
8-16X2.5	16.00	21.00	2.50	14
8-17X2.5	17.00	22.00	2.50	14
8-19X2.5	19.00	24.00	2.50	14
8-19X3	19.00	25.00	3.00	12
8-20X3	20.00	26.00	3.00	12
8-22X3	22.00	28.00	3.00	12
8-24X3	24.00	30.00	3.00	12
8-25X3	25.00	31.00	3.00	12
8-27X3	27.00	33.00	3.00	12
8-28X3	28.00	34.00	3.00	12
8-30X3	30.00	36.00	3.00	12
8-32X3	32.00	38.00	3.00	12
8-33X3	33.00	39.00	3.00	12
8-35X3	35.00	41.00	3.00	12
8-36X3	36.00	42.00	3.00	12
8-38X3	38.00	44.00	3.00	12
8-38X4	38.00	46.00	4.00	9
8-42X4	42.00	49.00	4.00	9
8-45X4	45.00	52.00	4.00	9

BOXBG

BSP -Self-centering bonded seal kit



The self-centering Bonded Seal kit includes:

Part number	Dimensions				
	ID	OD	d4	d5	s
RBGA-02	10.37	15.88	11.84	8.26	2
RBGA-04	13.74	20.57	15.21	11.18	2
RBGA-06	17.28	23.8	18.75	14.76	2
RBGA-08	21.54	28.58	23.01	18.24	2.47
RBGA-12	27.05	34.93	28.53	23.83	2.47
RBGA-16	33.89	42.8	36.88	29.92	3.4

PSPT-PU_ _

Standard projectiles



Flexible polyurethane

Part number	I.D.		pcs
	Inch	mm	
PSPT-PU05	3/16″	3,5 - 5	100
PSPT-PU07	1/4″	4,5 - 7	100
PSPT-PU10	5/16″	6 - 9	100
PSPT-PU12	3/8″	7 - 11	100
PSPT-PU14	1/2″	9 - 14	100
PSPT-PU18	5/8″	11 - 17	50
PSPT-PU22	3/4″	13 - 19	50
PSPT-PU26	1″	16,5 - 25	50
PSPT-PU30	1-1/4″	20 - 31	20
PSPT-PU40	1-1/2″	25 - 40	20
PSPT-PU55	2″	32 - 55	20

PSPT06-50

Classic cleaner gun



Cast aluminium

Part number	I.D.	
	Inch	mm
PSPT06-50	3/16″ to 2″	5 to 6

PSPT-UU _ _

Hose nozzle

Black thermoplast



Part number	I.D.
	Inch
PSPT-UU04	3/16”
PSPT-UU06	1/4”
PSPT-UU08	5/16”
PSPT-UU10	3/8”
PSPT-UU13	1/2”
PSPT-UU16	5/8”
PSPT-UU19	3/4”
PSPT-UU25	1”
PSPT-UU32	1-1/4”
PSPT-UU38	1-1/2”
PSPT-UU50	2”

PSPT-UU_ _ - STEEL

Hose nozzle (steel)

Nickel-plated steel



For the nozzles from PSPT UU04-STEEL-to-PSPT UU32-STEEL is required the use of the adapter **PSPT-AD**.



Part number	I.D.
	Inch
PSPT-UU04	3/16”
PSPT-UU06	1/4”
PSPT-UU08	5/16”
PSPT-UU10	3/8”
PSPT-UU13	1/2”
PSPT-UU16	5/8”
PSPT-UU19	3/4”
PSPT-UU25	1”
PSPT-UU32	1-1/4”
PSPT-UU38	1-1/2”
PSPT-UU50	2”

KIT CLEANER

Hose cleaning set



PSPT06-50-KIT CLASSIC

Kit includes :
- 1 Classic cleaner gun
- 11 Thermoplastic hose nozzles (3/16" - 2")
- 1 Protective carrying case



PSPT06-50-KIT STEEL

Kit includes :
- 1 Classic cleaner gun
- 11 Steel hose nozzles (3/16" - 2")
- 1 Protective carrying case

Analytics Index

CAFV 107
CFVS 106
CTA 108
Female plug 111
GP085 105
HSM 109
Male plug 110
MANB 101
MANN 101
Manual with bss 109
Manual without bss 109
PFS3 112
PFS6 112
POCG 112
Protection plugs 111
RB00 115
RBGA 116
RBM0 115
RBMA 116
RG00 114
RM00 114
SAPB 102
SKPB 103
T2E101K 62
T2E102K 63
Table mounted 109
TBOP350 73
TF00LTC 94
TF000T1 90
TF000T2 92
TF00THP 93
TF00TP1 91
TFA201K 8
TFA202K 9
TFE02TE 15
TFD03TE 17
TFD04SP 11
TFD0012 4
TFD0021 5
TFDC011B 24
TFDE011 64
TFDG015 42
TFDH011B 25
TFDH021B 26
TFDL011N 27
TFDL021N 28
TFDM4SP 12
TFDR013 41
TFDR015 22
TFDR4SH 40
TFE0P15 31
TFE001K 6
TFE002K 7
TFEM02KN 29
TFN001K TFB001K 48
TFN002K TFB002K 49
TFN0011 TFB0011 46
TFN0021 TFB0021 47
TFS00CP 86
TFS00H1 80
TFS00H2 81
TFS00HP 82
TFS00MP 84
TFS0003 16
TFS0004 18
TFS04JG THS00JG 72
TFS0005 19
TFS0006 14
TFS0007 78
TFS0008 79
TFS0017 10
TFS0018 83
TFSM012 13
TFW0070 55
TFW0085 56
TFW0110 TFW0100 57
TFW0125 TFW0120 58
TFW0145 TFW0135 59
THD0021 32
THDB4SH 39
THE0L1K THE0L2K 65
THE001K 33
THE002K 34
THE003K 35
THE201K 36
THE202K 40
THE2M2K 38
THE2J2K 66
THEMMDR 71
THEPS1K 67
THL201K 60
THL202K 61
THN201K THB201K 52
THN202K THB202K 53
THN2011 THB2011 50
THN2021 THB2021 51
TI00CO2 85
TMBS 113
TPRS 104
TSW2280 54
TTRK200 68
TTRK250 69
TTRK350 70

Section Index

International Standard 1

Hypress One 1SN 4
Hypress Two 2SN 5
INTERPUMP Hypress 1SC 6
INTERPUMP Hypress 2SC 7
Hypress EASY K 1SC 8
Hypress EASY K 2SC 9
Hypress R17 10
INTERPUMP Hypress 4SP 11
INTERPUMP Hypress 4SP 12
INTERPUMP Hypress R12 13
Hypress UniLock 14
Hypress 2TE 15
EN 854 SAE 100R3 16
EN 854 3TE 17
INTEPUMP Hy-VACUUM - SAE 100R4 18
SAE 100R5 19

High Performance 20

INTERPUMP COMPRESSOR 24
INTERPUMP HyCelsius 1SN 25
INTERPUMP HyCelsius 2SN 26
INTERPUMP HyFreeze 1SN 27
INTERPUMP HyFreeze 2SN 28
INTERPUMP HyOzone 29
INTERPUMP PilotFlex 120 30
INTERPUMP Pilot Plus 150 31
INTERPUMP Kaizen 2SN 32
INTERPUMP Hipac 1SC 33
INTERPUMP Hipac 2SC 34
INTERPUMP Hipac 3SC 35
INTERPUMP LongLife 1SC 36
INTERPUMP LongLife 2SC 37
INTERPUMP MARATHON 2SC 38
BIO - FLEX 39
INTERPUMP HyGreen 4SH 40
INTERPUMP HyGreen R13 41
INTERPUMP HyGreen R15 42

Solution for Applications 43

INTERPUMP Jet 1SN 46
INTERPUMP Jet 2SN 47
INTERPUMP Jet 1SC 48
INTERPUMP Jet 2SC 49
INTERPUMP Jet Plus 1SN 50
INTERPUMP Jet Plus 2SN 51
INTERPUMP Jet Plus 1SC 52
INTERPUMP Jet Plus 2SC 53
INTERPUMP SEWERJET 280 54
INTERPUMP HyBLAST 10k 55
INTERPUMP HyBLAST 12k 56
INTERPUMP HyBLAST 15k 57
INTERPUMP HyBLAST 18k 58
INTERPUMP HyBLAST 20k 59
INTERPUMP LongLift 1SC 60
INTERPUMP LongLift 2SC 61
INTERPUMP LongLife Dual 1SC 62
INTERPUMP LongLife Dual 2SC 63
Hypress HyRail 64
INTERPUMP Power Lift - 1SC/2SC 65
INTERPUMP HYJACK 66
Hypress Snow Storm 1SC 67
INTERPUMP HyTruck 200 bar 68
INTERPUMP HyTruck 250 bar 69
INTERPUMP HyTruck 350 bar 70
Hypress Mega Drill 71
INTERPUMP Mega Jet 72
INTERPUMP BOP FIRESCREEN 5000 73
INTERPUMP HyGEAR 1SC 74

Thermoplastic 76

SAE 100R7 78
SAE 100R8 79
One high tensile steel wire braid 80
Two high tensile steel wire braid 81
INTERPUMP HyUltra 82
R18 Low temperature 83
Mini- lexible 84
INTERPUMP HyFire 85
Costant pressure low temperature 86

P.T.F.E.Hoses 88

Tubo P.T.F.E. tipo T1 90
Tubo P.T.F.E. tipo TP1 91
Tubo P.T.F.E. tipo T2 92
Tubo P.T.F.E. tipo THP 93
Tubo P.T.F.E. corrugato tipo LTC 94

Accessories 96

INTERPUMP
FLUID SOLUTIONS

Powered by I.M.M. Hydraulics

I.M.M. HYDRAULICS

I.M.M. Hydraulics Spa
interpumpfluidsolutions.com

Via Italia, 49-51
66041 - Atessa (Ch) - Italy
T. +39 (0) 0872 889225
F. +39 (0) 0872 889226

INTERPUMP GROUP

CAT-IFS-H rev. 1.2